


SOLO 20

ACCENT SPOTLIGHT | 48V MULTISYSTEM TRACK

STATIC WHITE



OVERVIEW

Solo 20 is our most powerful spotlight to date, with static white configurations offering delivered outputs exceeding 3,000 lumens of high-quality light. Our light engines are meticulously engineered for specific needs: the ‘Plus’ engine achieves outstanding colour rendition with a typical CRI of 98 and R9 values above 90, and the ‘HE’ (High Efficiency) engine maximizes both output and energy efficiency, making it ideal for meeting stringent regulations such as Part L.

KEY FEATURES

- Specification grade spotlight with minimal design aesthetic
- Concealed hinge allows full 360° locking pan, and 90° Tilt
- 2 Static White light engines to choose between
- Options for ultra high colour quality and efficacy
- Customisable with a range of optical accessories and holders
- Adapted for use with Stucchi Multisystem Evo 48V track

PERFORMANCE SUMMARY

	plus ⁺				HE			
	Narrow	Medium	Wide	V. Wide	Narrow	Medium	Wide	V. Wide
FWHM	14°	22°	35°	49°	21°	28°	41°	51°
Luminous Flux*	1,991 lm	1,845 lm	2,036 lm	1,948 lm	3,108 lm	3,052 lm	3,133 lm	3,076 lm
Peak Intensity	25,452 Cd	14,047 Cd	6,230 Cd	3,074 Cd	20,114 Cd	14,023 Cd	7,224 Cd	4,366 Cd
CCT	2400K 2700K 3000K 3500K 4000K				2700K 3000K			
CRI Min.	CRI 90 CRI 98 CRI 98 CRI 98 CRI 95				CRI 90 CRI 90			
Drive Current	700 mA (LED Current)				800 mA (LED Current)			
Nom. Voltage	48 V				48 V			
Max. Wattage	27.6 W				30.1 W			
Max. Efficacy	82.2 lm/W				116.8 lm/W			
Driver Type	Constant Current Integral				Constant Current Integral			
Class	SELV Class III				SELV Class III			

* Luminous Flux @ 3000K as delivered

ORDERING CODES

Luminaire:

Base Code	Type	Output	CCT	Beam Angle	Voltage	Control	Adapter Finish	Finish
SOL20	-	-	-	-	-	-	-	-
	MU Multisystem Track	PL Plus	24K 2400K*	NR Narrow	48V 48V DC	010G 0-10V Log	WH White	WH White
		HE High Efficiency	27K 2700K	ME Medium		CAS Casambi	BK Black	BK Black
			30K 3000K	WD Wide		DALI DALI		AL Brushed Aluminium
			35K 3500K*	VW Very Wide				RBZ Rubbed Bronze
			40K 4000K*					BR Brushed Brass
								PB Polished Brass

* CCT available with ‘Plus’ Only

LIGHT ENGINE SELECTION

Select from two conciously engineered Static White light engines to best suit your project or application needs:

plus⁺

Precision's 'Plus' light engines offer the best balance between delivered lumens, beam quality and outstanding colour rendition.

- + Increased Lumen Output
- + CRI 98 Typical

HE

Precision's 'High Efficiency' light engines deliver the highest possible lumen values as well as outstanding energy efficiency.


- + Maximum Lumen Output
- + Maximum Energy Efficiency

LIFETIME + ENVIRONMENTAL

At Precision, we design and engineer our products with longevity in mind. Many of the components that make up our light fixtures are both modular, and re-usable, making it possible to service and repair them throughout their life in service. Once our products reach the end of their useful life, it is possible to re-work and renew them in to a new product. We prioritise the use of recyclable materials in both our products and packaging, and encourage our customers to engage responsibly in the correct disposal of any materials we supply.

	plus ⁺	HE
UK PART L		
Part L1A / L1B (Dwellings)	●	●
Part L2A (General)	○	●
Part L2A (Display)	●	●
CIBSE TM65	28.023 Kg/CO2e	
CIBSE TM66	2.4	

DIMENSIONS



MECHANICAL

Location	IP20 Indoor Dry Location Only
Mounting	Surface plate with decorative cover
Adjustability	360° Lockable Pan 90° Tilt
Material	Aluminium 6063 or Brass H59
Weight	0.80 Kg [1.76 lbs] or 1.38 Kg [3.04 lbs]

FINISHES




TRACK 48V PSU SELECTION

Remote | 100W

Input Voltage	230 VAC 50/60 Hz	
Output Voltage	48 VDC	
Driver Type	Remote Constant Voltage	
Location	IP20 Indoor Dry Location Only	
Usage Region	International	

	plus+	HE
Compatability	●	●
Max. Fixtures	4	3
Order Code	PSCV-100-48-N1-MW	PSCV-100-48-N1-MW




			L	W	H
mm			190	52	37
in			7.48	2.05	1.46

Remote | 96W

Input Voltage	120 - 277 VDC	
Output Voltage	48 VDC	
Driver Type	Remote Enclosure Constant Voltage	
Location	IP20 Indoor Dry Location Only	
Usage Region	North America Only	

	plus+	HE
Compatability	●	●
Max. Fixtures	3	3
Order Code	USCV-96-48-N1-SC-EN	PSCV-100-48-N1-MW




			L	W	H
mm			153	76.2	30.5
in			6.0	3.0	1.2

FIXTURE | INTEGRATED DRIVER DATA


Fixture Integrated | 32W | 0-10V

Input Voltage	48 VDC
Dimming Control	0-10V
Min. Dim Level	0.1%
Flicker	No Observable Effect
Driver Type	Integral Constant Voltage
Location	IP20 Indoor Dry Location Only
Hotplug Protection	Yes




Fixture Integrated | 32W | DALI

Input Voltage	48 VDC
Dimming Control	DALI
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible No Observable Effect
Driver Type	Integral Constant Voltage
Location	IP20 Indoor Dry Location Only
Hotplug Protection	Yes



Fixture Integrated | 32W | Casambi


Input Voltage	48 VDC
Dimming Control	Casambi Bluetooth Mesh App Required [7]
Min. Dim Level	0.5%
Flicker	No Observable Effect
Driver Type	Integral Constant Voltage
Location	IP20 Indoor Dry Location Only
Hotplug Protection	Yes



* Integrated driver is non-removable | data provided for information only


PHOTOMETRY DIAGRAMS

Narrow 14° Beam	
FWHM	14°
Delivered Flux	1,991 lm
Peak Intensity	25,452 Cd
UGR	UGR 4.2





1m	0.25m	25452lx	2828fc	0.7ft	3ft
2m	0.49m	6363lx	707fc	1.5ft	6ft
3m	0.74m	2828lx	314fc	2.2ft	9ft
4m	0.98m	1591lx	177fc	2.9ft	12ft
5m	1.23m	1018lx	113fc	3.7ft	15ft
			79fc	4.4ft	18ft

Medium 22° Beam	
FWHM	22°
Delivered Flux	1,845 lm
Peak Intensity	14,047 Cd
UGR	UGR 1.6





1m	0.39m	14047lx	1561fc	1.2ft	3ft
2m	0.78m	3512lx	390fc	2.3ft	6ft
3m	1.17m	1561lx	173fc	3.5ft	9ft
4m	1.56m	878lx	98fc	4.7ft	12ft
5m	1.94m	562lx	62fc	5.8ft	15ft
			43fc	7.0ft	18ft

Wide 35° Beam	
FWHM	35°
Delivered Flux	2,036 lm
Peak Intensity	6,230 Cd
UGR	UGR 3.8



1m	0.63m	6230lx	692fc	1.9ft	3ft
2m	1.26m	1558lx	173fc	3.8ft	6ft
3m	1.89m	692lx	77fc	5.7ft	9ft
4m	2.52m	389lx	43fc	7.6ft	12ft
5m	3.15m	249lx	28fc	9.5ft	15ft
			19fc	11.4ft	18ft

Very Wide 49° Beam	
FWHM	49°
Delivered Flux	1,948 lm
Peak Intensity	3,074 Cd
UGR	UGR 16.2



1m	0.91m	3074lx	342fc	2.7ft	3ft
2m	1.82m	769lx	85fc	5.5ft	6ft
3m	2.73m	342lx	38fc	8.2ft	9ft
4m	3.65m	192lx	21fc	10.9ft	12ft
5m	4.56m	123lx	14fc	13.7ft	15ft
			9fc	16.4ft	18ft

All diagrams and data as measured @ 3000K

PERFORMANCE SCALING BY CCT

CCT	Output Multiplier	CRI Min.	R9 Typ.	TM-30: Rf	TM-30: Rg	Max Lm
2400K	x1.05	CRI 90	61	-	-	2,137 lm
2700K	x0.94	CRI 95	91	-	-	1,913 lm
3000K	x1.00	CRI 95	91	-	-	2,036 lm
3500K	x1.00	CRI 95	91	-	-	2,036 lm
4000K	x1.10	CRI 95	91	-	-	2,239 lm

Digital photometric files available as .LDT format.

Contact your sales rep or visit www.luminii.com for more information.



PHOTOMETRY DIAGRAMS

Narrow | 21° Beam

FWHM	21°
Delivered Flux	3,108 lm
Peak Intensity	20,114 Cd
UGR	UGR 7.6

1m	0.37m	20114lx	2235fc	1.1ft	3ft
2m	0.74m	5029lx	559fc	2.2ft	6ft
3m	1.11m	2235lx	248fc	3.3ft	9ft
4m	1.48m	1257lx	140fc	4.4ft	12ft
5m	1.85m	805lx	89fc	5.6ft	15ft
			62fc	6.7ft	18ft

Medium | 28° Beam

FWHM	28°
Delivered Flux	3,052 lm
Peak Intensity	14,023 Cd
UGR	UGR 5.9

1m	0.50m	14023lx	1558fc	1.5ft	3ft
2m	1.00m	3506lx	390fc	3.0ft	6ft
3m	1.50m	1558lx	173fc	4.5ft	9ft
4m	1.99m	876lx	97fc	6.0ft	12ft
5m	2.49m	561lx	62fc	7.5ft	15ft
			43fc	9.0ft	18ft

Wide | 41° Beam

FWHM	41°
Delivered Flux	3,133 lm
Peak Intensity	7,224 Cd
UGR	UGR 7.4

1m	0.75m	7224lx	803fc	2.2ft	3ft
2m	1.50m	1806lx	201fc	4.5ft	6ft
3m	2.24m	803lx	89fc	6.7ft	9ft
4m	2.99m	452lx	50fc	9.0ft	12ft
5m	3.74m	289lx	32fc	11.2ft	15ft
			22fc	13.5ft	18ft

Very Wide | 51° Beam

FWHM	51°
Delivered Flux	3,076 lm
Peak Intensity	4,366 Cd
UGR	UGR 18.9

1m	0.95m	4366lx	485fc	2.9ft	3ft
2m	1.91m	1092lx	121fc	5.7ft	6ft
3m	2.86m	485lx	54fc	8.6ft	9ft
4m	3.82m	273lx	30fc	11.4ft	12ft
5m	4.77m	175lx	19fc	14.3ft	15ft
			13fc	17.2ft	18ft

All diagrams and data as measured @ 3000K

PERFORMANCE SCALING BY CCT

CCT	Output Multiplier	CRI Min.	R9 Typ.	TM-30: Rf	TM-30: Rg	Max Lm
2700K	x0.96	CRI 90	61	-	-	3,007 lm
3000K	x1.00	CRI 90	61	-	-	3,133 lm

Digital photometric files available as .LDT format.
Contact your sales rep or visit www.luminii.com for more information.

DC251119

RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

7

PRODUCT ANATOMY




- 1 High Intensity Single-Source LED
- 2 Permanently Installed Base Optic
- 3 Interchangeable Ø66mm MICROLENS Optic
- 4 Integral Single Accessory Holder
- 5 Range of Optical Accessories
- 6 Accessory Retention Clip



- 1 High Output COB Light Engine
- 2 Interchangeable TIR Optic
- 3 Integral Double Accessory Holder
- 4 Range of Optical Accessories
- 5 Accessory Retention Clip

INTEGRATED ACCESSORY HOLDERS




Single Accessory Holder

Built-in to Solo 20 Intense only

Accessory Dia. Ø68mm | Ø2.68"

Capacity 3.2mm | 0.125" Max. Thickness




Double Accessory Holder

Built-in to Solo 20 Plus & HE only

Accessory Dia. Ø68mm | Ø2.68"


Capacity 5.0mm | 0.2" Max Thickness

GLARE GUARD ACCESSORY HOLDER




The Glare Guard Accessory Holder is an angled, snap-in snoot extension capable of holding a range of optical accessories, including honeycombs, gels, and beam shaping optics such as Wallwash and Linear Spread Lenses. The holder comprises of two halves, a front compartment and a rear compartment. The rear compartment is capable of holding a single accessory, whilst the the front compartment is used to hold orientation dependent beam shaping optics such as the Wallwash and Linear Spread lens.

	a. Front Compartment	b. Rear Compartment
Accessory Diameter	Ø66 mm 2.60"	Ø68 mm 2.67"
Capacity	1.2mm 0.05" Max. Thickness	3.2mm 0.125" Max. Thickness
Orientation Indexing	Yes - Alignment Notches	No
Weight	Aluminium: 114g Brass: 287g	
Ordering Codes*		
 Black	1120-GLR-01-BK	 Polished Brass 1120-GLR-02-PB
 Traffic White	1120-GLR-01-TW	 Brushed Brass 1120-GLR-02-SB
 Brushed Aluminium	1120-GLR-01-AL	 Rubbed Bronze 1120-GLR-02-RB




Orientation Indexing

For optical accessories that require a specific orientation, use their alignment notches to position them correctly within the Glare Guard Accessory Holder. Ensure that discs are installed with their textured side facing inwards towards LED.



Wallwash Fixture Angle

For optimum performance, the fixture should be angled at approx. 30° from the vertical plane.



Wallwash Positioning and Pitch

Wallwash fixtures should be positioned one-third of the ceiling height away from the wall and spaced apart by the same distance.



plus⁺

WALLWASH PHOTOMETRY





- Recommended wall height is 3.0 m / 9.84 ft
- Recommended set back and fixture spacing is 1.00 m / 3.28 ft
- Recommended base optics are Narrow 14°, Medium 22° or Wide 35°
- The Wallwash Disc **HKFD-68-WAS-1** can only be used in combination with the Glare Guard Accessory Holder **1120-GLR-XX-XX**
- Follow the set back and fixture spacing rules outlined on page 10 - results may vary depending on your application



Base Optic	Narrow (14°)
Distribution Angle	23° x 51°
Delivered Flux	1,444 lm
Peak Intensity	3,295 Cd
Efficiency	58.2 lm/W
Efficiency Multiplier	x 0.73






Base Optic	Medium (22°)
Distribution Angle	28° x 54°
Delivered Flux	1,488 lm
Peak Intensity	2,880 Cd
Efficiency	60.0 lm/W
Efficiency Multiplier	x 0.80



Base Optic	Wide (35°)
Distribution Angle	36° x 57°
Delivered Flux	1,588 lm
Peak Intensity	2,294 Cd
Efficiency	64.0 lm/W
Efficiency Multiplier	x 0.78



Base Optic	Very Wide (49°)
Distribution Angle	47° x 62°
Delivered Flux	1,340 lm
Peak Intensity	1,531 Cd
Efficiency	54.0 lm/W
Efficiency Multiplier	x 0.69




Digital photometric files available as .LDT format.
Contact your sales rep or visit www.luminii.com for more information.







WALLWASH PHOTOMETRY





- Recommended wall height is 3.0 m / 9.84 ft
- Recommended set back and fixture spacing is 1.00 m / 3.28 ft
- Recommended base optics are Narrow 21°, Medium 28° or Wide 41°
- The Wallwash Disc **HKFD-68-WAS-1** can only be used in combination with the Glare Guard Accessory Holder **1120-GLR-XX-XX**
- Follow the set back and fixture spacing rules outlined on page 10 - results may vary depending on your application



Base Optic	Narrow (21°)
Distribution Angle	27° x 51°
Delivered Flux	1,820 lm
Peak Intensity	3,773 Cd
Efficiency	67.6 lm/W
Efficiency Multiplier	x 0.59





Base Optic	Medium (28°)
Distribution Angle	31° x 52°
Delivered Flux	1,915 lm
Peak Intensity	3,425 Cd
Efficiency	71.2 lm/W
Efficiency Multiplier	x 0.63



Base Optic	Wide (41°)
Distribution Angle	40° x 57°
Delivered Flux	2,061 lm
Peak Intensity	2,778 Cd
Efficiency	76.6 lm/W
Efficiency Multiplier	x 0.66



Base Optic	Very Wide (51°)
Distribution Angle	47° x 61°
Delivered Flux	1,739 lm
Peak Intensity	1,983 Cd
Efficiency	64.6 lm/W
Efficiency Multiplier	x 0.56



Digital photometric files available as .LDT format.
Contact your sales rep or visit www.luminii.com for more information.



SNOOT ACCESSORY HOLDER



The Snoot Accessory Holder (sold separately) enhances the Solo 20's optical accessory capacity while adding decorative trim in a variety of complementary finishes. Its snap-in, snap-out mechanism is completely tool-free, making on-site adjustments simple and ensuring the holder fits flush with the snoot's front edge.

Accessory Diameter	Ø68 mm 2.67"
Capacity	3.2mm 0.125" Max. Thickness
Orientation Index	No
Weight	Aluminum 31g Brass 91g

Ordering Codes*

 Black	1120-HOL-01-BK	 Polished Brass	1120-HOL-02-PB
 Traffic White	1120-HOL-01-TW	 Brushed Brass	1120-HOL-02-SB
 Brushed Aluminium	1120-HOL-01-AL	 Rubbed Bronze	1120-HOL-02-RB



*Optical accessories ordered separately







Ø68MM LINEAR SPREAD LENS



- Linear Disc **HKFD-68-LIN** is a microprismatic PMMA lens that can be used to create asymmetric linear beam effects
- Although it fits in Solo 20's integral accessory holder, it is recommended to be used in conjunction with the Snoot Accessory Holder **1120-HOL-01-XX** to reduce beam clipping
- Using narrower base optics will produce a longer, thinner beam
- The beam is spread perpendicular to the disc's vertical stripes

► intense ◀	Ultra Narrow (6°)	Narrow (16°)	Wide (31°)	Very Wide (48°)	
	Distribution Angle	7° x 38°	16° x 39°	29° x 41°	43° x 49°
	Delivered Flux	893 lm	772 lm	686 lm	599 lm
	Peak Intensity	10,213 Cd	3,390 Cd	1,486 Cd	807 Cd
Efficiency	51.0 lm/W	44.1 lm/W	39.2 lm/W	34.2 lm/W	
Efficiency Multiplier	x 0.82	x 0.90	x 0.79	x 0.82	
plus ⁺	Narrow (14°)	Medium (22°)	Wide (35°)	Very Wide (49°)	
	Distribution Angle	15° x 39°	20° x 38°	31° x 41°	41° x 46°
	Delivered Flux	1,703 lm	1,726 lm	1,814 lm	1,537 lm
	Peak Intensity	7,901 Cd	5,877 Cd	4,122 Cd	2,423 Cd
Efficiency	68.7 lm/W	69.6 lm/W	73.1 lm/W	62.0 lm/W	
Efficiency Multiplier	x 0.86	x 0.94	x 0.89	x 0.79	
HE	Narrow (21°)	Medium (28°)	Wide (41°)	Very Wide (51°)	
	Distribution Angle	20° x 39°	25° x 39°	36° x 42°	45° x 48°
	Delivered Flux	2,295 lm	2,324 lm	2,521 lm	2,256 lm
	Peak Intensity	7,864 Cd	6,599 Cd	4,911 Cd	3,207 Cd
Efficiency	85.3 lm/W	86.4 lm/W	93.7 lm/W	83.9 lm/W	
Efficiency Multiplier	x 0.73	x 0.76	x 0.80	x 0.82	

OPTICAL ACCESSORIES

SPARE OPTICS	 Narrow TIR Optic For Solo 20 Plus & HE Only HKHG-68-15-PMMA	 Medium TIR Optic For Solo 20 Plus & HE Only HKHG-68-24-PMMA	 Wide TIR Optic For Solo 20 Plus & HE Only HKHG-68-36-PMMA	 Very Wide TIR Optic For Solo 20 Plus & HE Only HKHG-68-50-PMMA
GLARE CONTROL	 Ø68 Honeycomb Louvre Ø68 x 3.2mm Ø2.67 x 0.125" Fits all accessory holders 995-68-BK			
BEAM MODIFIERS	 Ø68 Linear Spread Lens Ø68 x 3.0mm Ø2.67 x 0.12" Fits all accessory holders HKFD-68-LIN	 Ø66 Linear Spread Lens Ø66 x 1.2mm Ø2.60 x 0.05" <i>For Glare Guard Accessory only</i> HKFD-68-LIN-1	 Ø66 Wallwash Lens Ø66 x 1.2mm Ø2.60 x 0.05" <i>For Glare Guard Accessory only</i> HKFD-68-WAS-1	
COLOUR MODIFIERS	 Ø68 1/4 CTO Filter Ø68 x 1.75mm Ø2.67 x 0.07" Fits all accessory holders Contact Sales Rep	 Ø68 1/2 CTO Filter Ø68 x 1.75mm Ø2.67 x 0.07" Fits all accessory holders Contact Sales Rep	 Ø68 Custom Colour Filter Ø68 x 1.75mm Ø2.67 x 0.07" Fits all accessory holders Contact Sales Rep	