





## Features

- 24VDC Class 2 fixtures made to order up to 144".
- Comes with 8ft silver adjustable cable
- Class two listed for damp locations.
- Dot free even illumination with frosted lens
- Proprietary strong bond solder method handles up to 50 lbs of pull force on wire leads and connectors.
- Average Life (L70): 50,000hrs
- 7 year warranty
- Tunable White allows individual control of CCT and output, can be paired with Vintage Dim power supply for warm dim effect.
- Warm Dim follows the incandescent dimming curve and is compatible with MLV, ELV, and Incandescent dimmers.
- RGB offers balanced output across the color gamut and a true white with RGBW
- Smart Pixel allows for infinite color combinations with cascading and chasing effects.




**Finish Options** (see page 2 for additional information)

| | | | | | |
|---|---|---|---|---|---|
| Base | Silver Anodized | | | | |
| Powder Coat | Black | Bronze | White | | |
| Premium | Matte Black | Warm Nickel | Aged Brass | Polished Gold | Chrome |

## Technical Information

| TYPE | Warm Dim | | | Tunable White | | | | RGB | | RGBW | | Pixel | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTPUT OPTIONS | WD51 (18K-30K) | | | TW51 (27K-65K) | | | | RGB42 | | RGBW36 | | RGBX18 | RGBWX18 |
| | SO | HO | VHO | SO | HO | VHO | X2VHO | SO | HO | SO | HO | SO | SO |
| Lumens Output (All On w/ Frosted Lens) | 117 lm/ft | 246 lm/ft | 351 lm/ft | 261 lm/ft | 323 lm/ft | 438 lm/ft | 575 lm/ft | 131 lm/ft | 192 lm/ft | 132 lm/ft | 219 lm/ft | 105 lm/ft | 159 lm/ft |
| Average Power Consumption (for a 4' section) | 2.3 W/ft | 4.7 W/ft | 6.9 W/ft | 4.4 W/ft | 5.4 W/ft | 7.6 W/ft | 9.5 W/ft | 4.5 W/ft | 8.3 W/ft | 4 W/ft | 7.6 W/ft | 4.5 W/ft | 5.7 W/ft |
| Efficacy | 51 lm/W | 52 lm/W | 51 lm/W | 59 lm/W | 60 lm/W | 58 lm/W | 61 lm/W | 29 lm/W | 23 lm/W | 33 lm/W | 29 lm/W | 23 lm/W | 28 lm/W |
| Max Run Length (in series) | 37 ft | 22 ft | 15 ft | 27.9 ft | 22 ft | 15 ft | 11.9 ft | 28ft | 14ft | 26ft | 13ft | 30ft | 20ft |
| Ambient Operating Temperature Range* | -4°F – 122°F (-20°C – 50°C) | | -4°F – 113°F (-20°C – 45°C) | -4°F – 122°F (-20°C – 50°C) | | -4°F – 104°F (-20°C – 40°C) | -4°F – 86°F (-20°C – 30°C) | -4°F – 122°F (-20°C – 50°C) | -4°F – 104°F (-20°C – 40°C) | -4°F – 122°F (-20°C – 50°C) | -4°F – 104°F (-20°C – 40°C) | -4°F – 122°F (-20°C – 50°C) | -4°F – 122°F (-20°C – 50°C) |
| Control/Dimming Protocol | 0–10V, DALI, DALI2, MLV (Triac), ELV, Incandescent | | | 0–10V, DMX, DALI-DT8 | | | | DMX, DALI-DT8 | | DMX, DALI-DT8 | | SPI Protocol UCS 2903 | SPI Protocol UCS 2904 |

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

**Warm Dim (WD51)**

| CCT | | Multiplier (ref. - 18K30K) | TM-30 CRI | $R_f$ | $R_g$ | $R_9$ |
|---|---|---|---|---|---|---|
| 18K24K | 1800K | 0.90 | 92 | 85 | 91 | 86 |
| | 2400K | | 96 | 95 | 104 | 97 |
| 18K27K | 1800K | 0.97 | 92 | 85 | 91 | 86 |
| | 2700K | | 96 | 95 | 104 | 96 |
| 18K30K | 1800K | 1.00 | 92 | 85 | 91 | 86 |
| | 3000K | | 95 | 95 | 104 | 90 |

**Tunable White (TW51)**

| CCT | | Multiplier (ref. - 27K65K) | TM-30 CRI | $R_f$ | $R_g$ | $R_9$ |
|---|---|---|---|---|---|---|
| 18K30K | 1800K | 0.78 | 92 | 85 | 91 | 86 |
| | 2400K | | 95 | 93 | 106 | 98 |
| | 3000K | | 97 | 94 | 104 | 95 |
| 27K65K | 2700K | 1.00 | 97 | 95 | 103 | 93 |
| | 4200K | | 96 | 93 | 105 | 95 |
| | 6500K | | 91 | 90 | 101 | 63 |

**RGBW (3000K)**

| Tape | TM-30 CRI | $R_f$ | $R_g$ | $R_9$ |
|---|---|---|---|---|
| RGBW36 | 95 | 93 | 106 | 84 |
| RGBWX18 | 93 | 91 | 99 | 64 |

**Dominant Wavelength**

| Color | RGB42/ RGBW36 | RGBX18/ RGBWX18 |
|---|---|---|
| Red | 620nm | 621nm |
| Green | 525nm | 519nm |
| Blue | 467nm | 465nm |

## Ordering Code

MODEL - LENGTH[1] - OUTPUT[2] - CCT - LENS - MOUNTING - FINISH[3,4] - POWER FEED

MODEL: CLS - Clareo S; CLQ - Clareo Q

LENGTH[1]: 12"–144" 2" increments; 12"–144" 4" increments

OUTPUT[2] / CCT:
- WD51SO - Standard, WD51HO - High, WD51VHO - Very High → 18K24K 1800K - 2400K; 18K27K - 1800K - 2700K; 18K30K 1800K - 3000K
- TW51SO - Standard, TW51HO - High, TW51VHO - Very High, TW51X2VHO - Very High → 18K30K - 1800K - 3000K; 27K65K - 2700K - 6500K
- RGBW36SO - Standard, RGBW36HO - High, RGB42SO - Standard, RGB42HO - High → CLR - Color
- RGBWX18SO - Standard, RGBX18SO - Standard → PXSPI - Smart Pixel Control

LENS: F - Frosted


MOUNTING: S - Straight; P - Sloped

FINISH[3,4]:
- BASE: SA - Silver Anodized
- POWDER COAT: BK - Black; BZ - Bronze; WH - White
- PREMIUM: MBK - Matte Black; WN - Warm Nickel; AB - Aged Brass; PG - Polished Gold[5]; CH - Chrome[5]


POWER FEED: R - Remote power supply

1 - Custom lengths and increments are available, please consult Inside Sales with specific request.
2 - Warm Dim and Tunable White options can be used to comply with Title 24 JA8 at max brightness depending on Lens selection, see multiplier charts to calculate specific efficacy.
3 - Non Base finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
4 - White canopy included with all finishes except Black and Matte Black, which includes a Black canopy.
5 - Polished Gold finishes and Chrome finishes have a maximum fixture length of 96".


## Product Dimensions





Clareo S




Clareo Q




**Canopy Options**





## Finish Options

- Finish options are available in a wide variety, allowing for complete customization of style and aesthetic.
- Non Base finishes may have extended lead times and price adder.
- Polished Gold and Chrome finishes have a maximum fixture length of 96".
- Custom RALs are available, please consult Inside Sales with specific request.




**Silver Anodized** *Base*

Silver Anodized is a soft silver with a clear finish.




**Black** *Powder Coat*

Black is a true deep black with a glossy finish.




**Bronze** *Powder Coat*

Bronze is a rich, dark brown with a satin finish.



**White** *Powder Coat*

White is a polar bright white and field paintable.




**Matte Black** *Premium*

Matte Black is a dark, pitch-black with a soft flat finish.




**Warm Nickel** *Premium*

Warm Nickel is a soft, silvery smoke with warm tones and a satin finish.




**Aged Brass** *Premium*

Aged Brass is a deep brown shade with slightly golden undertones.



**Polished Gold** *Premium*

Polished Gold is bright and radiant for a brilliant finish.




**Chrome** *Premium*

Chrome is a highly reflective silver polish.

## Light Transmission and Dotting

| | Lens/Accessory | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Output Options** | **CLQ Frosted Lens** | | | | **CLS Frosted Lens** | | | |
| **Dimming Level** | 100% | 50% | 10% | 1% | 100% | 50% | 10% | 1% |
| WD51SO | ND | ND | ND | ND | ND | ND | ND | ND |
| WD51HO | ND | ND | ND | ND | ND | ND | ND | ND |
| WD51VHO | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51SO (All On) | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51HO (All On) | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51VHO (All On) | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51SO (1 CH) | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51HO (1 CH) | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51VHO (1 CH) | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51X2VHO (All On) | ND | ND | ND | ND | ND | ND | ND | ND |
| TW51X2VHO (1 CH) | ND | ND | ND | ND | ND | ND | ND | ND |
| RGBW36SO | ND | ND | ND | ND | ND | ND | ND | ND |
| RGBW36HO | ND | ND | ND | ND | ND | ND | ND | ND |
| RGB42SO | ND | ND | ND | ND | ND | ND | ND | ND |
| RGB42HO | ND | ND | ND | ND | ND | ND | ND | ND |
| RGBWX18SO | SD | SD | SD | CD | SD | SD | SD | CD |
| RGBX18SO | SD | SD | SD | CD | SD | SD | SD | CD |
| **Transmission Percentage** | 100% | | | | 100% | | | |



**CD** - Clear Dotting

**SD** - Slight Dotting

**ND** - No Dotting

Use complete Dotting Chart Tool online for more dotting information

I'm also click-able

## Power Consumption

Please visit the link/QR code below to access the Luminii Power Consumption Chart tool on our website.

There you will be able to select your fixture, ouput, and desired power feed to get a full power consumption table.

I'm also click-able

Desired Nominal Length: _____

Desired Output: _____

Desired CCT: _____

## Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

| Wattage [W] | Maximum Wire Length From Power Supply to Start of Run [ft] | | | | | | |
|---|---|---|---|---|---|---|---|
| | 12 AWG | 14 AWG | 16 AWG | 18 AWG | 20 AWG | 22 AWG | 24 AWG |
| **5** | 1088.2 | 684.4 | 430.3 | 270.6 | 170.2 | 107.1 | 67.3 |
| **10** | 544.1 | 342.2 | 215.1 | 135.3 | 85.1 | 53.5 | 33.7 |
| **15** | 362.7 | 228.1 | 143.4 | 90.2 | 56.7 | 35.7 | 22.4 |
| **20** | 272.0 | 171.1 | 107.6 | 67.7 | 42.6 | 26.8 | 16.8 |
| **25** | 217.6 | 136.9 | 86.1 | 54.1 | 34.0 | 21.4 | 13.5 |
| **30** | 181.4 | 114.1 | 71.7 | 45.1 | 28.4 | 17.8 | 11.2 |
| **35** | 155.5 | 97.8 | 61.5 | 38.7 | 24.3 | 15.3 | 9.6 |
| **40** | 136.0 | 85.5 | 53.8 | 33.8 | 21.3 | 13.4 | 8.4 |
| **45** | 120.9 | 76.0 | 47.8 | 30.1 | 18.9 | 11.9 | 7.5 |
| **50** | 108.8 | 68.4 | 43.0 | 27.1 | 17.0 | 10.7 | 6.7 |
| **55** | 98.9 | 62.2 | 39.1 | 24.6 | 15.5 | 9.7 | 6.1 |
| **60** | 90.7 | 57.0 | 35.9 | 22.6 | 14.2 | 8.9 | 5.6 |
| **65** | 83.7 | 52.6 | 33.1 | 20.8 | 13.1 | 8.2 | 5.2 |
| **70** | 77.7 | 48.9 | 30.7 | 19.3 | 12.2 | 7.6 | 4.8 |
| **75** | 72.5 | 45.6 | 28.7 | 18.0 | 11.3 | 7.1 | 4.5 |
| **80** | 68.0 | 42.8 | 26.9 | 16.9 | 10.6 | 6.7 | 4.2 |
| **85** | 64.0 | 40.3 | 25.3 | 15.9 | 10.0 | 6.3 | 4.0 |
| **90** | 60.5 | 38.0 | 23.9 | 15.0 | 9.5 | 5.9 | 3.7 |
| **96** | 56.7 | 35.6 | 22.4 | 14.1 | 8.9 | 5.6 | 3.5 |

## Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

### For use with Warm Dim

#### Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC


| MODEL | | INPUT CONTROL | | WATTAGE | | OUTPUT |
|---|---|---|---|---|---|---|
| | – | | – | | – | |
| **PS** - Power Supply, 120-277VAC | | **UNI** - 0-10V Dimming (0.1%), Phase Dimming (0.1%) | | **30** - 30 Watts<br>**60** - 60 Watts<br>**96** - 96 Watts<br>**3x96** - 3x96 Watts | | **24** - 24 VDC |

**Compatibility:** View a complete list of compatible dimmers on the PS-UNI product page.


**0-10V - 0.1% dimming**
**MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart**

| MODELS | PS-UNI-30W | PS-UNI-60W | PS-UNI-96W | PS-UNI-3X96W |
|---|---|---|---|---|
| **Length** | 6.50" | 7.40" | 8.66" | 11.85" |
| **Width** | 3.73" | 3.73" | 3.73" | 4.32" |
| **Depth** | 1.61" | 1.61" | 1.61" | 1.81" |

PS-UNI-30/60/96





PS-UNI-3X96




#### Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

| MODEL | | INPUT CONTROL | | ENVIRONMENT | | WATTAGE | | OUTPUT |
|---|---|---|---|---|---|---|---|---|
| | - | | - | | - | | - | |
| **PS** - Power Supply, 120-277VAC | | **DALI2-DT6** - DALI2 DT6 (0.1%) | | **D** - Dry | | **96** - 96 Watts | | **24** - 24 VDC |




| Model | 96W |
|---|---|
| **Length** | 14.40" |
| **Width** | 5.20" |
| **Depth** | 2.60" |


## Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

### For use with Warm Dim


#### Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

| MODEL | INPUT CONTROL | ENVIRONMENT | WATTAGE | OUTPUT |
|---|---|---|---|---|
| PS - Power Supply, 120-277VAC | 010V-LIN - 0-10V Dimming (0.1%), Linear<br>010V-LOG - 0-10V Dimming (0.1%), Logarithmic | D - Dry | 96 - 96 Watts<br>3x96 - 3x96 Watts | 24 - 24 VDC |




| MODELS | 96W | 3X96 |
|---|---|---|
| Length | 14.40" | 15.00" |
| Width | 5.20" | 6.62" |
| Depth | 2.60" | 4.45" |


PS-010V-LIN/LOG-D-3X96




#### Ordering Code - Athena 0-10V LED Driver

| MODEL | INPUT CONTROL | ENVIRONMENT | WATTAGE | OUTPUT | FEATURE |
|---|---|---|---|---|---|
| PS - Power Supply, 120-277VAC | 010V-LIN - 0-10V Dimming (0.1%), Linear<br>010V-LOG - 0-10V Dimming (0.1%), Logarithmic | D - Dry | 96 - 96 Watts | 24 - 24 VDC | AWNR - Athena Wireless Node |

PS-010V-LIN/LOG-D-96-ANWR




| MODELS | 96W |
|---|---|
| Length | 14.40" |
| Width | 5.20" |
| Depth | 2.60" |


## Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

### For use with Tunable White

#### Ordering Code - DALI2 Dimming Power Supplies 0.1% 120VAC - 277VAC


| MODEL | INPUT CONTROL | ENVIRONMENT | WATTAGE | OUTPUT |
|---|---|---|---|---|
| PS - Power Supply, 120-277VAC | DALI2-DT8 - DALI DT8 Tunable White (0.1%) | D - Dry | 96 - 96 Watts | 24 - 24 VDC |




| MODELS | 96W |
|---|---|
| Length | 14.40" |
| Width | 5.20" |
| Depth | 2.60" |

#### Ordering Code - Athena DALI2 Dimming Power Supplies 0.1% 120VAC - 277VAC


| MODEL | INPUT CONTROL | ENVIRONMENT | WATTAGE | OUTPUT | FEATURE |
|---|---|---|---|---|---|
| PS - Power Supply, 120-277VAC | DALI2-DT8 - DALI DT8 Tunable White (0.1%) | D - Dry | 96 - 96 Watts | 24 - 24 VDC | AWNR - Athena |




| MODELS | 96W |
|---|---|
| Length | 14.40" |
| Width | 5.20" |
| Depth | 2.60" |

#### Ordering Code - DALI2 Dimming Power Supplies 0.1% 120VAC - 277VAC - for Dim-to-Warm functionality with Tunable White Output

| MODEL | INPUT CONTROL | ENVIRONMENT | WATTAGE | OUTPUT |
|---|---|---|---|---|
| PS - Power Supply, 120-277VAC | DALI2-WD - DALI2 DT6 Warm Dim (0.1%) | D - Dry | 96 - 96 Watts | 24 - 24 VDC |




| MODELS | 96W |
|---|---|
| Length | 14.40" |
| Width | 5.20" |
| Depth | 2.60" |

## Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.


### For use with Tunable White


#### Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

| MODEL | | INPUT CONTROL | | ENVIRONMENT | | WATTAGE | | OUTPUT |
|---|---|---|---|---|---|---|---|---|
| | - | | - | | - | | - | |
| PS - Power Supply, 120-277VAC | | DMX - DMX (0.1%) | | D - Dry | | 96 - 96 Watts<br>3X96 - 3X96 Watts | | 24 - 24 VDC |

| MODELS | 96W | 3X96 |
|---|---|---|
| Length | 14.40" | 15.00" |
| Width | 5.20" | 6.62" |
| Depth | 2.60" | 4.56" |


DMX CABLES
(FOR DMX CABLES, USE BELDEN 9829, 9842,OR CAT5 SHIELDED TWISTED PAIR CABLING OR EQUIVALENT)





#### Ordering Code - VintageDim® 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

| MODEL | | INPUT CONTROL | | ENVIRONMENT | | WATTAGE | | OUTPUT |
|---|---|---|---|---|---|---|---|---|
| | - | | - | | - | | - | |
| PS - Power Supply, 120-277VAC | | 010V-WD - 0 -10V Dimming (0.1%), Standard Warm Dim Curve (with Tunable White LED)<br>010V-TW - 0 -10V Dimming (0.1%), Two Channel Control, Brightness and CCT1-CCT2 Ratio<br>010V-2CH - 0 -10V Dimming (0.1%), Two Channel Control, LED1 Brightness and LED2 Brightness<br>010V-WDX - 0 -10V Dimming (0.1%), Customizable Warm Dim Curve (with Tunable White LED) | | D - Dry | | 96 - 96 Watts<br>3X96 - 3x96 Watts[1] | | 24 - 24 VDC |




1 - 3x96 is only available with input control options 010V-WD and 010V-TW

| MODELS | 96W | 3X96 |
|---|---|---|
| Length | 14.40" | 15.00" |
| Width | 5.20" | 6.62" |
| Depth | 2.60" | 4.56" |



## Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

### For use with RGB/RGBW


#### Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC

| MODEL | | INPUT CONTROL | | WATTAGE | | OUTPUT |
|---|---|---|---|---|---|---|
| | – | | – | | – | |
| PS - Power Supply, 120-277VAC | | UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%) | | 30 - 30 Watts<br>60 - 60 Watts<br>96 - 96 Watts<br>3x96 - 3x96 Watts | | 24 - 24 VDC |


| MODELS | PS-UNI-30W | PS-UNI-60W | PS-UNI-96W | PS-UNI-3X96W |
|---|---|---|---|---|
| Length | 6.50" | 7.40" | 8.66" | 11.85" |
| Width | 3.73" | 3.73" | 3.73" | 4.32" |
| Depth | 1.61" | 1.61" | 1.61" | 1.81" |

REQUIRES A CONTROLLER AND A DECODER TO WORK PROPERLY

PS-UNI-30/60/96




PS-UNI-3X96





### For use with RGB/RGBW

#### Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC


| MODEL | | INPUT CONTROL | | ENVIRONMENT | | WATTAGE | | OUTPUT |
|---|---|---|---|---|---|---|---|---|
| | - | | - | | - | | - | |
| PS - Power Supply, 120-277VAC | | DMX - DMX (0.1%) | | D - Dry | | 96 - 96 Watts<br>3X96 - 3X96 Watts | | 24 - 24 VDC |

| MODELS | 96W | 3X96 |
|---|---|---|
| Length | 14.40" | 15.00" |
| Width | 5.20" | 6.62" |
| Depth | 2.60" | 4.56" |

DMX CABLES
(FOR DMX CABLES, USE BELDEN 9829, 9842 OR CAT5 SHIELDED TWISTED PAIR CABLING OR EQUIVALENT)




PS-DMX-D-3X96-24





### For use with RGB/RGBW/Pixel

#### Ordering Code - Non-Dimming Power Supply 120VAC - 277VAC

| MODEL | | INPUT CONTROL | | ENVIRONMENT | | WATTAGE | | OUTPUT |
|---|---|---|---|---|---|---|---|---|
| | - | | - | | - | | - | |
| PS - PSV Series | | ND - Non Dimming | | D - Dry | | 96 - 96 Watts | | 24 - 24 VDC |

| MODELS | 96W |
|---|---|
| Length | 14.40" |
| Width | 5.20" |
| Depth | 2.60" |




REQUIRES A CONTROLLER AND A DECODER TO WORK PROPERLY

## Controllers and Decoders

### For use with Tunable White Power Supplies



ORDERING CODE

MODEL

**DTW-MC**

DTW-MC - Tunable White controller

Tunable White wall-mount controller controls lighting fixtures, wireless control of TW lighting fixture. Fits in any standard US switch box. Includes all the outputs in the back of the controller.

**Features**

- Switch & dimming control function, control range > 20M.
- Smooth transition between light levels.
- Separately operate dimming and color temperature functions.
- Able to control 1 zone with endless receivers. Each receiver can maximally be controlled by 8 remotes.
- Power, temperature color and dimming functions operated by push button after receivers are connected.

**Operating Voltage**

3V DC battery

**Color Parameters**

- Brightness
- Saturation
- Fading



ORDERING CODE

MODEL

**TW-DMX**

TW-DMX - DMX controller

Tunable White DMX wall-mount controller is a fully touch sensitive controller designed in accordance with standard protocol DMX512. Offers fast and accurate color temperature adjustment and brightness dimming of natural white, warm white and cold white. Designed with a touch color wheel, the DMX512 controller can adjust color temperature and brightness for all white LEDs smoothly and accurately. The DMX controller can control 1 zone with endless decoders.

**Features**

- 1 zone
- 6 color scenes
- DMX Control
- Touch Sensitive Glass Surface
- Dimming and Speed Control
- Memory Function
- Easily Fits Standard US Switch Boxes

**Operating Voltage**

12 - 24V DC

**Color Parameters**

- Brightness
- Saturation
- Primary colors
- Fading
- Color changing speed




ORDERING CODE

MODEL

**SLD-DIMTW**

SLD-DIMTW - Tunable white LED dimming module

The SLD DimTW is a constant voltage warm dimming LED dimming module. The unique dimming module accepts 0-10V control and mimics a smooth, incandescent dimming curve.

**Features**

- Flicker free 0-100% dimming
- High efficiency up to 97%
- High precision dimming ratio:>1:1000
- Fully isolated plastic housing
- Comply with EN55015 and FCC part 15 without additional input filter and capacitors
- compact size, high reliability
- 3 years warranty

**Operating Voltage**

8-48 VDC

## Controllers and Decoders

### For use with Tunable White, RGB/RGBW Power Supplies




Translates controller DMX512 programs for RGB and white LED strips.

Unique DMX address for the decoder can be set easily and displayed by the numeric display on the case. Changing and resetting the DMX address requires manual input.

Use power repeater to expand output.

**Operating Voltage**

12-36 VDC

**Power Capacity**

up to 96W at 24V

**Operating Temperature Range**

from -4°F to +122°F in case

ORDERING CODE

MODEL

| **DDMX-RGBW** |
|---|

**DDMX-RGBW** - DMX decoder

---




The RGBW receiver is easily paired with controller by the click of a button. Receiver can be reset to factory settings at any time.

Each receiver can store one static RGB color, one color sequence, and one brightness setting for the white LED strip. Receivers assigned to the same scene within the same zone will have the same LED static color and color sequence.

**Operating Voltage**

12-36 VDC

**Power Capacity**

up to 96W at 24V

**Operating Temperature Range**

from -4°F to +122°F in case


ORDERING CODE

MODEL

| **RGBW-RC-R** |
|---|

**RGBW-RC-R** - RGBW receiver

---




Extends identical signal when connected in series to an RGBW LED control system. The RGBW signal repeater works with Luminii RGB and RGBW controllers, receivers, and decoders.

RGBW signal can be extended indefinitely when adequate power supply (not included) is connected to the system.

**Operating Voltage**

12-36 VDC

**Power Capacity**

up to 96W at 24V

**Operating Temperature Range**

from -4°F to +122°F in case

ORDERING CODE

MODEL

| **RGBW-SR** |
|---|

**RGBW-SR** - RGBW signal repeater

## Controllers and Decoders

### For use with RGB/RGBW Power Supplies



ORDERING CODE

MODEL

**RGBW-MC3**

RGBW-MC3 - 4-zone RGBW controller

Easy to operate wireless interface suitable for static or color changing scenes. Control 4 different color zones separately or at the same time. RGBW receiver (RGBW-RC-R) required for operation. Assign multiple receivers per zone to cover a large area.

Color wheel enables highly stable and sensitive color control functionality. Create your own color changing sequences with ease and flexibility.

**Power**

qty 3 AAA batteries

**Scenes**

up to 4 unique zones

**Signal**

Wireless (RF)

**Energy Saving**

Deactivates after 10 seconds of inactivity

**Color Parameters**

- Brightness
- Saturation
- Primary colors
- Speed of color changing sequence
- Fading



ORDERING CODE

| MODEL | | ZONES | | COLOR |
|---|---|---|---|---|
| | - | | - | |

DMX - DMX Controller

3Z - Three Zone
1Z - One Zone

RGBW - Red,Green, Blue,& White

DMX /Wireless RGB-W wall-mount controller controls DMX lighting fixtures, wireless control of RGB-W lighting fixture or use both simultaneously. Fits in any standard US switch box. Includes all the outputs in the back of the controller.

Control brightness levels with a single touch, personalize and memorize 3 different scenes, and even create 3 variations of white.

**Features**

- 2 in 1 in-Wall Controller: DMX Control or Wireless RGB-W
- 65,000 Color Options, Dimming and Speed Control
- Memory Function
- 50 Foot Wireless Range
- Easily Fits Standard US Switch Boxes
- Touch Sensitive Glass Surface
- Includes 10 Built in Programs, or Create and Play Your Own


**Operating Voltage**

12 - 24V DC

**Color Parameters**

- Brightness
- Saturation
- Primary colors
- Fading
- Color changing speed

### For use with Tunable White, RGB/RGBW, Pixel Power Supplies



ORDERING CODE

MODEL

**TSDMX-E**

TSDMX-E - Touchscreen DMX controller

Programmable advanced DMX512 lighting controller featuring a touch-screen interface. Operates as stand alone controller or integrated with most architectural lighting control systems. Can controller endless DMX512 enabled devices.

Mounts to standard single or dual gang wall box with the included power supply inside the junction box. Terminal block design for power and data connections.

**Features**

- Sleek glass design which sits 0.43" from the wall
- Graphical color display to show selected environment
- Color/dimmer/speed palette
- Color temperature mixing
- Touch sensitive buttons. No mechanical parts
- Touch sensitive wheel allows for accurate color selection
- Multi-zone microSD memory
- Multi-room control with 500 scenes, 10 zones
- 1024 DMX channels. Control 340 RGB fixtures
- USB & Ethernet connectivity for programming and control

**Power Supply**

7 VDC (included)

**Programmability**

PC, Mac, Tablet, Smartphone

**Output Signal**


DMX512 (1024 channels)

**Color Parameters**

- Brightness
- Saturation
- Speed of color changing sequence
- Fading / dimming / brightness

## Controllers and Decoders

### For use with Tunable White, RGB/RGBW Power Supplies



ORDERING CODE

MODEL

**DALI2-DT8-RGBW**

DALI2-DT8-RGBW - DALI-2 RGBW Decoder

A 4-channel DALI2 DT8 decoder designed to control RGB, RGBW, and TW LED fixtures, featuring adjustable color temperature and customizable lumen output.

Voltage/Frequency
12-36VDC

Max Output Power
4 output channels, 60-180W each

Max Output Current
4 output channels, max of 5A each

Ambient Operating Temperature Range
-20 to 50°C

Environment
Dry (IP20)



ORDERING CODE

MODEL

**DDMX-5CH-RDM-PRO**

DDMX-5CH-RDM-PRO - DMX512 Decoder

DMX512 decoder with RDM functionality features 5 PWM output channels with common anode. High PWM output frequency range allows the product to be used in HD video conferencing spaces.
All DMX products to be installed per DMX512 Standard.

**Power**
96 Watt

**Inputs**
RJ45, XLR-5Pin, Terminal Block

**DMX Channels**
1 to 5 settable

**PWM Output Resolution Ratio**
8 or 16 bit

**PWM Output Frequency**
500Hz - 30KHz

**Output Dimming Curve Gamma Value**
0.1 ~ 9.9




ORDERING CODE

MODEL

**RGBW-WI-R**

RGBW-WI-R - WIFI generator

RGBW-WI-R creates a local network that enables any electronic device (phone, tablet, etc.) to control the RGB/W strip connected to a RGBW-RC-R receiver.


The control functions are achieved through a free application download for Android and iOS devices called REALCOLOR.

**Operating Voltage**
12-36 VDC

**Power Supply**
PI-130-24 (included)

**Operating Temperature Range**
from -4°F to +122°F in case

### For use with Pixel Power Supplies - Pair with PS-ND-96-24



ORDERING CODE

MODEL

**SR-DMX-SPI**

SR-DMX-SPI - Smart Pixel Decoder

The SR-DMX-SPI is a smart LED pixel decoder that controls 12-24V RGB/RGBW pixel LED strips with SPI signal.
Designed with an OLED backlit panel, the pixel controller allows for easy configuration of most settings. Four push buttons provide access to configuration settings through OLED display.

**Features**

- SPI signal output for RGB/RGBW pixel light control
- DMX512 controllable or RF remote controllable. 512 DMX decoding channels
- 35 built in sequences for chasing, changing, and static colors under RF mode
- Works with integrated DMX consoles and sequencing software
- Supports 44 selectable pixel IC protocols including UCS2903 and UCS2904

**Operating Voltage**
DC5V - DC12-24V

**Power capacity**
up to 96W at 24V

**Operating temperature range**
-4°F to +122°F

**Pixel Capacity**
RGB - 170 pixels individually
(3,333 pixels at the same time)
RGBW - 128 RGBW pixels individually
(2,499 pixels at the same time)