EVO S11

PRODUCT OVERVIEW SHORT SNOOT | GLARE GUARD | LONG SNOOT

INTENSE LIGHT ENGINE



KEY FEATURES

Beam Options: 11 | 14 | 18 | 30 | 50
Light Engine Performance: 413lm | 4.20W
Movement: 360 Pan | 180 Tilt
Tool-less field changeable optics
Ultra narrow high intensity beams
Interchangeable accessories
UK Part L1 / L2 (Display) Compliant

OVERVIEW

Evo S11 is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium finishes. It has five site-changeable optics for flexible beam distribution and fully lockable bearing aided pan and tilt. Our 413lm | 4.20W light engine has a max peak intensity of 7259cd. There are 3 snoot options, Short, Glare Guard and Long. An accessory holder is available separately that can accommodate 37mm (1.45") lenses and louvers. The Jack Plug is compatible with Precision Lighting's 24V Jack systems. The onboard 24V DC driver ensures overcurrent protection and is not polarity sensitive. An external AC to 24V DC power supply is required.

PERFORMANCE

	Intense				
	U. Narrow	Narrow	Medium	Flood	W. Flood
FWHM	11°	14°	18°	30°	50°
Luminous Flux	396 lm	413 lm	391 lm	322 lm	317 lm
Peak Intensity	7259 cd	5422 cd	3338 cd	1052 cd	383 cd
CCT	2700K | 3000K | 3500K | 4000K				
CRI Min.	92 | 92 | 92 | 90				
LED Current	0.350 A				
Voltage	24 V				
Input Wattage	4.8 W				
Efficacy	98.3 lm/W				
Driver Type	Constant Voltage | Remote AC to 24VDC				
Class	SELV | Class III				

ORDER CODE

Model	Type	Shape	Output	CCT	Beam Angle	Finish
EVOS11 *Evo S11*	**MJ** *No mounting* [2]	**SN** *Short Snoot*	**IO** *Intense Output*	**27K** *2700K*	**UN** *Ultra Narrow 11°*	**WH** *White*
	FMJ *Flat Monopoint*	**LN** *Long Snoot*		**30K** *3000K*	**NR** *Narrow 14°*	**BK** *Black*
	SMJ *Surface Monopoint*	**GL** *Glare Guard*		**35K** *3500K*	**ME** *Medium 18°*	**AL** *Br. Aluminium*
	NMJ *Node Monopoint*			**40K** *4000K*	**FL** *Flood 30°*	
	TMJ *Trimless Monopoint*				**WF** *Wide Flood 50°*	
	BT *Basis Track* [1]					
	BTW *Basis Track Wall* [1]					

Example code: EVOS11-MJ-SN-IO-27K-UN-WH

[1] BT and BTW are available for AL and RBZ only [2] MJ requires the specification of a separate mounting point. [3] Evo S is not available in RBZ, BR or PB finishes

See Drivers, Power Supplies and Accessories sections for further order codes

RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

EVO S11

LIGHT ENGINE SELECTION

This product is available with our Intense static white light engine option outlined below.

▸ intense ◂

Precisions signature intense light engines offer tight, surgical beams combined with the highest peak intensity values available.

- Ultra-tight beams
- High Peak Cd

LIFETIME & ENVIRONMENTAL


At Precision, we design and engineer our products with longevity in mind. Many of the components that make up our light fixtures are both modular and re-usable, making it possible to service and repair them throughout their life in service. Once our products reach the end of their useful life, it is possible to re-work and renew them in to a new product. We prioritise the use of recyclable materials in both our products and packaging, and encourage our customers to engage responsibly in the correct disposal of any materials we supply.

CIBSE TM65	12.76 Kg/CO2e
CIBSE TM66	2.4
RoHS Compliance	Yes
REACH Compliance	Yes
WEEE Compliance	Yes - Registered Producer
Declare	Declared
Lifetime	L90B10 100,000hrs
Warranty	5 Years


UK PART L	
Part L1A / L1B (Dwellings) *≥75 lm/W source lumens*	*Compliant 105 lm/W* *Source lm (441 lm) / Source W (4.20 W)*
Part L2A (General) *≥95lm/W delivered lumens*	-
Part L2A (Display) *≥80 lm/W source lumens*	*Compliant 105 lm/W* *Source lm (441 lm) / Source W (4.20 W)*

RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK


DIMENSIONS



EVO 16
SHORT SNOOT



EVO 16
GLARE GUARD



EVO 16
LONG SNOOT

MECHANICAL

Location	IP20 | Indoor Dry Location Only	**Cutout**	N/A
Mounting	Basis Track | 24V Monopoints	**Ceiling Thickness**	N/A
Adjustability	360 Pan | 180 Tilt	**Product Class**	SELV | Class III
Lockable	Pan & Tilt	**Material**	Machined AL 6063-T6
Accessories	Snoots | Louver | Lenses	**Weight**	238g | 0.52lb

FINISHES



White | Black | Brushed Aluminium

EVO S11

DRIVERS & POWER SUPPLIES – UK, EU, MIDDLE EAST, ASIA, PACIFIC

INTENSE LIGHT ENGINE

100W | 0-10V | Remote | Constant Voltage

Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	0-10V
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	12 AWG - 10m (33')



	All CCT's		L	W	H
Max. Lights	1 to 14	**mm**	240	50	34
Order Code	PSCV-100-24-A-OS	**in**	9.45	1.97	1.34

130W | 0-10V | Remote | Constant Voltage

Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	0-10V
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	12 AWG - 10m (33')



	All CCT's		L	W	H
Max. Lights	1 to 16	**mm**	240	63	37
Order Code	PSCV-130-24-A-OS	**in**	9.45	2.48	1.46

100W | DALI-2 | Remote | Constant Voltage

Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	DALI-2
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	12 AWG - 10m (33')



	All CCT's		L	W	H
Max. Lights	1 to 15	**mm**	388	42	30
Order Code	PSCV-100-24-D-EL	**in**	15.28	1.65	1.18

INSTALLATION

To ensure consistent dimming performance when using monopoints, it is recommended to use a 12 AWG / 4 mm² cable. The increased cross-sectional area of 12 AWG / 4 mm² cable minimizes voltage drop between lights, maintaining consistent brightness levels across the entire circuit, especially when dimmed.

Minimize Total Circuit Length:

- To reduce voltage drop, the total length of the lighting circuit should be kept as short as possible.

Close the Loop:

- Arranging the circuit in a U-shape, L-shape, or ring configuration (by joining the first and last lights) helps to balance voltage distribution.
- This technique effectively reduces voltage variation between lights, promoting uniform brightness.

Wiring in a Ring:

- Creating a ring circuit allows current to flow from both ends, significantly reducing the impact of voltage drop along the line.
- This approach is especially beneficial in larger installations or where long cable runs are unavoidable.

Positioning the Power Supply:

- Place the power supply as centrally as possible to reduce voltage drop to the furthest points.
- Consider using multiple supplies for larger installations to maintain consistent voltage.

100W | 0-10V | Remote | Constant Voltage

Input Voltage	120V AC Only | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	0-10V
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	12 AWG - 10m (33')



	All CCT's		L	W	H
Max. Lights	1 to 15	**mm**	550.0	65.0	57.0
Order Code	USCV-100-24-A-MW-ENC	**in**	21.65	2.56	2.24

96W | Phase | Remote | Constant Voltage

Input Voltage	120V AC Only | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	Phase
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	12 AWG - 10m (33')



	All CCT's		L	W	H
Max. Lights	1 to 15	**mm**	380.0	77.0	57.0
Order Code	USCV-96-24-P-LU	**in**	14.96	3.03	2.24

100W | DALI-2 | Remote | Constant Voltage

Input Voltage	120-277V | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	DALI-2
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	12 AWG - 10m (33')



	All CCT's		L	W	H
Max. Lights	1 to 15	**mm**	550	65	57
Order Code	USCV-100-24-D-EL-ENC	**in**	21.65	2.56	2.24

INSTALLATION

To ensure consistent dimming performance when using monopoints, it is recommended to use a 12 AWG / 4 mm² cable. The increased cross-sectional area of 12 AWG / 4 mm² cable minimizes voltage drop between lights, maintaining consistent brightness levels across the entire circuit, especially when dimmed.

Minimize Total Circuit Length:

- To reduce voltage drop, the total length of the lighting circuit should be kept as short as possible.

Close the Loop:

- Arranging the circuit in a U-shape, L-shape, or ring configuration (by joining the first and last lights) helps to balance voltage distribution.
- This technique effectively reduces voltage variation between lights, promoting uniform brightness.

Wiring in a Ring:

- Creating a ring circuit allows current to flow from both ends, significantly reducing the impact of voltage drop along the line.
- This approach is especially beneficial in larger installations or where long cable runs are unavoidable.

Positioning the Power Supply:

- Place the power supply as centrally as possible to reduce voltage drop to the furthest points.
- Consider using multiple supplies for larger installations to maintain consistent voltage.

EVO S11

PHOTOMETRY

INTENSE LIGHT ENGINE

OUTPUT SCALING


CCT	Output Multiplier	CRI	R9 Typ.	TM-30: Rf	TM-30: Rg	Max Lm
2400K	-	-	-	-	-	-
2700K	0.90	92	50	90	99	372
3000K	1.00	92	50	90	99	413
3500K	1.00	92	50	90	99	413
4000K	1.00	90	50	90	98	413


Colour Consistency: 2 SDCM at 2700K / 3000K, 3DCM at 3500 / 4000K


PHOTOMETRY

ULTRA NARROW

FWHM	11°
Delivered Flux	396 lm
Peak Intensity	7259 cd










NARROW

FWHM	14°
Delivered Flux	413 lm
Peak Intensity	5422 cd










MEDIUM

FWHM	18°
Delivered Flux	391 lm
Peak Intensity	3338 cd










FLOOD

FWHM	30°
Delivered Flux	322 lm
Peak Intensity	1052 cd










WIDE FLOOD

FWHM	50°
Delivered Flux	317 lm
Peak Intensity	383 cd












RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK






OPTICS


There are 5 tool-less interchangeable optics, cross reference the text on the optic disc for beam.

Optic Disc	Optic Disc	Optic Disc	Optic Disc	Optic Disc
				
Ultra Narrow Disc	**Narrow Disc**	**Medium Disc**	**Flood Disc**	**Wide Flood Disc**
FWHM 11 deg	FWHM 14 deg	FWHM 18 deg	FWHM 30 deg	FWHM 50 deg
Order Code	**Order Code**	**Order Code**	**Order Code**	**Order Code**
911-01	**911-02**	**911-03**	**911-04**	**911-05**

ACCESSORIES

This product can hold 2 x accessories using the double accessory holder. The kick reflector must be paired with the glare guard snoot. Accessories are pre-installed unless otherwise requested.


Accessory Holder	Accessory Holder	Glare Control	Beam Shaping	Beam Shaping
				
Double Reflector Holder	**Double Accessory Holder**	**Honeycomb Louver**	**Softening Lens**	**Linear Lens**
W43xH40mm | W1.69xH1.57"	W43xH14mm | W1.69xH0.55"	W37xH3.2mm | W1.46xH0.13"	W37xH3.2mm | W1.46xH0.13"	W37xH3.2mm | W1.46xH0.13"
Order Code	**Order Code**	**Order Code**	**Order Code**	**Order Code**
245-BK	**244-BK**	**995-37-BK**	**991-37**	**992-37**

Colour Change	Colour Change
	
1/4 CTO	**Custom Colour Filter**
W37xH1.8mm | W1.46xH0.07"	W37xH1.8mm | W1.46xH0.07"
Order Code	**Order Code**
997-1/4CTO-37	**Contact Sales Rep**

Linear



Softening



1/4 CTO



Honeycomb





Microlens


For on site beam changing

No holder required




Clip

Included with holder



Accessory



Kick Reflector

Can hold 2 accessories

Requires Glare Guard snoot



Double Accesory Holder


Can hold 2 accessories


MOUNTING OPTIONS

BT & BTW - BASIS TRACK

For use with Precision Lighting Basis Track

ADAPTOR CODE	FINISH
BT-01-AL	Brushed Aluminium
BT-01-RB	Rubbed Bronze
BTW-01-AL	Brushed Aluminium
BTW-01-RB	Rubbed Bronze






MPZ - SURFACE MONOPOINT

For blind mounting on solid surfaces

MONOPOINT CODE	FINISH
MPZ-01-AL	Brushed Aluminium
MPZ-01-WH	White RAL 9010
MPZ-01-BK	Black RAL 9005
MPZ-01-RB	Rubbed Bronze
MPZ-01-PB	Polished Brass
MPZ-01-SB	Brushed Brass






MPS - TRIMLESS MONOPOINT

For use with plasterboard / sheetrock
Note: Canopy not standard, for non-trimless install.

MONOPOINT CODE	FINISH
MPS-01-AL	Brushed Aluminium


CANOPY CODE	FINISH
MPS-02-AL	Brushed Aluminium
MPS-02-BK	Black RAL 9005
MPS-02-WH	White RAL 9010



MPY - NODE MONOPOINT

For use in cabinetry
Note: rear access required after install

MONOPOINT CODE	FINISH
MPY-05-AL	Brushed Aluminium
MPY-05-WH	White RAL 9010
MPY-05-BK	Black RAL 9005
MPY-05-RB	Rubbed Bronze
MPY-05-PB	Polished Brass
MPY-05-SB	Brushed Brass





MPX - FLAT MONOPOINT

For use with most mounting surfaces
Note: wiring void required

MONOPOINT CODE	FINISH
MPX-02-AL	Brushed Aluminium
MPX-02-WH	White RAL 9010
MPX-02-BK	Black RAL 9005
MPX-02-RB	Rubbed Bronze
MPX-01-PB	Polished Brass
MPX-01-SB	Brushed Brass

