Hero Ceiling Recessed
LightShift Adjustable Luminaire

glint by luminii

Hero adjustable luminaire with LightShift technology allows for 40 degree tilt and 360 degree pan beam adjustment without moving or rotating the luminaire body. Harmonious integration into the architecture and flexible installation into the tightest spaces. Fixed light emitting face orientation, precision optics, adaptive glare baffle, and advanced anti-reflective materials provide for exceedingly low glare. Available with a wide range of beam characteristics, shapes, colors, and mounting configurations. Hero Recessed easily directs light where its needed without breaking a sweat, or the plane of the ceiling.

Mounting	Non IC and IC new construction	**Dimming**	Phase 1%, 0-10V 1%/0.1%, or DALI 0.1%
Shape	Rounded or rectangular	**Beam Angle**	11°, 14°, 23°, 36°, 44°
Hanger Length	14" to 24" standard, Up to 48" optional	**Location**	Dry and Damp
Ceiling Thickness	Trimless: 1/4" - 2", low-profile trim: 1/2" - 5/8"	**Lifetime**	60,000 hours
Operating Power	120-277 V, 50-60 Hz, power factor > 0.9	**Warranty**	5 years



c UL us LISTED · MADE IN U.S.A · FC · Declare · TITLE 24 JA8 COMPLIANT

Technical Information

MODEL:	Hero
Light Output (3000K)	1290 lm
Efficacy	58 lm/W
Color Temperature	2700K, 3000K, 3500K, 4000K
CRI	92
Wattage	23W
Beam Tilt	Rated to ±40 deg
Beam Pan	Infinite (360 Deg with no stops)

10 LED

CCT	Lumens	CRI	TM-30			CBCP				
		R_a	R_9	R_f	R_g	LS11	LS14	LS23	LS36	LS44
2700K	1220	92	65	89	103	27712	18379	7206	3212	2375
3000K	1290	96	79	94	101	29252	19400	7606	3390	2507
3500K	1335	95	81	94	102	30330	20115	7886	3515	2599
4000K	1390	94	74	92	99	32724	21703	8509	3792	2805

*HO multiplier = 1.2x

BEAM

Name	LS11	LS14	LS23	LS36	LS44
Width (Diameter)	11°	14°	23°	36°	44°
Field Angle	20°	25°	38°	59°	69°

Ordering Code

Fixture

MODEL - TYPE - SHAPE - CCT - OPTIC - FINISH

MODEL	TYPE	SHAPE	CCT	OPTIC	FINISH
HER10 - Hero Adjustable 10 LED[1]	RC - Recessed Mount	RD - Rounded Endcaps SQ - Squared Endcaps[2]	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	LS11 - 11 Degree LightShift LS14 - 14 Degree LightShift LS23 - 23 Degree LightShift LS36 - 36 Degree LightShift LS44 - 44 Degree LightShift	BK - Black

Housing

HOUSING TYPE - MODEL - SHAPE - OUTPUT - TRIM & FINISH - PAN HANGER OPTIONS - DRIVER - VOLTAGE

HOUSING TYPE	MODEL	SHAPE	OUTPUT	TRIM & FINISH	PAN HANGER OPTIONS	DRIVER	VOLTAGE
HNC - Non-IC New Const	HER10 - Hero 10 LED	SQ - Squared Endcaps RD - Rounded Endcaps	SO - Standard Output	TL - Mud Flange	ST - Pan with Standard 24" Bar Hanger BFB - Pan with Butterfly Bracket CBH - Pan with 48" Commercial Bar Hanger	PHSD - Forward/Reverse Phase, 1% Dim, 120V 010S - 0-10V, 1% Dim, 120V/277V 010L - eldoLED, 0-10V, Linear, 0.1% Dim, 120V/277V 010G - eldoLED, 0-10V, Log, 0.1% Dim, 120V/277V DALI - eldoLED, Dali Protocol 2, DT-6, 0.1% Dim, 120V/277V	120 - 120V 277 - 277V
HNR - Non-IC Remodel	HER10 - Hero 10 LED	RD - Rounded Endcaps	SO - Standard Output	TW - Trim White TB - Trim Black	NA - None[2]		

1. Fixture must be ordered with a housing.
2. Pan and hanger will NOT be provided

Product Dimensions

Trimless Non-IC





Trim Non-IC





Product Dimensions

Trimless IC





Trim IC





Shape

RD
Rounded Endcaps



SQ
Squared Endcaps



Trim Finsh

TB
Trim Black

TW
Trim White



TL
Trimless mud-in

Photometry

A-Downlight

B-30 Degree Beam Adjustment



*Beam steering achived with intuitive joystick movement.





















Family