



Features

The KS Channel linear aluminum extrusion has been designed to fit many LED lighting needs. Multiple mounting and lens options allow for great flexibility and adaptability for any application. Extrusion and diffuser lenses are also field cuttable. Substantial aluminum mass in profile provides excellent heat sink for high power LEDs. Channels come with specified Mounting Clips and End Caps.

Finish

Silver anodized, White, Black, Bronze

Diffuser Lens

Polycarbonate, snap-in-place, UV resistant

Mounting


Multiple mounting clip

Warranty

7 Years

Declare. 

Product Dimensions



INCLUDED MOUNTING ACCESSORIES

EXTRUSION LENGTH	MOUNTING CLIPS (ALL TYPES)	ENDCAP PAIR
48"	3	1
72"	3	1
96"	4	1
120"	4	1
144"	5	1

Each pair of endcaps includes 1x H3 (no wire feed hole) and 1x H4 (with hole) where applicable. Additional endcaps and mounting clips are available for purchase.

TRANSMISSION PERCENTAGE (COMPARED TO LED TAPE WITHOUT CHANNEL)

LENS	TRANSMISSION %						
	LENS ONLY	BLBK	BLS	BLWH	GSBK	GSS	GSWH
Clear	90%	27%	44%	41%	48%	63%	72%
Medium	85%	26%	42%	38%	46%	60%	68%
Half Frosted	73%	22%	36%	33%	39%	51%	59%
Raised	64%	N/A	N/A	N/A	N/A	N/A	N/A
Flat Frosted	56%	17%	27%	25%	30%	39%	45%
Frosted	58%	18%	28%	26%	31%	40%	47%

More details of the Blade Louver and Glare Shield accessory on page 2. See LED tape spec sheet for lens dotting characteristics & compatibility. Raised lens not compatible with the Blade Louver or Glare Shield. Use complete Dotting Chart Tool online for more dotting information ([Link](#))

Ordering code

MODEL	LENGTH	LENS	MOUNTING ²	FINISH ⁴
KSC - KS Channel	48 - 48"	C - Clear	FC - Fixed Clip	BASE
	72 - 72"	F - Frosted	FC45 - Fixed, Clip 45°	SA - Silver Anodized
	96 - 96" ³	HF - Half Frosted	A - Adjustable Hinge Mounting	POWDER COATED
	120 - 120" ³	M - Medium	EFC - Tamper Resistant Fixed Clip	BK - Black
	144 - 144" ³	R - Raised		BZ - Bronze
		FF - Flat Frosted		WH - White

1 - End Caps are included with channel, one of H3 (no hole) and one of H4 (with hole). Order additional End Caps as necessary.
2 - Mounting Clips are included with channel. Refer to chart above for provided mounting clip quantities.
Order additional Mounting Clips as necessary.

3 - For Channels and lenses over 96", incremental shipping charges will apply.


4 - Powder Coated finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.

All Channels come with a specified set of Mounting Clips and End Caps, see Ordering Code for details. Order additional Mounting Clips and End Caps as necessary.

Mounting Clips

MB-KMSC-XX


Fixed mounting clip
-FC



XX	Color
SA	Silver Anodized
WH	White
BK	Black
BZ	Bronze

MB-KMSC-45-XX


Fixed mounting clip 45°
-FC45



XX	Color
SA	Silver Anodized
WH	White
BK	Black
BZ	Bronze

MB-KMSC-A.-XX


Adjustable mounting clip
-A



XX	Color
SA	Silver Anodized
WH	White
BK	Black
BZ	Bronze

MB-KMSC-EFC-SS


Tamper Resistant Fixed Clip
-EFC



End Caps

EC-KSC-F-H4-XX


End Cap with Powerfeed Opening



NOTE: Endcap compatible with Clear, Frosted, Half-Frosted, and Flat Frosted Lens options

EC-KSC-G-H4-XX


End Cap with Powerfeed Opening



NOTE: Endcap compatible with Medium Lens option only

EC-KSC-R-H4-XX

End Cap with Powerfeed Opening



XX	Color
SA	Silver Anodized
WH	White
BK	Black
BZ	Bronze

NOTE: Endcap compatible with Raised Lens option only

Glare Shield and Blade Louver Accessory

LV-GS-KMSC-24-XX

Glare Shield reduces glare at high angle, field cuttable.
Also available with complete fixture, use ordering code
-GSXX

LV-BL-KMSC-24-XX

Blade Louver reduces glare at high angle in two directions
Also available with complete fixture, use ordering code
-BLXX

