



Features

- 24VDC Class 2 fixtures made to order up to 144". Fixtures can be linked up to 37' depending on output
- Suitable for grazer, surface mount, architectural reveals, handrail, and accent lighting applicaitons.
- Class two listed for damp locations.
- Proprietary strong bond solder method handles up to 50 lbs of pull force on wire leads and connectors.
- Average Life (L70): 50,000hrs
- 7 year warranty
- Warm Dim follows the incandescent dimming curve and is compatible with MLV, ELV, and Incandescent dimmers.
- Tunable White allows individual control of CCT and output, can be paired with Vintage Dim power supply for warm dim effect
- RGB offers balanced output across the color gamut and a true white with RGBW
- Smart Pixel allows for infinite color combinations with cascading and chasing effects





Finish Options (see page 3 for additional information)

Powder Coat: Black, Bronze, White

Premium: Matte Black, Warm Nickel, Aged Brass, Polished Gold, Chrome

Technical Information

TYPE	Warm Dim			Tunable White			RGB		RGBW		Pixel	
OUTPUT OPTIONS	WD51 (18K-30K)			TW51 (27K-65K)			RGB42		RGBW36		RGBX18	RGBWX18
	SO	HO	VHO	SO	HO	VHO	SO	HO	SO	HO	SO	SO
Lumens Output (3000K) (All On w/ Narrow Beam Grazer)	106 lm/ft	223 lm/ft	317 lm/ft	236 lm/ft	293 lm/ft	396 lm/ft	172 lm/ft	253 lm/ft	173 lm/ft	287 lm/ft	138 lm/ft	209 lm/ft
Average Power Consumption (for a 4' section)	2.3 W/ ft	4.7 W/ ft	6.9 W/ ft	4.4 W/ ft	5.4 W/ ft	7.6 W/ ft	4.5 W/ft	8.3 W/ft	4 W/ft	7.6 W/ft	4.5 W/ft	5.7 W/ft
Efficacy	46 lm/W	47 lm/W	46 lm/W	54 lm/W	54 lm/W	52 lm/W	38 lm/W	30 lm/W	43 lm/W	38 lm/W	31 lm/W	37 lm/W
Max Run Length (in series)	37 ft	22 ft	15 ft	27.9 ft	22 ft	15 ft	28ft	14ft	26ft	13ft	30ft	20ft
Ambient Operating Temperature Range*	-4°F – 122°F (-20°C – 50°C)		-4°F – 113°F (-20°C – 45°C)	-4°F – 122°F (-20°C – 50°C)		-4°F – 104°F (-20°C – 40°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 95°F (-20°C – 35°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 104°F (-20°C – 40°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 122°F (-20°C – 50°C)
Control/Dimming Protocol	0–10V, DALI, DALI2, MLV (Triac), ELV, Incandescent			0–10V, DMX, DALI-DT8			DMX, DALI-DT8		DMX, DALI-DT8		SPI Protocol UCS 2903	SPI Protocol UCS 2904

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

Warm Dim (WD51)

CCT		Multiplier (ref. - 18K30K)	TM-30 CRI	R_f	R_g	R_9
18K24K	1800K	0.90	92	85	91	86
	2400K		96	95	104	97
18K27K	1800K	0.97	92	85	91	86
	2700K		96	95	104	96
18K30K	1800K	1.00	92	85	91	86
	3000K		95	95	104	90

Tunable White (TW51)

CCT		Multiplier (ref. - 27K65K)	TM-30 CRI	R_f	R_g	R_9
18K30K	1800K	0.78	92	85	91	86
	2400K		95	93	106	98
	3000K		97	94	104	95
27K65K	2700K	1.00	97	95	103	93
	4200K		96	93	105	95
	6500K		91	90	101	63

RGBW (3000K)

Tape	TM-30 CRI	R_f	R_g	R_9
RGBW36	95	93	106	84
RGBWX18	93	91	99	64

Dominant Wavelength

Color	RGB42/ RGBW36	RGBX18/ RGBWX18
Red	620nm	621nm
Green	525nm	519nm
Blue	467nm	465nm

Ordering Code

MODEL - LENGTH[1] - OUTPUT[2] - CCT - LENS - MOUNTING - FINISH[4] - FEED POSITION LEFT[6] - FEED POSITION RIGHT[6] - ACCESSORIES

MODEL
- KM-BABA - Kendo M BABA

LENGTH[1]
- 12"–144" 2" increments
- 12"–144" 2" increments
- 12"–144" 2" increments
- 12"–144" 4" increments

OUTPUT[2]
- WD51SO - Standard
- WD51HO - High
- WD51VHO - Very High
- TW51SO - Standard
- TW51HO - High
- TW51VHO - Very High
- RGBW36SO - Standard
- RGBW36HO - High
- RGB42SO - Standard
- RGB42HO - High
- RGBWX18SO - Standard
- RGBX18SO - Standard

CCT
- 18K24K - 1800K - 2400K
- 18K27K - 1800K - 2700K
- 18K30K - 1800K - 3000K
- 18K30K - 1800K - 3000K
- 27K65K - 2700K - 6500K
- CLR - Color
- PXSPI - Smart Pixel Control

LENS
- GR - Narrow Beam Grazer

MOUNTING
- FC - Fixed Clip
- A - Adjustable Hinge Mounting
- FC45 - Fixed Clip, 45°
- MAG - Magnetic

FINISH[4]

POWDER COAT
- BK - Black
- BZ - Bronze
- WH - White

PREMIUM
- MBK - Matte Black
- WN - Warm Nickel
- AB - Aged Brass
- PG - Polished Gold[5]
- CH - Chrome[5]

FEED POSITION LEFT[6]

WIRE LEADS (72")
- LWE - Wire End Feed
- LWB - Wire Back Feed
- LWSA - Wire Side A Feed
- LWSB - Wire Side B Feed
- LNPF - No Power Feed

QUICK CONNECTS (4")
- LFE - Female Q/C, End Feed
- LFB - Female Q/C, Back Feed
- LFSA - Female Q/C, Side A Feed
- LFSB - Female Q/C, Side B Feed
- LNPF - No Power Feed

FEED POSITION RIGHT[6]

WIRE LEADS (72")
- RWE - Wire End Feed
- RWB - Wire Back Feed
- RWSA - Wire Side A Feed
- RWSB - Wire Side B Feed
- RNPF - No Power Feed


QUICK CONNECTS (4")
- RFE - Female Q/C, End Feed
- RFB - Female Q/C, Back Feed
- RFSA - Female Q/C, Side A Feed
- RFSB - Female Q/C, Side B Feed
- RNPF - No Power Feed

ACCESSORIES
- ___ - N/A, leave blank
- BLS - Blade louver, Silver
- BLBK - Blade louver, Black
- BLWH - Blade louver, White
- GSS - Glare shield, Silver
- GSBK - Glare shield, Black
- GSWH - Glare shield, White

1 - Custom lengths and increments are available, please consult Inside Sales with specific request.
2 - Warm Dim and Tunable White options can be used to comply with Title 24 JA8 at max brightness depending on Lens selection, see multiplier charts to calculate specific efficacy.
3 - Finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
4 - Polished Gold finishes and Chrome finishes have a maximum fixture length of 96".
5 - LNPF - RNPF is not a valid configuration option

Powerfeeds and Connectors

Power Feed Position Options and Orientation



WIRE LEADS

LWE - Left Wire End Feed
LWB - Left Wire Back Feed
RWE - Right Wire End Feed
RWB - Right Wire Back Feed
LWSA - Left Lead Wire, Side A Feed
LWSB - Left Lead Wire, Side B Feed
RWSA - Right Lead Wire, Side A Feed
RWSB - Right Lead Wire, Side A Feed

QUICK CONNECTS


LFE - Left Female QC End Feed
LFB - Left Female QC Back Feed
RFE - Right Female QC End Feed
RFB - Right Female QC Back Feed
LFSA - Left Female Q/C, Side A Feed
LFSB - Left Female Q/C, Side B Feed
RFSA - Right Female Q/C, Side A Feed
RFSB - Right Female Q/C, Side B Feed

Arrows indicate light directions.
Diagram not representative of mounting options available.


Luminii defines LEFT when the fixture lens is facing upwards. For asymmetric fixtures/lens', Luminii defined LEFT when the lens is facing up and towards the user.

Linking and Extension Cable Options


For use with Warm Dim (WD51):




LMC-70
Male quick-connect long, 2 pin, 70"




EC-48
Female/Female Extension Cable, 2 pin, 48"




FMA
Female to male adapter




For use with Tunable White (TW51), RGB Pixel (RGBX18) and RGBW Pixel (RGBWX18):



MOLEX-CON-LEAD-M-3-48
Molex Male Connector Cable, 3 pin, 48"




MOLEX-JC-F-M-3-48
Female/Male Jumper Cable, 3 pin, 48"




MOLEX-JC-M-M-3-4
Female to Male Adapter, 3 pin, 4"




For use with RGB (RGB42):




MOLEX-CON-LEAD-M-4-48
Molex Male Connector Cable, 4 pin, 48"




MOLEX-JC-F-M-4-48
Female/Male Jumper Cable, 4 pin, 48"




MOLEX-JC-M-M-4-4
Female to Male Adapter, 4 pin, 4"




For use with RGBW (RGBW36):




MOLEX-CON-LEAD-M-5-48
Molex Male Connector Cable, 5 pin, 48"




MOLEX-JC-F-M-5-48
Female/Male Jumper Cable, 5 pin, 48"




MOLEX-JC-M-M-5-4
Female to Male Adapter, 5 pin, 4"




Sample Layout




Product Dimensions




Narrow Beam Grazer Lens




Narrow Beam Grazer Lens with Adjustable Hinged Bracket




Narrow Beam Grazer Lens with Blade Louver or Glare Shield Accesory



Narrow Beam Grazer Lens with 45˚ Mounting Bracket



Narrow Beam Grazer Lens with Fixed Mounting Bracket




Narrow Beam Grazer Lens with Magnetic Fixed Mounting Bracket

Finish Options

- Finish options are available in a wide variety, allowing for complete customization of style and aesthetic.
- Finishes may have extended lead times and price adder.
- Polished Gold and Chrome finishes have a maximum fixture length of 96".
- Custom RALs are available, please consult Inside Sales with specific request.

Black
Powder Coat




Black is a true deep black with a glossy finish.

Bronze
Powder Coat




Bronze is a rich, dark brown with a satin finish.

White
Powder Coat




White is a polar bright white and field paintable.

Matte Black
Premium




Matte Black is a dark, pitch-black with a soft flat finish.

Warm Nickel
Premium




Warm Nickel is a soft, silvery smoke with warm tones and a satin finish.

Aged Brass
Premium




Aged Brass is a deep brown shade with slightly golden undertones.

Polished Gold
Premium



Polished Gold is bright and radiant for a brilliant finish.


Chrome
Premium



Chrome is a highly reflective silver polish.

Light Transmission and Dotting

Output Options	Lens/Accessory: Narrow Beam Grazer			
Dimming Level	100%	50%	10%	1%
WD51SO	CD	CD	CD	CD
WD51HO	CD	CD	CD	CD
WD51VHO	CD	CD	CD	CD
TW51SO (All On)	CD	CD	CD	CD
TW51HO (All On)	CD	CD	CD	CD
TW51VHO (All On)	CD	CD	CD	CD
TW51SO (1 CH)	CD	CD	CD	CD
TW51HO (1 CH)	CD	CD	CD	CD
TW51VHO (1 CH)	CD	CD	CD	CD
RGBW36SO	CD	CD	CD	CD
RGBW36HO	CD	CD	CD	CD
RGB42SO	CD	CD	CD	CD
RGB42HO	CD	CD	CD	CD
RGBWX18SO	CD	CD	CD	CD
RGBX18SO	CD	CD	CD	CD
Transmission Percentage	100%			



CD - Clear Dotting

SD - Slight Dotting


ND - No Dotting

Use complete Dotting Chart Tool online for more dotting information


I'm also click-able

Accessory Options


LV-GS-KMSC-24-XX
Glare Shield reduces glare at high angle, field cuttable. Also available with complete fixture, use ordering code **-GSXX**



LV-BL-KMSC-24-XX
Blade Louver reduces glare at high angle in two directions Also available with complete fixture, use ordering code **-BLXX**



LVSP-4T-BK
Low Voltage, 4 Terminal Splice Box, Black, IP20



XX	Color
WH	White
BK	Black
SL	SIlver

Power Consumption

Please visit the link/QR code below to access the Luminii Power Consumption Chart tool on our website.

There you will be able to select your fixture, ouput, and desired power feed to get a full power consumption table.

I'm also click-able

Desired Nominal Length: _____

Desired Output: _____

Desired CCT: _____

Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
10	544.1	342.2	215.1	135.3	85.1	53.5	33.7
15	362.7	228.1	143.4	90.2	56.7	35.7	22.4
20	272.0	171.1	107.6	67.7	42.6	26.8	16.8
25	217.6	136.9	86.1	54.1	34.0	21.4	13.5
30	181.4	114.1	71.7	45.1	28.4	17.8	11.2
35	155.5	97.8	61.5	38.7	24.3	15.3	9.6
40	136.0	85.5	53.8	33.8	21.3	13.4	8.4
45	120.9	76.0	47.8	30.1	18.9	11.9	7.5
50	108.8	68.4	43.0	27.1	17.0	10.7	6.7
55	98.9	62.2	39.1	24.6	15.5	9.7	6.1
60	90.7	57.0	35.9	22.6	14.2	8.9	5.6
65	83.7	52.6	33.1	20.8	13.1	8.2	5.2
70	77.7	48.9	30.7	19.3	12.2	7.6	4.8
75	72.5	45.6	28.7	18.0	11.3	7.1	4.5
80	68.0	42.8	26.9	16.9	10.6	6.7	4.2
85	64.0	40.3	25.3	15.9	10.0	6.3	4.0
90	60.5	38.0	23.9	15.0	9.5	5.9	3.7
96	56.7	35.6	22.4	14.1	8.9	5.6	3.5

Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

For use with Warm Dim

Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL		INPUT CONTROL		WATTAGE		OUTPUT
	–		–		–	
PS - Power Supply, 120-277VAC		**UNI** - 0-10V Dimming (0.1%), Phase Dimming (0.1%)		**30** - 30 Watts **60** - 60 Watts **96** - 96 Watts **3x96** - 3x96 Watts		**24** - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.


0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart

MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50"	7.40"	8.66"	11.85"
Width	3.73"	3.73"	3.73"	4.32"
Depth	1.61"	1.61"	1.61"	1.81"

PS-UNI-30/60/96




PS-UNI-3X96



Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		**DALI2-DT6** - DALI2 DT6 (0.1%)		**D** - Dry		**96** - 96 Watts		**24** - 24 VDC



Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"


Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

For use with Warm Dim


Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC



MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"


PS-010V-LIN/LOG-D-3X96



Ordering Code - Athena 0-10V LED Driver

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts	24 - 24 VDC	AWNR - Athena Wireless Node

PS-010V-LIN/LOG-D-96-ANWR



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"


Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

For use with Tunable White

Ordering Code - DALI2 Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		DALI2-DT8 - DALI DT8 Tunable White (0.1%)		D - Dry		96 - 96 Watts		24 - 24 VDC



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Ordering Code - Athena DALI2 Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT		FEATURE
	-		-		-		-		-	
PS - Power Supply, 120-277VAC		DALI2-DT8 - DALI DT8 Tunable White (0.1%)		D - Dry		96 - 96 Watts		24 - 24 VDC		AWNR - Athena



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Ordering Code - DALI2 Dimming Power Supplies 0.1% 120VAC - 277VAC - for Dim-to-Warm functionality with Tunable White Output

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		DALI2-WD - DALI2 DT6 Warm Dim (0.1%)		D - Dry		96 - 96 Watts		24 - 24 VDC



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.


For use with Tunable White


Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		DMX - DMX (0.1%)		D - Dry		96 - 96 Watts 3X96 - 3X96 Watts		24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"


DMX CABLES
(FOR DMX CABLES, USE BELDEN 9829, 9842,OR CAT5 SHIELDED TWISTED PAIR CABLING OR EQUIVALENT)






Ordering Code - VintageDim® 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		010V-WD - 0 -10V Dimming (0.1%), Standard Warm Dim Curve (with Tunable White LED) 010V-TW - 0 -10V Dimming (0.1%), Two Channel Control, Brightness and CCT1-CCT2 Ratio 010V-2CH - 0 -10V Dimming (0.1%), Two Channel Control, LED1 Brightness and LED2 Brightness 010V-WDX - 0 -10V Dimming (0.1%), Customizable Warm Dim Curve (with Tunable White LED)		D - Dry		96 - 96 Watts 3X96 - 3x96 Watts[1]		24 - 24 VDC



1 - 3x96 is only available with input control options 010V-WD and 010V-TW

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"



Power Supplies

See fixture and power supply instructions & spec sheet for wiring information. Dimming possible in select models - view Luminii website for list of compatible dimmers.

For use with RGB/RGBW


Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		WATTAGE		OUTPUT
	–		–		–	
PS - Power Supply, 120-277VAC		UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)		30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC


MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50"	7.40"	8.66"	11.85"
Width	3.73"	3.73"	3.73"	4.32"
Depth	1.61"	1.61"	1.61"	1.81"

REQUIRES A CONTROLLER AND A DECODER TO WORK PROPERLY

PS-UNI-30/60/96



PS-UNI-3X96




For use with RGB/RGBW

Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		DMX - DMX (0.1%)		D - Dry		96 - 96 Watts 3X96 - 3X96 Watts		24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

DMX CABLES
(FOR DMX CABLES, USE BELDEN 9829, 9842 OR CAT5 SHIELDED TWISTED PAIR CABLING OR EQUIVALENT)



PS-DMX-D-3X96-24




For use with RGB/RGBW/Pixel

Ordering Code - Non-Dimming Power Supply 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - PSV Series		ND - Non Dimming		D - Dry		96 - 96 Watts		24 - 24 VDC

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"



REQUIRES A CONTROLLER AND A DECODER TO WORK PROPERLY

Controllers and Decoders

For use with Tunable White Power Supplies



ORDERING CODE

MODEL

DTW-MC

DTW-MC - Tunable White controller

Tunable White wall-mount controller controls lighting fixtures, wireless control of TW lighting fixture. Fits in any standard US switch box. Includes all the outputs in the back of the controller.

Features

- Switch & dimming control function, control range > 20M.
- Smooth transition between light levels.
- Separately operate dimming and color temperature functions.
- Able to control 1 zone with endless receivers. Each receiver can maximally be controlled by 8 remotes.
- Power, temperature color and dimming functions operated by push button after receivers are connected.

Operating Voltage

3V DC battery

Color Parameters

- Brightness
- Saturation
- Fading



ORDERING CODE

MODEL

TW-DMX

TW-DMX - DMX controller

Tunable White DMX wall-mount controller is a fully touch sensitive controller designed in accordance with standard protocol DMX512. Offers fast and accurate color temperature adjustment and brightness dimming of natural white, warm white and cold white. Designed with a touch color wheel, the DMX512 controller can adjust color temperature and brightness for all white LEDs smoothly and accurately. The DMX controller can control 1 zone with endless decoders.

Features

- 1 zone
- 6 color scenes
- DMX Control
- Touch Sensitive Glass Surface
- Dimming and Speed Control
- Memory Function
- Easily Fits Standard US Switch Boxes

Operating Voltage

12 - 24V DC

Color Parameters

- Brightness
- Saturation
- Primary colors
- Fading
- Color changing speed



ORDERING CODE

MODEL

SLD-DIMTW

SLD-DIMTW - Tunable white LED dimming module

The SLD DimTW is a constant voltage warm dimming LED dimming module. The unique dimming module accepts 0-10V control and mimics a smooth, incandescent dimming curve.

Features

- Flicker free 0-100% dimming
- High efficiency up to 97%
- High precision dimming ratio:>1:1000
- Fully isolated plastic housing
- Comply with EN55015 and FCC part 15 without additional input filter and capacitors
- compact size, high reliability
- 3 years warranty

Operating Voltage

8-48 VDC

Controllers and Decoders

For use with Tunable White, RGB/RGBW Power Supplies



Translates controller DMX512 programs for RGB and white LED strips.

Unique DMX address for the decoder can be set easily and displayed by the numeric display on the case. Changing and resetting the DMX address requires manual input.

Use power repeater to expand output.

Operating Voltage

12-36 VDC

Power Capacity

up to 96W at 24V

Operating Temperature Range

from -4°F to +122°F in case

ORDERING CODE

MODEL

DDMX-RGBW

DDMX-RGBW - DMX decoder



The RGBW receiver is easily paired with controller by the click of a button. Receiver can be reset to factory settings at any time.

Each receiver can store one static RGB color, one color sequence, and one brightness setting for the white LED strip. Receivers assigned to the same scene within the same zone will have the same LED static color and color sequence.

Operating Voltage

12-36 VDC

Power Capacity

up to 96W at 24V

Operating Temperature Range


from -4°F to +122°F in case

ORDERING CODE

MODEL

RGBW-RC-R

RGBW-RC-R - RGBW receiver



Extends identical signal when connected in series to an RGBW LED control system. The RGBW signal repeater works with Luminii RGB and RGBW controllers, receivers, and decoders.

RGBW signal can be extended indefinitely when adequate power supply (not included) is connected to the system.

Operating Voltage

12-36 VDC

Power Capacity

up to 96W at 24V

Operating Temperature Range

from -4°F to +122°F in case

ORDERING CODE

MODEL

RGBW-SR

RGBW-SR - RGBW signal repeater

Controllers and Decoders

For use with RGB/RGBW Power Supplies



ORDERING CODE

MODEL

RGBW-MC3

RGBW-MC3 - 4-zone RGBW controller

Easy to operate wireless interface suitable for static or color changing scenes. Control 4 different color zones separately or at the same time. RGBW receiver (RGBW-RC-R) required for operation. Assign multiple receivers per zone to cover a large area.

Color wheel enables highly stable and sensitive color control functionality. Create your own color changing sequences with ease and flexibility.

Power

qty 3 AAA batteries

Scenes

up to 4 unique zones

Signal

Wireless (RF)

Energy Saving

Deactivates after 10 seconds of inactivity

Color Parameters

- Brightness
- Saturation
- Primary colors
- Speed of color changing sequence
- Fading



ORDERING CODE

MODEL		ZONES		COLOR
	-		-	

DMX - DMX Controller

3Z - Three Zone
1Z - One Zone

RGBW - Red,Green, Blue,& White

DMX /Wireless RGB-W wall-mount controller controls DMX lighting fixtures, wireless control of RGB-W lighting fixture or use both simultaneously. Fits in any standard US switch box. Includes all the outputs in the back of the controller.

Control brightness levels with a single touch, personalize and memorize 3 different scenes, and even create 3 variations of white.

Features

- 2 in 1 in-Wall Controller: DMX Control or Wireless RGB-W
- 65,000 Color Options, Dimming and Speed Control
- Memory Function
- 50 Foot Wireless Range
- Easily Fits Standard US Switch Boxes
- Touch Sensitive Glass Surface
- Includes 10 Built in Programs, or Create and Play Your Own


Operating Voltage

12 - 24V DC

Color Parameters

- Brightness
- Saturation
- Primary colors
- Fading
- Color changing speed

For use with Tunable White, RGB/RGBW, Pixel Power Supplies



ORDERING CODE

MODEL

TSDMX-E

TSDMX-E - Touchscreen DMX controller

Programmable advanced DMX512 lighting controller featuring a touch-screen interface. Operates as stand alone controller or integrated with most architectural lighting control systems. Can controller endless DMX512 enabled devices.

Mounts to standard single or dual gang wall box with the included power supply inside the junction box. Terminal block design for power and data connections.

Features

- Sleek glass design which sits 0.43" from the wall
- Graphical color display to show selected environment
- Color/dimmer/speed palette
- Color temperature mixing
- Touch sensitive buttons. No mechanical parts
- Touch sensitive wheel allows for accurate color selection
- Multi-zone microSD memory
- Multi-room control with 500 scenes, 10 zones
- 1024 DMX channels. Control 340 RGB fixtures
- USB & Ethernet connectivity for programming and control

Power Supply

7 VDC (included)

Programmability

PC, Mac, Tablet, Smartphone

Output Signal


DMX512 (1024 channels)

Color Parameters

- Brightness
- Saturation
- Speed of color changing sequence
- Fading / dimming / brightness

Controllers and Decoders

For use with Tunable White, RGB/RGBW Power Supplies



ORDERING CODE

MODEL

DALI2-DT8-RGBW

DALI2-DT8-RGBW - DALI-2 RGBW Decoder

A 4-channel DALI2 DT8 decoder designed to control RGB, RGBW, and TW LED fixtures, featuring adjustable color temperature and customizable lumen output.

Voltage/Frequency
12-36VDC

Max Output Power
4 output channels, 60-180W each

Max Output Current
4 output channels, max of 5A each

Ambient Operating Temperature Range
-20 to 50°C

Environment
Dry (IP20)



ORDERING CODE

MODEL

DDMX-5CH-RDM-PRO

DDMX-5CH-RDM-PRO - DMX512 Decoder

DMX512 decoder with RDM functionality features 5 PWM output channels with common anode. High PWM output frequency range allows the product to be used in HD video conferencing spaces. All DMX products to be installed per DMX512 Standard.

Power
96 Watt

Inputs
RJ45, XLR-5Pin, Terminal Block

DMX Channels
1 to 5 settable

PWM Output Resolution Ratio
8 or 16 bit

PWM Output Frequency
500Hz - 30KHz

Output Dimming Curve Gamma Value
0.1 ~ 9.9



ORDERING CODE

MODEL

RGBW-WI-R

RGBW-WI-R - WIFI generator

RGBW-WI-R creates a local network that enables any electronic device (phone, tablet, etc.) to control the RGB/W strip connected to a RGBW-RC-R receiver.


The control functions are achieved through a free application download for Android and iOS devices called REALCOLOR.

Operating Voltage
12-36 VDC

Power Supply
PI-130-24 (included)

Operating Temperature Range
from -4°F to +122°F in case

For use with Pixel Power Supplies



ORDERING CODE

MODEL

SR-DMX-SPI

SR-DMX-SPI - Smart Pixel Decoder

The SR-DMX-SPI is a smart LED pixel decoder that controls RGB/RGBW pixel LED strips with SPI signal. Designed with an OLED backlit panel, the pixel controller allows for easy configuration of most settings. Four push buttons are available for control of the LED functions.

*For pixel only.

Features

- 2 in 1 in-Wall Controller: DMX Control or Wireless RGB-W
- SPI signal output for RGB/RGBW pixel light control
- DMX512 controllable and RF/WIFI remote controllable
- Capable of addressing up to 1020 RGB pixels & 765 RGBW pixels
- OLED panel allows for easy configuration

Operating Voltage
12 - 36V DC

Power capacity
up to 96W at 24V

Operating temperature range
from -4°F to +122°F in case