Features

- 24VDC Class 2 and IP68 rated for wet locations, fixtures made to order up to 144". Fixtures can be linked up to 90' depending on output
- Suitable for undercabinet, millwork, surface mount, direct view, cove, outdoor, wet, architectual reveals, and accent lighting applications
- Dot free even illumination with frosted lens
- Average Life (L70): 50,000hrs
- Proprietary strong bond solder method handles up to 50 lbs of pull force on wire leads and connectors
- Vibrant Color options offer premium color quality with R9 values up to 97
- High Efficacy options offer best in class output and efficacy with over 680 lm/ft and over 97 lm/W
- 5 year warranty

IP68



Finish Options (see page 3 for additional information)

Base	Silver Anodized
Powder Coat	Black, Bronze, White
Premium	Matte Black, Warm Nickel, Aged Brass, Polished Gold, Chrome

RoHS Declare. CE | Single Bin +/- 30 CCT | DIM | MADE IN U.S.A | TITLE 24 JA8 COMPLIANT | BAA & BABA | cULus LISTED

Technical Information

TYPE	Vibrant Color VC72					
OUTPUT OPTIONS	**VC72VLO**	**VC72LO**	**VC72SO**	**VC72MO**	**VC72HO**	**VC72VHO**
Lumens Output (3000K) (with a Clear Lens)	77 lm/ft	197 lm/ft	262 lm/ft	346 lm/ft	418 lm/ft	557 lm/ft
Average Power Consumption (for a 4' section)	1.1 W/ft	2.8 W/ft	3.7 W/ft	4.9 W/ft	5.9 W/ft	7.9 W/ft
Efficacy	70 lm/W	70 lm/W	71 lm/W	71 lm/W	71 lm/W	71 lm/W
Max Run Length (in series)	56.9 ft	32 ft	28 ft	24 ft	21 ft	18 ft
Ambient Operating Temperature Range*	-13°F – 122°F (-25°C – 50°C)					-13°F – 95°F (-25°C – 35°C)

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

Vibrant Color (VC72)

CCT	Multiplier (ref. - 30K)	TM-30 CRI	R_f	R_g	R_9
2700K	0.79	96	89	95	97
3000K	1.00	96	93	97	87
3500K	1.03	97	94	99	89
4000K	1.05	96	95	101	90

TYPE	High Efficacy HE64					
OUTPUT OPTIONS	**HE64VLO**	**HE64LO**	**HE64SO**	**HE64MO**	**HE64HO**	**HE64VHO**
Lumens Output (3000K) (with a Clear Lens)	85 lm/ft	185 lm/ft	265 lm/ft	352 lm/ft	500 lm/ft	686 lm/ft
Average Power Consumption (for a 4' section)	1 W/ ft	1.9 W/ ft	2.9 W/ ft	3.8 W/ ft	5.6 W/ ft	7.1 W/ ft
Efficacy	85 lm/W	97 lm/W	91 lm/W	93 lm/W	89 lm/W	97 lm/W
Max Run Length (in series)	90 ft	55 ft	34.9 ft	26 ft	17 ft	13 ft
Ambient Operating Temperature Range*	-13°F – 122°F (-25°C – 50°C)					-13°F – 113°F (-25°C – 45°C)

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

High Efficacy (HE64)

CCT	Multiplier (ref. - 30K)	TM-30 CRI	R_f	R_g	R_9
2700K	0.90	96	89	94	74
3000K	1.00	96	91	97	69
3500K	1.05	97	92	101	78
4000K	1.09	96	90	99	73

Ordering Code

MODEL	LENGTH[1]	OUTPUT[2]	CCT	LENS	MOUNTING	FINISH[3]	FEED POSITION LEFT[5]	FEED POSITION RIGHT[5]	ACCESSORIES
KMW - Kendo M Wet	12"–144" 1" increments	VC72VLO - Very Low VC72LO - Low VC72SO - Standard VC72MO - Medium VC72HO - High VC72VHO - Very High	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	C - Clear F - Frosted GR - Narrow Beam Grazer	FC - Fixed Clip A - Adjustable Hinge Mounting FC45 - Fixed Clip 45° EFC - Tamper Resistant Fixed Clip	*BASE* SA - Silver Anodized *POWDER COAT* BK - Black BZ - Bronze WH - White	*WIRE LEADS (72")* LWE - Wire End Feed LWB - Wire Back Feed LWSA - Wire Side A Feed LWSB - Wire Side B Feed LNPF - No Power Feed	*WIRE LEADS (72")* RWE - Wire End Feed RWB - Wire Back Feed RWSA - Wire Side A Feed RWSB - Wire Side B Feed RNPF - No Power Feed	___ - N/A, leave blank BLS - Blade louver, Silver BLBK - Blade louver, Black BLWH - Blade louver, White GSS - Glare shield, Silver GSBK - Glare shield, Black GSWH - Glare shield, White
	12"–144" 2" increments	HE64VLO - Very Low HE64LO - Low HE64SO - Standard HE64MO - Medium HE64HO - High HE64VHO - Very High	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K			*PREMIUM* MBK - Matte Black WN - Warm Nickel AB - Aged Brass PG - Polished Gold[4] CH - Chrome[4]	*QUICK CONNECTS (6")* LFE - Female Q/C, End Feed LFB - Female Q/C, Back Feed LFSA - Female Q/C, Side A Feed LFSB - Female Q/C, Side B Feed LNPF - No Power Feed	*QUICK CONNECTS (6")* RFE - Female Q/C, End Feed RFB - Female Q/C, Back Feed RFSA - Female Q/C, Side A Feed RFSB - Female Q/C, Side B Feed RNPF - No Power Feed	

1 - Custom lengths and increments are available, please consult Inside Sales with specific request.
2 - Title 24 JA8 achievable depending on Output, CCT, and Lens selections. See multiplier charts to calculate specific efficacies.
3 - Non Base finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
4 - Polished Gold finishes and Chrome finishes have a maximum fixture length of 96".
5 - LNPF - RNPF is not a valid configuration option

Powerfeeds and Connectors

Power Feed Position Options and Orientation



Linking and Extension Cable Options



WET-FMA-2-2
Female to Male Adapter, 2 pin



WET-CON-LEAD-M-2-48
Male Wet Connector Cable, 2 pin, 48"



WET-CON-JC-F-M-2-48
Female/Male Wet Jumper Cable, 2 pin, 48"







Sample Layout





End feed shown



Side and Back feed shown

Product Dimensions



Clear, Half-frosted, Frosted, & Flat Frosted Lens



Narrow Beam Grazer Lens



Fixed Mounting Bracket



Adjustable Hinged Bracket



45° Mounting Bracket



Clear or Frosted Lens using the Exterior Fixed Clip

Finish Options

- Finish options are available in a wide variety, allowing for complete customization of style and aesthetic.
- Non Base finishes may have extended lead times and price adder.
- Polished Gold and Chrome finishes have a maximum fixture length of 96".
- Custom RALs are available, please consult Inside Sales with specific request.

Silver Anodized
Base



Silver Anodized is a soft silver with a clear finish.

Black
Powder Coat



Black is a true deep black with a glossy finish.

Bronze
Powder Coat

Bronze is a rich, dark brown with a satin finish.

White
Powder Coat



White is a polar bright white and field paintable.

Matte Black
Premium



Matte Black is a dark, pitch-black with a soft flat finish.

Warm Nickel
Premium



Warm Nickel is a soft, silvery smoke with warm tones and a satin finish.

Aged Brass
Premium



Aged Brass is a deep brown shade with slightly golden undertones.

Polished Gold
Premium



Polished Gold is bright and radiant for a brilliant finish.

Chrome
Premium



Chrome is a highly reflective silver polish.

Light Transmission and Dotting

	Lens/Accessory											
Output Options	**Clear Lens**				**Frosted Lens**				**Narrow Beam Grazer**			
Dimming Level	100%	50%	10%	1%	100%	50%	10%	1%	100%	50%	10%	1%
VC72VLO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
VC72LO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
VC72SO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
VC72MO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
VC72HO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
VC72VHO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
HE64VLO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
HE64LO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
HE64SO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
HE64MO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
HE64HO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
HE64VHO	CD	CD	CD	CD	ND	ND	ND	ND	CD	CD	CD	CD
Transmission Percentage	100%				55%				87%			

Use complete Dotting Chart Tool online for more dotting information

I'm also click-able



CD - Clear Dotting

SD - Slight Dotting

ND - No Dotting

Accessory Options

LVSP-WET
Splice box: wet rated, low voltage, gray, IP66



LVSP-WET-CM
Connector for splice box, low voltage for cable management, gray.



LV-GS-KMSC-24-XX
Glare Shield reduces glare at high angle, field cuttable.
Also available with complete fixture, use ordering code **-GSXX**



LV-BL-KMSC-24-XX
Blade Louver reduces glare at high angle in two directions
Also available with complete fixture, use ordering code **-BLXX**



XX	Color
WH	White
BK	Black
SL	Silver

Photometry

KMW-48-VC72VHO-30K-C

Kendo M Wet, 4ft, VHO, 3000K, Clear Lens



Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	154	28%
	0-40	260	47%
	0-60	457	82%
	0-90	551	99%
Total	0-180	557	100%

Beam Angle



KMW-48-VC72VHO-30K-F

Kendo M Wet, 4ft, VHO, 3000K, Frosted Lens



Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	77	25%
	0-40	129	42%
	0-60	232	76%
	0-90	301	99%
Total	0-180	305	100%

Beam Angle



KMW-48-VC72VHO-30K- GR

Kendo M Wet, 4ft, VHO, 3000K, Narrow Beam Grazer Lens



Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	202	42%
	0-40	287	60%
	0-60	419	87%
	0-90	477	99%
Total	0-180	483	100%

Beam Angle



Power Consumption

Please visit the link/QR code below to access the Luminii Power Consumption Chart tool on our website.

There you will be able to select your fixture, ouput, and desired power feed to get a full power consumption table.

I'm also click-able

Desired Nominal Length: _____

Desired Output: _____

Desired CCT: _____

Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
10	544.1	342.2	215.1	135.3	85.1	53.5	33.7
15	362.7	228.1	143.4	90.2	56.7	35.7	22.4
20	272.0	171.1	107.6	67.7	42.6	26.8	16.8
25	217.6	136.9	86.1	54.1	34.0	21.4	13.5
30	181.4	114.1	71.7	45.1	28.4	17.8	11.2
35	155.5	97.8	61.5	38.7	24.3	15.3	9.6
40	136.0	85.5	53.8	33.8	21.3	13.4	8.4
45	120.9	76.0	47.8	30.1	18.9	11.9	7.5
50	108.8	68.4	43.0	27.1	17.0	10.7	6.7
55	98.9	62.2	39.1	24.6	15.5	9.7	6.1
60	90.7	57.0	35.9	22.6	14.2	8.9	5.6
65	83.7	52.6	33.1	20.8	13.1	8.2	5.2
70	77.7	48.9	30.7	19.3	12.2	7.6	4.8
75	72.5	45.6	28.7	18.0	11.3	7.1	4.5
80	68.0	42.8	26.9	16.9	10.6	6.7	4.2
85	64.0	40.3	25.3	15.9	10.0	6.3	4.0
90	60.5	38.0	23.9	15.0	9.5	5.9	3.7
96	56.7	35.6	22.4	14.1	8.9	5.6	3.5

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		WATTAGE		OUTPUT
	–		–		–	
PS - Power Supply, 120-277VAC		UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)		30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.

0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart

MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50″	7.40″	8.66"	11.85"
Width	3.73″	3.73″	3.73"	4.32"
Depth	1.61″	1.61″	1.61"	1.81"

PS-UNI-30/60/96



PS-UNI-3X96



For use with Static White

Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic		D - Dry		96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"



PS-010V-LIN/LOG-D-3X96



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Athena 0-10V LED Driver

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS-Power Supply, 120-277VAC	010V-LIN-0-10V Dimming (0.1%), Linear 010V-LOG-0-10V Dimming (0.1%), Logarithmic	D-Dry	96-96 Watts	24-24 VDC	AWNR-Athena



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

For use with Static White

Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DALI2-DT6-DALI2 DT6 (0.1%)	D-Dry	96-96 Watts	24-24 VDC



Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"

For use with Static White

Ordering Code - DALI Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DALI-DALI (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC



PS-DALI-D-3X96-24



Model	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DMX-DMX (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

ZONAL CONTROL POWER SUPPLIES.
CONTROL MULTIPLE TAPES/ZONES USING DMX CHANNELS.





For use with Static White

Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"



For use with Static White

Ordering Code - In-Ground Power Supplies

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS120-Power Supply, 120VAC PS240-Power Supply, 240VAC PS277-Power Supply, 277VAC	ELV-ELV Dimming (1%)	IG-In Ground	2X96-2X96 Watts	24-24 VDC

MODELS	2X96W
Length	8.40"
Width	8.30"
Depth	8.10"



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

LUTRON®

Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 1%

MODEL

L3DA4U1UKL-CV240

Hi-lume™ 1% EcoSystem Voltage LED driver 40W max

MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"

L3DA4U1UKL-CV240



LUTRON®

Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

Hi-lume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™ 96W max

MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"