



Features

- Krest Corner is a recessed 90° corner detail for wall-to-wall or wall-to-ceiling transitions
- Class 2, LED strip listed for damp locations
- Indirect, dot free even illumination
- Krest System is a turn-key solution for complex layouts and runs - coming with pre-welded corners and specific power feed extrusions for installation ease.
- Shipped as field configurable strip and channel
- For use with 5/8" or thicker drywall
- Vibrant Color options offer premium quality and vibrant colors with R9 values up to 99
- High Efficacy options offer best in class output and efficacy with over 510 lm/ft and up to 73 lm/W
- Average Life (L70): 50,000hrs
- 7 year warranty



Technical Information

TYPE	Vibrant Color VC72					
OUTPUT OPTIONS	**2xVC72VLO**	**2xVC72LO**	**2xVC72SO**	**2xVC72MO**	**2xVC72HO**	**2xVC72VHO**
Lumens Output (3000K) (with a Frosted Lens)	80 lm/ft	203 lm/ft	270 lm/ft	357 lm/ft	432 lm/ft	575 lm/ft
Average Power Consumption (for a 4' section)	2.2 W/ft	5.6 W/ft	7.4 W/ft	9.8 W/ft	11.8 W/ft	15.8 W/ft
Efficacy	36 lm/W	36 lm/W	36 lm/W	36 lm/W	37 lm/W	36 lm/W
Max Run Length (in series)	28.5 ft	16 ft	14 ft	12 ft	10.5 ft	9 ft
Ambient Operating Temperature Range*	-4°F – 122°F (-20°C – 50°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 113°F (-20°C – 45°C)	-4°F – 104°F (-20°C – 40°C)	-4°F – 86°F (-20°C – 30°C)

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

Vibrant Color (VC72)

CCT	Multiplier (ref. - 30K)	TM-30 CRI	R_f	R_g	R_9
1800K	0.50	95	94	99	86
2200K	0.66	96	94	101	95
2400K	0.90	98	96	101	91
2700K	0.93	98	96	102	93
3000K	1.00	97	94	104	99
3500K	1.04	96	94	105	97
4100K	1.05	97	95	104	96

TYPE	High Efficacy HE64					
OUTPUT OPTIONS	**2xHE64VLO**	**2xHE64LO**	**2xHE64SO**	**2xHE64MO**	**2xHE64HO**	**2xHE64VHO**
Lumens Output (3000K) (with a Frosted Lens)	88 lm/ft	191 lm/ft	273 lm/ft	364 lm/ft	517 lm/ft	708 lm/ft
Average Power Consumption (for a 4' section)	2 W/ ft	3.8 W/ ft	5.8 W/ ft	7.6 W/ ft	11.2 W/ ft	14.2 W/ ft
Efficacy	44 lm/W	50 lm/W	47 lm/W	48 lm/W	46 lm/W	50 lm/W
Max Run Length (in series)	45 ft	27.4 ft	17.4 ft	13 ft	8.5 ft	6.5 ft
Ambient Operating Temperature Range*	-4°F – 122°F (-20°C – 50°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 122°F (-20°C – 50°C)	-4°F – 113°F (-20°C – 45°C)	-4°F – 95°F (-20°C – 35°C)

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

High Efficacy (HE64)

CCT	Multiplier (ref. - 30K)	TM-30 CRI	R_f	R_g	R_9
2200K	0.74	94	91	96	65
2400K	0.87	94	92	97	56
2700K	0.97	94	92	100	57
3000K	1.00	93	91	99	54
3500K	1.01	95	91	99	62
4000K	1.04	95	91	99	68

Ordering Code

KREST - MODEL - REFLECTOR - SYSTEM SHAPE - LENGTH[1] - OUTPUT[2] - CCT - LENS - MOUNTING - FINISH

KREST - Krest System

MODEL - CRNR - Corner

REFLECTOR - Q3 - Rounded Square 3" Reflector

SYSTEM SHAPE

- STR - Straight Run
- CMLX - Complex Shape
- UIC - U-Shape, Inside Corner
- UOC - U-Shape, Outside Corner
- LIC - L-Shape, Inside Corner
- LOC - L-Shape, Outside Corne
- RECIC - Rectangle, Inside Corner
- RECOC - Rectangle, Outside Corner

LENGTH[1]

- Overall System Length in Inches (1/16) EX: 1249.0625
- Leg 1 X Leg 2 X Leg 3 in Inches (1/16) EX: 115.0625 X 13.50 X 235.125
- Leg 1 X Leg 2 in Inches (1/16) EX: 115.0625 X 13.50

OUTPUT[2]

- VC72VLO - Very Low
- VC72LO - Low
- VC72SO - Standard
- VC72MO - Medium
- VC72HO - High
- VC72VHO - Very High
- HE64VLO - Very Low
- HE64LO - Low
- HE64SO - Standard
- HE64MO - Medium
- HE64HO - High
- HE64VHO - Very High

CCT

- 18K - 1800K
- 22K - 2200K
- 24K - 2400K
- 27K - 2700K
- 30K - 3000K
- 35K - 3500K
- 41K - 4100K
- 40K - 4000K

LENS

- F - Frosted Lens

MOUNTING


- GDS - Gypsum Drywall Surface

FINISH

- WH - White Powder Coat


1 - Length written in decimal format to the closest sixteenth of an inch.
2 - Title 24 JA8 achievable depending on Output, CCT, and Lens selections. See multiplier charts to calculate specific efficacies.

Applications



Floor-To-Ceiling / Wall-To-Wall Junction

Fixture vertically mounted on 5/8" or thicker drywall. Suggested to use two layers of drywall or strapping to offset drywall



Straight Corner / Wall-To-Ceiling Perimeter

Fixture horizontally mounted on 5/8" or thicker drywall at intersection of wall and ceiling.

Light Transmission and Dotting

	Lens/Accessory			
Output Options	**Frosted Lens**			
Dimming Level	100%	50%	10%	1%
VC72VLO	ND	ND	ND	ND
VC72LO	ND	ND	ND	ND
VC72SO	ND	ND	ND	ND
VC72MO	ND	ND	ND	ND
VC72HO	ND	ND	ND	ND
VC72VHO	ND	ND	ND	ND
HE64VLO	ND	ND	ND	ND
HE64LO	ND	ND	ND	ND
HE64SO	ND	ND	ND	ND
HE64MO	ND	ND	ND	ND
HE64HO	ND	ND	ND	ND
HE64VHO	ND	ND	ND	ND
Transmission Percentage	100%			



CD - Clear Dotting

SD - Slight Dotting

ND - No Dotting


Use complete Dotting Chart Tool online for more dotting information

I'm also click-able

Photometry

KREST-CRNR-Q3-STR-48-VC72VHO-30K-F


Krest Corner, Rounded Square 3" Backer Plate, 4ft, VHO, 3000K, Frosted Lens




Zonal Lumen Summary 3000K


Zone	Lumen	% Fixture
0-30	100	24.0%
0-40	161	38.6%
0-60	280	67.0%
0-90	378	90.4%
Total 0-180	418	100.0%


Beam Angle







Product Dimensions









Krest Cross with Junction Box

*Krest LED Extrusion and Krest Reflectors are not mechanically joined and instead are two seperate pieces.

Finish Options

- Finish options are only applied to the Reflector, LED extrusion will be in silver anodized finish.


White
Powder Coat



White is a polar bright white and field paintable.


Krest System - What's Included

A - Krest Straight Extrusion




Included with Krest System, the Krest Straight extrusion is the main architectural housing for the majority of the system run. It includes two LED extrusions, two lenses, two front joiners, mounting screws, and a reflector. Provided in lengths of 48"/96"/144" long.

B - Krest Power Feed



The Krest Power Feed has specially machined slots for wire management. It includes the LED extrusion, junction box, one back joiner, one front joiner, one front slot cover, and four trap door covers.
Note: Does NOT include the lens or reflector. 12" long. Two Krest Power Feeds required for Krest Corner.


C - LineLED




Included with Krest System, the LineLED will be split into runs based on system layout and max run length of the LED strip. By default, the LineLED will come with soldered leads (SL) on end and no connector (NC) on the other. Additonal configurations available upon request.

D - Krest Corner Power Feed
Based on ordered Run

Krest Corner - Outside Corner




Krest Corner - Inside Corner



Included with Krest System, the Krest Corner, Corner Power Feed has pre-welded corners and specially machined slots for wire management. Includes the two welded LED extrusion pieces, four lenses, one welded reflector, two junction boxes, two front joiners, four front slot covers, and eight trap door covers. Corners are nominally 18" x 18".
NOTE: ALL CORNERS CAN FEED POWER TO LED STRIPS IN BOTH DIRECTIONS. BY DEFAULT, TWO JUNCTION BOXES ARE PROVIDED PER KREST CORNER POWER FEED (ONE PER SIDE).


Krest Cross System - Sample Run



Accessories - Sold Separately

JB-KRESTC


Krest Junction Box with Hanger Bars



For use when wanting more than one junction box on the Krest Corner, Corner Channel.
NOTE: Does not mechanically mate to Krest Extrusion

DUST-CVR-KRESTC

Krest Dust Cover Foam Roll




Included with Krest System, the foam dust cover is used during the installation process to protect the LED cavity during plastering.
NOTE: Provided per foot. Max continuous length is 100ft


Minii Connectors

Minii connectors are easy, field-installable accessories that make joining LL strip simple! Their minimal width allows them to fit into extrusions, while their transparent frame eliminates dark spots.
Note: minii connectors are NOT included in Krest System by default. LED strip included in Krest System comes with soldered leads as standard. If requested, minii connectors could be ordered istead.

LL-PJC-10-03
Jumper minii connector with 3" wire for Static White LED strip




LL-PFC-10-72
Power feed minii connector with 72" wire for Static White LED strip



LL-BSC-10

Butt splice minii connector for Static White LED strip



Power Consumption

Please visit the link/QR code below to access the Luminii Power Consumption Chart tool on our website.

There you will be able to select your fixture, ouput, and desired power feed to get a full power consumption table.

I'm also click-able

Desired Nominal Length: _____

Desired Output: _____

Desired CCT: _____

Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
10	544.1	342.2	215.1	135.3	85.1	53.5	33.7
15	362.7	228.1	143.4	90.2	56.7	35.7	22.4
20	272.0	171.1	107.6	67.7	42.6	26.8	16.8
25	217.6	136.9	86.1	54.1	34.0	21.4	13.5
30	181.4	114.1	71.7	45.1	28.4	17.8	11.2
35	155.5	97.8	61.5	38.7	24.3	15.3	9.6
40	136.0	85.5	53.8	33.8	21.3	13.4	8.4
45	120.9	76.0	47.8	30.1	18.9	11.9	7.5
50	108.8	68.4	43.0	27.1	17.0	10.7	6.7
55	98.9	62.2	39.1	24.6	15.5	9.7	6.1
60	90.7	57.0	35.9	22.6	14.2	8.9	5.6
65	83.7	52.6	33.1	20.8	13.1	8.2	5.2
70	77.7	48.9	30.7	19.3	12.2	7.6	4.8
75	72.5	45.6	28.7	18.0	11.3	7.1	4.5
80	68.0	42.8	26.9	16.9	10.6	6.7	4.2
85	64.0	40.3	25.3	15.9	10.0	6.3	4.0
90	60.5	38.0	23.9	15.0	9.5	5.9	3.7
96	56.7	35.6	22.4	14.1	8.9	5.6	3.5

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL		INPUT CONTROL		WATTAGE		OUTPUT
	–		–		–	
PS - Power Supply, 120-277VAC		UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)		30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.


0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart

MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50″	7.40″	8.66"	11.85"
Width	3.73″	3.73″	3.73"	4.32"
Depth	1.61″	1.61″	1.61"	1.81"

PS-UNI-30/60/96



PS-UNI-3X96




For use with Static White


Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic		D - Dry		96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"



PS-010V-LIN/LOG-D-3X96



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.


For use with Static White

Ordering Code - Athena 0-10V LED Driver

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts	24 - 24 VDC	AWNR - Athena Wireless Node

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

PS-010V-LIN/LOG-D-96-ANWR




For use with Static White

Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI2-DT6 - DALI2 DT6 (0.1%)	D - Dry	96 - 96 Watts	24 - 24 VDC

Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"




For use with Static White


Ordering Code - DALI Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI - DALI (0.1%)	D - Dry	96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC

Model	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"



PS-DALI-D-3X96-24



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.


For use with Static White


Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DMX-DMX (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

ZONAL CONTROL POWER SUPPLIES.
CONTROL MULTIPLE TAPES/ZONES USING DMX CHANNELS.






For use with Static White

Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"




For use with Static White

Ordering Code - In-Ground Power Supplies

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS120-Power Supply, 120VAC PS240-Power Supply, 240VAC PS277-Power Supply, 277VAC	ELV-ELV Dimming (1%)	IG-In Ground	2X96-2X96 Watts	24-24 VDC

MODELS	2X96W
Length	8.40"
Width	8.30"
Depth	8.10"




Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Athena VintageDim® 0-10V Two Channel LED Driver, 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS-Power Supply, 120-277VAC	010V-2CH-0-10V Dimming Two Channel Control, LED1 Brightness and LED2 Brightness	D-Dry	96-96 W	24-24 VDC	AWNR-Athena



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

LUTRON®


Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 1%

MODEL

L3DA4U1UKL-CV240

HiLume™ 1% EcoSystem Voltage LED driver 40W max



MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"

LUTRON®


Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

HiLume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™ 96W max



MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"