



LETO 3 - Recessed downlight. LETO 3 has a few different styles. This round recessed model gives any space a well-balanced level of general light through a round aperture and allows for beam control options, making the LETO 3 a superb everyday choice.

Ordering Code

Fixture	678						
	1	2	3	4	5	6	7
Driver		678			--	--	
	1	2	3	4	5	6	

Product Specifications

SAMPLE: Fixture 678 - A90 - 618 - 27 - 07 - 00 - 01 | Driver 910 - 678 - STD - 120 - A90 - 07

1 - Model	2 - LED	3 - Reflector	4 - CCT	5 - Lumen	6 - Accessory	7 - Finish
678 · Leto 3	A90 · 93+ CRI Accuracy	618 · 18° 630 · 30° 645 · 45° 660 · 60°	25 · 2500K 27 · 2700K 30 · 3000K 35 · 3500K 40 · 4000K 65 · 6500K	07 · 700 (6.1W) 10 · 1000 (9.1W) 15 · 1500 (14W) 20 · 2000 (19.8W) 30 · 3000 (29.4W)	00 · No Accessory DL · Diffusing Lens DC · Disk Clear DF · Disk Frosted RC · Ring Clear RF · Ring Frosted TC · Tube Clear TF · Tube Frosted	01 · White 02 · Black 08 · Silver XX · Custom

1 - Housing Style	2 - Model	3 - Driver	Dim Level	Dim Level	4 - Voltage	
910 · Remote 915 · New Construction	678 · Leto 3	STD · Non Dimming LCS · 0 - 10 Volt Protocol DIM · Phase ^{*1} ELDOLC · EidoLED 0 - 10 Volt ^{*2} DALI · DALI Protocol ^{*2}	N/A 1% 10% 0.1% 0.1%	LUTES · Hilume Ecodigital ^{*2} LUT2W · 2 Wire for phase ^{*1/2} DMX · SENSO ^{*2} EMG · Emergency Driver ^{*2/3} CSMB · Casambi Wireless Control ^{*2/3}	1% 1% 10% 0.1% 0.1%	120 · 120V 277 · 277V 347 · 347V ^{*4}

5 - LED	6 - Lumen	
Same as Fixture	Same as Fixture	<p>*1 120V only *2 Requires remote housing *3 Specified separately *4 Not available with ELDO, Lutron or DMX</p> <p>Project : _____ Quantity : _____ Type : _____ Notes : _____</p>

Photometrics

Senso's in-house photometric testing ensures that our lighting design can match your needs precisely. Our Goniophotometer and testing lab produces on-demand photometry files based on any specified fixture, including LM-79 Test reports, IES Files, and CRI/CCT measurements. See Sensolighting.com for more information.

**Full photometric Reports and IES files available for every configuration*

Color Metrics

TM 30-15

Our clients deserve the best information possible about their lighting choices. That's why Senso has invested in the Illuminating Engineering Society (IES) TM 30-15, a new system that measures an LED light source's color rendering properties. Using Senso's state-of-the-art goniophotometer, this method identifies the optimal light source for your project and helps evaluate the trade-offs between efficacy and color rendering. Senso can provide TM 30-15 data for all of our products.

**Full Color Metric Info Available at Sensolighting.com*

LED Module Performance

Output: Up to 103 lumen/Watt

Efficacy: Color consistency within a 3-MacAdam Ellipse

CCT: 2500K - 6500K

Color Rendering: 93+ CRI

Min. R Values: R^g - 60 R^f - 90 R^g - 100

Driver and Power Consumption

Dimming: 1% dimming standard with 0.1% option

Casambi wireless control available

Ripple: Industry leading Low ripple

Efficiency: Power Factor >0.9

Efficiency over 85%

Class 2 output for safety


Installation: Remote mounted

Lumen Option	700lm	1000lm	1500lm	2000lm	3000lm
Fixture Wattage	6.1W	9.1W	14W	19.8W	31.8W
Delivered Lumen	628lm	932lm	1403lm	1921lm	2936lm

Reflector

Faceted Reflector

Senso metal spun reflectors for function, low glare and efficiency





Installation

- For new and retrofit installations
- Holds in place with three friction fit spring clips
- Simple connection between fixture and driver via quick connect

Construction / Finish


- Custom finishes are available
- Die cast aluminum trim
- Rated for damp location
- Made in Canada

Dimensions




Accessories


Floating Ring



Tube





Floating Disk



Standard Senso Housing - 910

Dimension



Included

Unless specified otherwise, this is provided as standard



- Bar hanger** • Length: from 14-3/16" to 26"
- Driver with enclosure** • Galvanized steel enclosure
- Security wire** • Flexible aircraft cable, 12" long
- Easy to clip snap body included

* driver can be installed either:

- (A) laying on top of ceiling. (B) mounted to the bar hanger and fixed to the ceiling. (C) remote from the fixture, with the bar hanger still used if desired to secure the fixture

New Construction - 915

Dimension



Included

- Plaster Frame** • Galvanized steel construction with cut-out to
- Bar hanger** • Length: from 14-3/16" to 26"
- Security wire** • Flexible aircraft cable, 12" long
- Easy to clip snap body included