

LETO 11 MINI

WALL MOUNT CYLINDER
TUNABLE WHITE & WARM DIM




Features

- Faceted metal reflectors provide beam spreads between 20° to 60°.
- Output options available up to 1500 lumens.
- Nine drivers selections available to cover wide range of applications.
- Five year warranty.

Finish Options

☐ White	☐ Silver	☐ Mocha
☐ Black	☐ Charcoal	☐ Cerulean
☐ Firebrick	☐ Warm Nickel	
☐ Bronze	☐ Aged Brass	



Technical Information

TYPE	WD1830	TW2765
OUTPUT OPTIONS	700 lm (S/M/L)	1000 lm (M/L)
Fixture wattage	7.2 W	11.4 W
Delivered Lumen	819 lm	1288 lm
Efficacy	114 lm/W	113 lm/W
Center Beam Candlepower (20° Faceted Reflector)	1689 cd	2680 cd

CCT	CRI	R _f	R _g	R ₉
1800K	94	90	93	61
3000K	94	89	97	72
2700K	91	90	96	59
6500K	93	87	97	73

Ordering Code

Integral Driver Example: Fixture LET11M-WM-S-07-WD1830-F20-NA-WH-WH-RDS-WH-PHSD-NA

Remote Driver Example: Fixture LET11M-WM-S-07-WD1830-F20-NA-WH-WH-RDS-WH-PHSD-NA-HRM-LET11M-WM-07-WD1830-PHSD-NA

Fixture

MODEL	TYPE	SIZE	OUTPUT	CCT	OPTIC	ACCESSORY	BODY FINISH	BAFFLE FINISH
LET11M-Leto 11 Mini	WM-Wall Mount	S-Small M-Medium L-Large	07-700 lumens (7.2W) 07-700 lumens (7.2W) 10-1000 lumens (11.4W)	WD1830-Warm Dim, 1800K-3000K WD1830-Warm Dim, 1800K-3000K TW2765-Tunable White, 2700K-6500K ^{1,2}	F20-20 Degree, Faceted F30-30 Degree, Faceted F60-60 Degree, Faceted	NA-No Accessory DL-Diffusing Lens HC-Honeycomb Louver ⁴	Standard WH-White BK-Black S-Silver Premium ³ MA-Mocha CC-Charcoal CR-Cerulean FB-Firebrick BZ-Bronze WN-Warm Nickel AB-Aged Brass	Standard WH-White BK-Black S-Silver Premium ³ MA-Mocha CC-Charcoal CR-Cerulean FB-Firebrick BZ-Bronze WN-Warm Nickel AB-Aged Brass

CANOPY/ HOUSING	CANOPY FINISH	DRIVER	DRIVER OPTIONS ⁸
RDS-Round Slim SQS-Square Slim RDR-Round Semi-Recessed	Standard WH-White BK-Black S-Silver Premium ³ MA-Mocha CC-Charcoal CR-Cerulean FB-Firebrick BZ-Bronze WN-Warm Nickel AB-Aged Brass	PHSD-Forward/Reverse Phase, 1% Dimming, 120V Only 010S-0-10V, 1% Dimming, 120/277V 0103-0-10V, 1% Dimming, 347V Only ⁶ 010L-EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V ⁶ 010G-EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V ⁶ DALI-EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V (Standard as LOG) ^{5,9} DALI8-EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V (Standard as LOG) ^{5,9} LUTE-Lutron Hilume Ecodigital, 1% Dimming, 120V/277V ^{5,6} DMX-EldoLED, DMX, 0.1% Dimming, 120V/277V ⁶	NA-None EMG-Emergency Driver ^{6,7}

1 - TW2765 only available with Drivers 010L/010G/DALI8/DMX. Not available with EMG driver option.

2 - TW2765 requires HRM - Remote Power Supply.

3 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.

4 - Size Small is not available with accessory HC Honeycomb.

5 - LUTE driver is not available at 700 lumens.

6 - Drivers 0103/010L/010G/DALI/DALI8/DMX/LUTE/EMG are only available with HRM - Remote Power Supply.

7 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 0103, DMX, DALI8 or LUTE Driver.

8 - AVNLR/CSMB available upon request.

9 - DALI and DALI8 driver options use logarithmic dimming curve as standard. For LINEAR dimming curve, add "LIN" after the dimming code, i.e. DALI LIN


CONTACT FACTORY FOR MORE OPTIONS.

LETO 11 MINI


WALL MOUNT CYLINDER
TUNABLE WHITE & WARM DIM

Canopy


RDS Round Slim Canopy



SQS Square Slim Canopy



RDR Semi-Recessed



RDS or SQS	
Integral Drivers	PHSD, 010S
Remote Drivers	0103, 010L, 010G, DALI, DALI8, LUTE, DMX

RDR	
Integral Drivers	
Remote Drivers	PHSD, 010S, 0103, 010L, 010G, DALI, DALI8, LUTE, DMX

Lens & Accessory Options

DL Diffusing Lens



HC Honeycomb



Optics

FXX (20°, 30°, 60°) Faceted Reflector



LETO 11 MINI

WALL MOUNT CYLINDER
TUNABLE WHITE & WARM DIM

Remote Driver Housing

Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.


REMOTE DRIVER	MODEL	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM-Housing, Remote	LET11M-WM-Leto 11 Mini Wall Mount	Same as Fixture	Same as Fixture	Same as Fixture	Same as Fixture

Maximum mounting distance to luminaire using 18 AWG wire

010S	0103	PHSD	010L	010G	DALI	DMX	LUTE
16'	16'	16'	72'	72'	72'	149'	15'


4" J-box

Minimum volume required to mount drivers in junction box: 70mm x 40mm x 30mm.




Canopy	+	Driver
RDS	+	PHSD
RDS	+	010S
SQS	+	PHSD
SQS	+	010S

HRM Single with Externally Mounted Driver



Driver
0103
010L
010G
010S
DALI
LUTE


HRM Double



Driver
DALI8
DMX

EMG Emergency Driver

120 minute EMG operation time.



Driver
EMG

LETO 11 MINI

WALL MOUNT CYLINDER
TUNABLE WHITE & WARM DIM



Standard Finishes

BK
Black



WH
White



SL
Silver



Premium Finishes

MA
Mocha



CC
Charcoal



CR
Cerulean



FB
Firebrick



BZ
Bronze



WN
Warm Nickle



AB
Antique Bronze




LETO 11 MINI

WALL MOUNT CYLINDER
TUNABLE WHITE & WARM DIM

TM-30

Warm Dim 1800K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

Warm Dim 3000K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

Tunable White 2700K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

Tunable White 6500K



COLOR VECTOR GRAPHIC





— Reference Source — Test Source

Photometry

20° Faceted Reflector



30° Faceted Reflector



60° Faceted Reflector

