LETO 11 MINI WET

SURFACE MOUNT CYLINDER

TUNABLE WHITE & WARM DIM

senso by luminii

Features

- Faceted metal reflectors provide beam spreads between 20° to 60°.
- Output options available up to 1500 lumens.
- Nine drivers selections available to cover wide range of applications.
- Five year warranty.

WET · TITLE 24 JA8 COMPLIANT · RoHS · c UL us LISTED · Declare.


Finish Options

White · Silver · Mocha · Firebrick · Warm Nickle
Black · Charcoal · Cerulean · Bronze · Aged Brass









Made in Canada with Imported Parts

Technical Information

TYPE	WD1830			TW2765
OUTPUT OPTIONS	**700 lm (S/M/L)**	**1000 lm (M/L)**	**1500 lm (L)**	**1500 lm (L)**
Fixture wattage	8.5 W	13.2 W	16.6 W	18.8 W
Delivered Lumen	690 lm	1118 lm	1431 lm	1584 lm
Efficacy	81 lm/W	84.4 lm/W	86 lm/W	84 lm/W
Center Beam Candlepower (20° Faceted Reflector)	1453 cd	2342.6 cd	2962 cd	3184.4 cd

CCT	TM-30			
	CRI	R_f	R_g	R_9
1800K	94	90	93	61
3000K	94	89	97	72
2700K	91	90	96	59
6500K	93	87	97	73

Integral Driver Example: Fixture LET11MW-SM-S-07-WD1830-F20-NA-WH-WH-RDS-WH-PHSD-NA
Remote Driver Example: Fixture LET11MW-SM-S-07-WD1830-F20-NA-WH-WH-RDS-WH-PHSD-NA
HRM-LET11MW-SM-07-WD1830-PHSD-NA

Ordering Code

Fixture

MODEL	TYPE	SIZE	OUTPUT	CCT	OPTIC	ACCESSORY	BODY FINISH	BAFFLE FINISH
LET11MW - Leto 11 Mini Wet Rated	SM - Surface Mount	S - Small	07 - 700 lumens (8.5W)	WD1830 - Warm Dim, 1800K-3000K	F20 - 20 Degree, Faceted F30 - 30 Degree, Faceted F60 - 60 Degree, Faceted	NA - No Accessory[7] DF - Diffusing Film HC - Honeycomb Louver[4] AF - Asymmetric Film	Standard WH - White BK - Black SL - Silver Premium[1] MA - Mocha CC - Charcoal CR - Cerulean FB - Firebrick BZ - Bronze WN - Warm Nickel AB - Aged Brass	Standard WH - White BK - Black SL - Silver Premium[1] MA - Mocha CC - Charcoal CR - Cerulean FB - Firebrick BZ - Bronze WN - Warm Nickel AB - Aged Brass
		M - Medium	07 - 700 lumens (8.5W) 10 - 1000 lumens (13.2W)	WD1830 - Warm Dim, 1800K-3000K				
		L - Large	07 - 700 lumens (8.5W) 10 - 1000 lumens (13.2W) 15 - 1500 lumens (16.6W)	WD1830 - Warm Dim, 1800K-3000K				
		L - Large	15 - 1500 lumens (18.8W)	TW2765 - Tunable White, 2700K-6500K				


CANOPY/ HOUSING	CANOPY FINISH	DRIVER	DRIVER OPTIONS[6]
RDS - Round Slim	Standard WH - White BK - Black SL - Silver Premium[1] MA - Mocha CC - Charcoal CR - Cerulean FB - Firebrick BZ - Bronze WN - Warm Nickel AB - Aged Brass	PHSD - Forward/Reverse Phase, 1% Dimming, 120V Only 010S - 0-10V, 1% Dimming, 120/277V 0103 - 0-10V, 1% Dimming, 347V Only[4] 010L - EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V[4,8] 010G - EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V[4,8] DALI - EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V (Standard as LOG)[2,4] DALI8 - EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V (Standard as LOG)[2,4,8] LUTE - Lutron Hilume Ecodigital, 1% Dimming, 120V/277V[3,4] DMX - EldoLED, DMX, 0.1% Dimming, 120V/277V[4,8]	NA - None EMG - Emergency Driver[4,5,9]

1 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
2 - DALI and DALI8 driver options use logarithmic dimming curve as standard. For LINEAR dimming curve, add "LIN" after the dimming code, i.e. DALILIN
3 - LUTE driver is not available at 700 lumens.
4 - Drivers 0103/010L/010G/DALI/DALI8/DMX/LUTE/EMG are only available with Remote Power Supply.
5 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 0103, DMX, DALI8 or LUTE Driver.
6 - AWNR/CSMB available upon request.
7 - Fixture will come with a clear lens.
8 - TW2765 only available with drivers 010L/010G/DALI8/DMX.
9 - TW2765, cannot be used with EMG
CONTACT FACTORY FOR MORE OPTIONS.

info@luminii.com | luminii.com
*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

Canopy

RDS
Round Slim Canopy



Integral Drivers	Remote Drivers
PHSD 010S	0103 010L 010G DALI DALI8 LUTE DMX

Driver operation temprature -40C to 50C		
Control Type	**min.**	**max.**
PHSD,010S*	-10C	50C
DALI,DALI8,DMX	-20C	50C
LUTE	0C	45C
010L/010G	-20C	50C
0103	-40C	50C

*-40C to 50C ambient operation temperature when using remote option.

Lens & Accessory Options

DL
Diffusing Film



HC
Honeycomb



AF
Asymmetric Film



Optics

FXX (20°, 30°, 60°)
Faceted Reflector



info@luminii.com | luminii.com
*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

Remote Driver Housing


Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.

REMOTE DRIVER	MODEL	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM - Housing, Remote	LET11MW-SM - Leto 11 Mini Wet Surface Mount	Same as Fixture	Same as Fixture	Same as Fixture	Same as Fixture

Maximum mounting distance to luminaire using 18 AWG wire							
010S	0103	PHSD	010L	010G	DALI	DMX	LUTE
16'	16'	16'	72'	72'	72'	149'	15'


4" J-box

Minimum volume required to mount drivers in junction box: 70mm x 40mm x 30mm.




Canopy	+	Driver
RDS	+	PHSD
RDS	+	010S

HRM Single with Externally Mounted Driver



Driver
0103
010L
010G
010S
DALI
LUTE


HRM Double



Driver
DALI8
DMX

EMG Emergency Driver

120 minute EMG operation time.



Driver
EMG

*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

LETO 11 MINI WET

SURFACE MOUNT CYLINDER

TUNABLE WHITE & WARM DIM

Standard Finishes

BK
Black



WH
White



SL
Silver



Premium Finishes

MA
Mocha



CC
Charcoal



CR
Cerulean



FB
Firebrick



BZ
Bronze



WN
Warm Nickle



AB
Aged Brass




info@luminii.com | luminii.com

*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

TM-30


Warm Dim 1800K

COLOR VECTOR GRAPHIC




Warm Dim 3000K

COLOR VECTOR GRAPHIC




Tunable White 2700K

COLOR VECTOR GRAPHIC




Tunable White 6500K

COLOR VECTOR GRAPHIC




Photometry


Warm Dim 20° Faceted Reflector




CBCP




Tunable White 20° Faceted Reflector




CBCP




Warm Dim 30° Faceted Reflector




CBCP




Tunable White 30° Faceted Reflector




CBCP




Warm Dim 60° Faceted Reflector




CBCP



Tunable White 60° Faceted Reflector



CBCP



info@luminii.com | luminii.com

*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE