LETO 11 MINI WET

WALL MOUNT UP/DOWN CYLINDER

senso by luminii

Features

- Faceted metal reflectors provide beam spreads between 20° to 60°.
- Multiple options available between 500 - 1500 lumens.
- Nine drivers selections available to cover wide range of applications.
- IP65
- Five year warranty.


WET · TITLE 24 JA8 COMPLIANT · RoHS · c UL us LISTED · Declare.

Finish Options

White · Silver · Mocha · Firebrick · Warm Nickle
Black · Charcoal · Cerulean · Bronze · Aged Brass



Made in Canada with Imported Parts



Technical Information

OUTPUT OPTIONS		0505	1010	1515
Size		S/M/L	M/L	L
DOWN	Fixture wattage	5.5 W	10.0 W	15.5 W
	Delivered Lumen	500 lm	1002 lm	1449 lm
	Efficacy	90 lm/W	100 lm/W	93 lm/W
	Center Beam Candlepower (20° Faceted Reflector)	1489 cd	3096 cd	4010 cd
UP	Fixture wattage	5.5 W	10.0 W	15.5 W
	Delivered Lumen	500 lm	1000 lm	1430 lm
	Efficacy	90 lm/W	100 lm/W	93 lm/W

CCT	Multiplier	TM-30 CRI	TM-30 R_f	TM-30 R_g	TM-30 R_9
2500K	0.80	93+	93	102	50+
2700K	0.92	93+	92	100	50+
3000K	0.97	93+	92	103	50+
3500K	1.00	93+	93	102	50+
4000K	1.07	93+	92	101	50+
6500K	1.05	93+	92	101	50+

Integral Driver Example: Fixture LET11MW-WM-S-0505-25K-F20-NA-WH-WH-RDS-WH-PHSD-NA
Remote Driver Example: Fixture LET11MW-WM-S-0505-25K-F20-NA-WH-WH-RDS-WH-PHSD-NA HRM-LET11MW-WM-0505-25K-PHSD-NA

Ordering Code

Fixture

MODEL
- LET11MW - Leto 11 Mini Wet Rated

TYPE
- WM - Wall Mount

SIZE / OUTPUT
- S - Small: 0505 - 500/500 lumens
- M - Medium: 0505 - 500/500 lumens; 1010 - 1000/1000 lumens
- L - Large: 0505 - 500/500 lumens; 1010 - 1000/1000 lumens; 1515 - 1500/1500 lumens[1]

CCT
- 25K - 2500K
- 27K - 2700K
- 30K - 3000K
- 35K - 3500K
- 40K - 4000K
- 65K - 6500K

OPTIC
- F20 - 20 Degree, Faceted
- F30 - 30 Degree, Faceted
- F60 - 60 Degree, Faceted[2]

OPTIC UP
- F20 - 20 Degree, Faceted
- F30 - 30 Degree, Faceted
- F60 - 60 Degree, Faceted[2]

ACCESSORY
- NA - No Accessory[3]
- DF - Diffusing Film[4]
- HC - Honeycomb Louver[5]
- AF - Asymmetric Film[4]

BODY FINISH

Standard
- WH - White
- BK - Black
- SL - Silver

Premium[6]
- MA - Mocha
- CC - Charcoal
- CR - Cerulean
- FB - Firebrick
- BZ - Bronze
- WN - Warm Nickel
- AB - Aged Brass

BAFFLE FINISH

Standard
- WH - White
- BK - Black
- SL - Silver

Premium[6]
- MA - Mocha
- CC - Charcoal
- CR - Cerulean
- FB - Firebrick
- BZ - Bronze
- WN - Warm Nickel
- AB - Aged Brass

CANOPY/ HOUSING
- RDS - Round Slim

CANOPY FINISH

Standard
- WH - White
- BK - Black
- SL - Silver

Premium[6]
- MA - Mocha
- CC - Charcoal
- CR - Cerulean
- FB - Firebrick
- BZ - Bronze
- WN - Warm Nickel
- AB - Aged Brass

DRIVER
- PHSD - Forward/Reverse Phase, 1% Dimming, 120V Only
- 010S - 0-10V, 1% Dimming, 120/277V
- 0103 - 0-10V, 1% Dimming, 347V Only[8]
- 010L - EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V[8]
- 010G - EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V[8]
- DALI - EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V (Standard as LOG)[7,8]
- DALI8 - EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V (Standard as LOG)[7,8]
- LUTE - Lutron Hilume Ecodigital, 1% Dimming, 120V/277V[8]
- DMX - EldoLED, DMX, 0.1% Dimming, 120V/277V[8]

DRIVER OPTIONS[10]
- NA - None
- EMG - Emergency Driver[8,9]


1 - All drivers with Output 1515 are Remote (HRM) builds.
2 - Optic F60 (Up or Down), Not available with Size S - Small.
3 - Fixture will come with a clear lens.
4 - Accessory DF and AF available for UP light by MOD request. All accessories available for Downlight.
5 - Accessory HC, Honeycomb. Not available on Size S, Small.
6 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
7 - DALI and DALI8 driver options use logarithmic dimming curve as standard. For LINEAR dimming curve, add "LIN" after the dimming code, i.e. DALILIN
8 - Drivers 0103/010L/010G/DALI/DALI8/DMX/LUTE/EMG are only available with Remote Power Supply.
9 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 0103, DMX, DALI8 or LUTE Driver.
10 - AWNR/CSMB available upon request.

CONTACT FACTORY FOR MORE OPTIONS.

info@luminii.com | luminii.com
*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

Canopy

RDS
Round Slim Canopy



Integral Drivers	Remote Drivers
PHSD 010S	0103 010L 010G DALI DALI8 LUTE DMX

Driver operation temprature -40C to 50C		
Control Type	**min.**	**max.**
PHSD,010S*	-10C	50C
DALI,DALI8,DMX	-20C	50C
LUTE	0C	45C
010L/010G	-20C	50C
0103	-40C	50C

*-40C to 50C ambient operation temperature when using remote option.

Lens & Accessory Options

DL
Diffusing Film



HC
Honeycomb



AF
Asymmetric Film



Optics

FXX (20°, 30°, 60°)
Faceted Reflector



info@luminii.com | luminii.com

*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

Remote Driver Housing


Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.

REMOTE DRIVER	MODEL	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM-Housing, Remote	LET11MW-WM-Leto 11 Mini Wet Wall Mount	Same as Fixture	Same as Fixture	Same as Fixture	Same as Fixture

Maximum mounting distance to luminaire using 18 AWG wire							
010S	0103	PHSD	010L	010G	DALI	DMX	LUTE
16'	16'	16'	72'	72'	72'	149'	15'


4" J-box - For Output option 0505, 1010 only.

Minimum volume required to mount drivers in junction box: 70mm x 40mm x 30mm.




Canopy	+	Driver
RDS	+	PHSD
RDS	+	010S

HRM Single with Externally Mounted Driver



Driver
0103
010L
010G
010S
DALI
LUTE


HRM Double



Driver
DALI8
DMX

EMG Emergency Driver

120 minute EMG operation time.



Driver
EMG

*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

LETO 11 MINI WET

WALL MOUNT UP/DOWN CYLINDER

senso by luminii

Standard Finishes

BK
Black



WH
White



SL
Silver



Premium Finishes

MA
Mocha



CC
Charcoal



CR
Cerulean



FB
Firebrick



BZ
Bronze



WN
Warm Nickle



AB
Aged Brass




info@luminii.com | luminii.com

*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE

TM-30

2500K


COLOR VECTOR GRAPHIC



Reference Source Test Source

2700K


COLOR VECTOR GRAPHIC



Reference Source Test Source

3000K


COLOR VECTOR GRAPHIC



Reference Source Test Source

3500K


COLOR VECTOR GRAPHIC



Reference Source Test Source

4000K


COLOR VECTOR GRAPHIC



Reference Source Test Source

6500K

COLOR VECTOR GRAPHIC




Reference Source Test Source


info@luminii.com | luminii.com

*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE


Photometry


20° Faceted Reflector Down, 20° Faceted Reflector Up







30° Faceted Reflector Down, 30° Faceted Reflector Up





60° Faceted Reflector Down, 60° Faceted Reflector Up





info@luminii.com | luminii.com
*LUMINII RESERVES THE RIGHTS TO CHANGE SPECIFICATION & INSTRUCTION WITHOUT NOTICE