


Features

- Nine drivers selections available to cover wide range of applications.
- Three output options available up to 2000 lumens.
- Five year warranty.

Finish Options



Technical Information

TYPE	WD1830		TW2765	
OUTPUT OPTIONS	700 lm	1000 lm	1300 lm	1300 lm
Fixture wattage	6.7 W	11.2 W	14.5 W	13.4 W
Delivered Lumen at full on	775 lm	859 lm	1095 lm	1145 lm
Efficacy	116 lm/W	77 lm/W	76 lm/W	85 lm/W
Center Beam Candlepower	5680 cd	1249 cd	1632 cd	7495 cd

TM-30				
CCT	CRI	R _f	R _g	R ₉
1800K	94	90	93	61
3000K	94	89	97	72
2700K	91	90	96	59
6500K	93	87	97	73

Integral Driver Example: Fixture LET115-S-07-WD1830-ASM-DL-WH-WH-RD-WH-2AF-NA-PHSD-NA
Remote Driver Example: Fixture LET11-S-07-WD1830-ASM-DL-WH-WH-RD-WH-2AF-NA-010L-NA
HRM-LET115-S-07-WD1830-010L-NA

Ordering Code

Fixture

MODEL	TYPE	OUTPUT	CCT	OPTIC	ACCESSORY	BODY FINISH	BAFFLE FINISH
LET115 - Leto 11.5	S - Suspended	07 - 700 lumens ¹ 10 - 1000 lumens 13 - 1300 lumens	WD1830 - Warm Dim, 1800K-3000K TW2765 - Tunable White, 2700K-6500K ¹¹	ASM - Asymmetric	DL - Diffusing Lens	Standard WH - White BK - Black SL - Silver	Standard WH - White BK - Black SL - Silver

CANOPY/ HOUSING	CANOPY FINISH	SUSPENSION TYPE	SUSPENSION FINISH	DRIVER	DRIVER OPTIONS
RD - Round RTL - Round Trimless ^{3,5} SQ - Square	Standard WH - White BK - Black SL - Silver	2AF - 2AC+Feed Cable SS2 - Solid Stem, 2ft SS3 - Solid Stem, 3ft SS6 - Solid Stem, 6ft HS2 - Hang Straight, 2ft ⁵ HS3 - Hang Straight, 3ft ⁵ HS6 - Hang Straight, 6ft ⁵ POA - 2 Powered Aircraft	Standard NA - None ⁷ CL - Clear ¹² WH - White BK - Black SL - Silver ⁶	PHSD - Forward/Reverse Phase, 1% Dimming, 120V Only 010S - 0-10V, 1% Dimming, 120/277V 0103 - 0-10V, 1% Dimming, 347V Only 010L - EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V ⁴ 010G - EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V ⁴ DALI - EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V (Standard as LOG) ¹³ DALI8 - EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V (Standard as LOG) ¹³ LUTE - Lutron Hilmate Ecodigital, 1% Dimming, 120V/277V DMX - EldoLED, DMX, 0.1% Dimming, 120V/277V ³	NA - None EMG - Emergency Driver ^{3,8} CSMB - Casambi ^{9,10} AWNR - Athena ^{9,10}

1 - 700 lumens is not available with LUTE driver.
2 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
3 - All drivers remote mounted when using RTL canopy, DALI8 driver, DMX driver, or EMG driver options.
4 - Requires square canopy SQ for integral driver, otherwise remote mounted.
5 - RTL canopy is not available with HS2/HS3/HS6 suspension.
6 - These finishes are only available with SS Solid Stem or HS Hang Straight.
7 - Must select NA None when POA option is selected.

8 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes.
Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 010S, DMX, DALI8 or LUTE Driver.
9 - AWNR/CSMB only available with 010S driver and RD/SQ canopy.
10 - AWNR/CSMB available upon request with RTL canopy.
11 - TW2765 only available with 13 lumens and 010L/010G/DALI8/DMX. Always remote mounted. Cannot use with EMG.
12 - Clear Suspension Finish only available with 2AF.
13 - DALI and DALI8 driver options use logarithmic dimming curve as standard. For LINEAR dimming curve, add "LIN" after the dimming code, i.e. DALI LIN

Canopy

RD

Round Canopy

	Integral Drivers	Remote Drivers
010S	010L	
0103	010G	
PHSD	DALI	
	DALI8	
	LUTE	
	DMX	



Please see next page for Remote Driver Housing details.

RTL

Round Trimless Canopy

	Integral Drivers	Remote Drivers
N/A	010S	
	0103	
	PHSD	
	010L	
	010G	
	DALI	
	DALI8	
	LUTE	
	DMX	



SQ

Square Canopy

	Integral Drivers	Remote Drivers
010S	DMX	
0103	DALI8	
PHSD		
010L		
010G		
DALI		
DALI8		
LUTE		



Suspension

2AF

2 Aircraft + Feed Cable



SSX

{2', 3', 6' max} Solid Stem



HSX

{2', 3', 6' max} Hang Straight Solid Stem



POA

2 Powered Aircraft



Maximum Slope: 30°

Lens

DL

Diffusing Lens



Light Loss Factor: 87%*

*Light Loss Factor calculated with 60° faceted reflector.


Remote Driver Housing

Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.

REMOTE DRIVER	MODEL	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM-Housing, Remote	LET115-S-Leto 11.5 Suspended	Same as Fixture	Same as Fixture	Same as Fixture	Same as Fixture


Maximum mounting distance to luminaire using 18 AWG wire						
010S	PHSD	010L	010G	DALI DALI8	DMX	LUTE
16'	16'	72'	72'	72'	149'	15'

HRM Single with Externally Mounted Driver




Canopy	+	Driver
RTL or RD	+	010L or 010G
RTL or RD	+	010S
RTL	+	010L or 010G or 010S
RTL or RD	+	DALI or LUTE

HRM Single



Canopy	+	Driver
RTL	+	PHSD


HRM Double



Driver
DALI8
DMX

EMG Emergency Driver

120 minute EMG operation time.



Driver
EMG

Standard Colors

BK
Black

WH
White

SL
Silver


Premium Colors

MA
Mocha



CC
Charcoal

CR
Cerulean

FB
Firebrick



Two Tone Finishes

Inside finish refers to Baffle Finish selection from page 1. Any combination may be used for baffle and body finishes.




TM-30


Warm Dim 1800K




Warm Dim 3000K



Tunable White 2700K



Tunable White 6500K



Photometry

Diffusing Lens

