


Features

- Faceted and Smooth metal reflectors, along with TIR optics provide beam spreads between 10° to 80°.
- Nine drivers selections available to cover wide range of applications.
- Three output options available up to 1500 lumens.
- 5 year warranty.



Finish Options



Made in Canada
with Imported Parts

Technical Information

OUTPUT OPTIONS	700 lm	1000 lm	1500 lm
Fixture wattage	6.1 W	9.1 W	14.0 W
Delivered Lumen at 3500K	647 lm	965 lm	1474 lm
Efficacy	106 lm/W	106 lm/W	105 lm/W
Center Beam Candlepower (10° Faceted Reflector)	5399 cd	8052 cd	12300 cd

CCT	Multiplier	CRI	TM-30		
			R _f	R _g	R _g
2500K	0.81	92	90	104	77
2700K	0.92	92	91	102	61
3000K	0.97	95	92	102	61
3500K	1.00	95	93	101	72
4000K	1.07	95	92	103	68
6500K	1.05	96	91	100	89

Ordering Code

Fixture

MODEL	TYPE	OUTPUT	CCT	OPTIC	ACCESSORY	BODY FINISH	BAFFLE FINISH
LET115	WM	07-700 lumens (6.1W) 10-1000 lumens (9.1W) 15-1500 lumens (14.0W)	25K-2500K 27K-2700K 30K-3000K 35K-3500K 40K-4000K 65K-6500K	F10-10 Degree, Faceted F18-18 Degree, Faceted F30-30 Degree, Faceted F45-45 Degree, Faceted F60-60 Degree, Faceted S30-30 Degree, Smooth S45-45 Degree, Smooth S80-80 Degree, Smooth	NA - No Accessory CL - Clear Lens DL - Diffusing Lens HC - Honeycomb Louver SL - Solite Lens	Standard WH - White BK - Black SL - Silver	Standard WH - White BK - Black SL - Silver

Premium ²	Premium ²
MA - Mocha CC - Charcoal CR - Cerulean FB - Firebrick	MA - Mocha CC - Charcoal CR - Cerulean FB - Firebrick

DRIVER ³	DRIVER OPTIONS ⁴
	NA - None EMG - Emergency Driver ⁴

PHSD - Forward/Reverse Phase, 1% Dimming, 120V Only
010S - 0-10V, 1% Dimming, 120V/277V
0103 - 0-10V, 1% Dimming, 347V Only
010L - EldoLED, 0-10V, Linear, 0.1% Dimming, 120V/277V
010G - EldoLED, 0-10V, Log, 0.1% Dimming, 120V/277V
DALI - EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120V/277V (Standard as LOG)⁵
DALI8 - EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120V/277V (Standard as LOG)⁵
LUTE - Lutron Hilume Ecodigital, 1% Dimming, 120V/277V
DMX - EldoLED, DMX, 0.1% Dimming, 120V/277V

NA - None
EMG - Emergency Driver⁴

1 - 700 lumens is not available with LUTE driver.

2 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.

3 - All drivers remote except PHSD/010S driver options.

4 - Emergency remote except prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 010S, DMX, DALI8 or LUTE Driver.

5 - AVNR/CSMB available upon request, contact Senso for details.

6 - DALI and DALI8 driver options use logarithmic dimming curve as standard. For LINEAR dimming curve, add "LIN" after the dimming code, i.e. DALI LIN

CONTACT FACTORY FOR MORE OPTIONS.

Lens & Accessory Options

OPTC-ACC-CL-94MM

Clear Lens

Also available with complete fixture, use ordering code.
-CL



Light Loss Factor: 100%*

OPTC-ACC-DL-94MM

Diffusing Lens

Also available with complete fixture, use ordering code.
-DL



Light Loss Factor: 87%*

OPTC-ACC-HC-94MM

Honeycomb Lens

Also available with complete fixture, use ordering code.
-HC



Light Loss Factor: 45%*

OPTC-ACC-SL-94MM

Solite Lens

Also available with complete fixture, use ordering code.
-SL



Light Loss Factor: 92%*

*Light Loss Factor calculated with 60° faceted reflector.

Optics

RFLC-FXX-94MM

Faceted Reflector

Also available with complete fixture, use ordering code.
-F10/-F18/-F30/-F45/-F60



RFLC-SXX-94MM

Smooth Reflector

Also available with complete fixture, use ordering code.
-S30/-S45/-S80



FXX	Optic
F10	10° Faceted
F18	18° Faceted
F30	30° Faceted
F45	45° Faceted
F60	60° Faceted
S30	30° Smooth
S45	45° Smooth
S80	80° Smooth

Remote Driver Housing


Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.

REMOTE DRIVER	MODEL	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM-Housing, Remote	LET115-WM-Leto 11.5 Wall Mount	Same as Fixture	Same as Fixture	Same as Fixture	Same as Fixture

Maximum mounting distance to luminaire using 18 AWG wire						
010S	PHSD	010L	010G	DALI DALI8	DMX	LUTE
16'	16'	72'	72'	72'	149'	15'


4" J-box

Minimum volume required to mount drivers in junction box: 70mm x 40mm x 30mm.




Driver
PHSD
010S

HRM Single with Externally Mounted Driver




Driver
010L or 010G
010S
010L or 010G or 010S
DALI or LUTE

HRM Single



Driver
PHSD


HRM Double



Driver
DALI8
DMX

EMG Emergency Driver

120 minute EMG operation time.



Driver
EMG

Standard Finishes

BK
Black



WH
White



SL
Silver



Premium Finishes


MA
Mocha



CC
Charcoal



CR
Cerulean




FB
Firebrick




Two Tone Baffle

Inside finish refers to Baffle Finish selection from page 1. Any combination may be used for baffle and body finishes.




TM-30


2500K




2700K




3000K




3500K



4000K




6500K




Photometry


10° Faceted Reflector




30° Smooth Reflector




18° Faceted Reflector




45° Smooth Reflector




30° Faceted Reflector



80° Smooth Reflector



45° Faceted Reflector



60° Faceted Reflector

