

# LETO 44 MINI

## SUSPENDED CYLINDER

### TUNABLE WHITE & WARM DIM


senso  
by luminii

#### Features

- Faceted metal reflectors provide beam spreads between 20° to 60°.
- Three output options available up to 1500 lumens.
- Nine drivers selections available to cover wide range of applications.
- Five year warranty.

#### Finish Options

|                                |                                   |                                   |                                    |                                      |
|--------------------------------|-----------------------------------|-----------------------------------|------------------------------------|--------------------------------------|
| <input type="checkbox"/> White | <input type="checkbox"/> Silver   | <input type="checkbox"/> Mocha    | <input type="checkbox"/> Firebrick | <input type="checkbox"/> Warm Nickel |
| <input type="checkbox"/> Black | <input type="checkbox"/> Charcoal | <input type="checkbox"/> Cerulean | <input type="checkbox"/> Bronze    | <input type="checkbox"/> Aged Brass  |



Made in Canada  
with Imported Parts

TITLE 24  
JA8  
COMPLIANT  
RoHS  
cUL  
LISTED

#### Technical Information

| TYPE   | WD1830         |               |               | TW2765 |
|--|----------------|---------------|---------------|--------|
| OUTPUT OPTIONS                                     | 700 lm (S/M/L) | 1000 lm (M/L) | 1500 lm (M/L) |        |
| Fixture wattage                                    | 7.2 W          | 11.4 W        | 16.5 W        |        |
| Delivered Lumen                                    | 819 lm         | 1288 lm       | 1617 lm       |        |
| Efficacy   | 114 lm/W       | 113 lm/W      | 98 lm/W       |        |
| Center Beam Candlepower<br>(20° Faceted Reflector) | 1689 cd        | 2680 cd       | 3464 cd       |        |

| CCT   | TM-30 |                |                |                |
|-------|-------|----------------|----------------|----------------|
|       | CRI   | R <sub>f</sub> | R <sub>g</sub> | R <sub>g</sub> |
| 1800K | 94    | 90             | 93             | 61             |
| 3000K | 94    | 89             | 97             | 72             |
| 2700K | 91    | 90             | 96             | 59             |
| 6500K | 93    | 87             | 97             | 73             |

#### Ordering Code

Integral Driver Example: Fixture LET44M-S-S-07-WD1830-F20-NA-WH-WH-RDS-WH-SS2-NA-PHSD-NA

Remote Driver Example: Fixture LET44M-S-S-07-WD1830-F20-NA-WH-WH-RDS-WH-SS2-NA-PHSD-NA-HRM-LET44M-S-07-WD1830-PHSD-NA

#### Fixture

| MODEL               | TYPE        | SIZE                | OUTPUT   | CCT  | OPTIC  | ACCESSORY  | BODY FINISH  | BAFFLE FINISH  |
|---------------------|-------------|---------------------|--|--|--|--|--|--|
| LET44M-Leto 44 Mini | S-Suspended | S-Small             | 07-700 lumens (7.2W)                           | WD1830-Warm Dim, 1800K-3000K                     | F20-20 Degree, Faceted<br>F30-30 Degree, Faceted<br>F60-60 Degree, Faceted | NA-No Accessory<br>DL-Diffusing Lens<br>HC-Honeycomb Louver <sup>4</sup> | Standard<br>WH-White<br>BK-Black<br>SL-Silver  | Standard<br>WH-White<br>BK-Black<br>SL-Silver  |
|                     |             | M-Medium<br>L-large | 07-700 lumens (7.2W)<br>10-1000 lumens (11.4W) | WD1830-Warm Dim, 1800K-3000K                     |  |  | Premium <sup>3</sup><br>MA-Mocha<br>CC-Charcoal<br>CR-Cerulean<br>FB-Firebrick<br>BZ-Bronze<br>WN-Warm Nickel<br>AB-Aged Brass | Premium <sup>3</sup><br>MA-Mocha<br>CC-Charcoal<br>CR-Cerulean<br>FB-Firebrick<br>BZ-Bronze<br>WN-Warm Nickel<br>AB-Aged Brass |
|                     |             | M-Medium<br>L-large | 15-1500 lumens (16.5W)                         | TW2765-Tunable White, 2700K-6500K <sup>1,2</sup> |  |  |  |  |

| CANOPY/ HOUSING  | CANOPY FINISH  | SUSPENSION TYPE  | SUSPENSION FINISH   | DRIVER  | DRIVER OPTIONS <sup>11</sup>                    |
|--|--|--|---|---|---|
| RDS-Round Slim<br>SQS-Square Slim<br>RTL-Round Flangeless<br>SQR-Square Semi-Recessed <sup>5</sup> | Standard<br>WH-White<br>BK-Black<br>SL-Silver  | SS2-Solid Stem, 2ft<br>SS3-Solid Stem, 3ft<br>SS6-Solid Stem, 6ft<br>POA-2 Powered Aircraft, 6ft | Standard<br>NA-None <sup>6</sup><br>WH-White<br>BK-Black<br>SL-Silver <sup>7</sup>  | PHSD-Forward/Reverse Phase, 1% Dimming, 120V Only <sup>5</sup><br>010S-0-10V, 1% Dimming, 120/277V <sup>5</sup><br>0103-0-10V, 1% Dimming, 347V Only <sup>9</sup><br>010L-EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V <sup>9</sup><br>010G-EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V <sup>9</sup><br>DALI-EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V <sup>9</sup><br>(Standard as LOG) <sup>12</sup><br>DALI8-EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V <sup>9</sup><br>(Standard as LOG) <sup>12</sup><br>LUTE-Lutron Hilume Ecdigital, 1% Dimming, 120V/277V <sup>8,9</sup><br>DMX-EldoLED, DMX, 0.1% Dimming, 120V/277V <sup>9</sup> | NA-None<br>EMG-Emergency Driver <sup>9,10</sup> |
|  | Premium <sup>3</sup><br>MA-Mocha<br>CC-Charcoal<br>CR-Cerulean<br>FB-Firebrick<br>BZ-Bronze<br>WN-Warm Nickel<br>AB-Aged Brass |  | Premium <sup>3</sup><br>MA-Mocha <sup>7</sup><br>CC-Charcoal <sup>7</sup><br>CR-Cerulean <sup>7</sup><br>FB-Firebrick <sup>7</sup><br>BZ-Bronze <sup>7</sup><br>WN-Warm Nickel <sup>7</sup><br>AB-Aged Brass <sup>7</sup> |   |   |

1 - TW2765 only available with Drivers 010L/010G/DALI8/DMX. Not available with EMG driver option.

2 - TW2765 requires HRM - Remote Power Supply.

3 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.

4 - HC Honeycomb Louver is not available with size small.

5 - SQR Canopy with PHSD/010S is not available with 700 lumens.

6 - Must select NA None when POA 2 Powered Aircraft Suspension is selected.

7 - These finishes are only available with SS Solid Stem.

8 - LUTE driver is not available at 700 lumens.

9 - Drivers 0103/010L/010G/DALI8/DMX/LUTE/EMG are only available with HRM - Remote Power Supply.

10 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 0103, DMX, DA18 or LUTE Driver.

11 - AVNR/CSMB available upon request.


12 - DALI and DALI8 driver options use logarithmic dimming curve as standard. For LINEAR dimming curve, add "LIN" after the dimming code, i.e. DALI1LIN.

CONTACT FACTORY FOR MORE OPTIONS.

## Canopy


### RDS

Round Slim Canopy




### SQS

Square Slim Canopy




### RTL

Round Flangless Canopy



### SQR

Semi-Recessed




| RDS or SQS or SQR | RTL  |
|-------------------|--|
| Integral Drivers  | PHSD, 010S   |
| Remote Drivers    | 0103, 010L, 010G, DALI, DALI8, LUTE, DMX             |
|                   | PHSD, 010S, 0103, 010L, 010G, DALI, DALI8, LUTE, DMX |

## Suspension

**SSX** (2', 3', 6' max)  
Solid Stem



**POA** (6' incl.)  
2 Powered Aircraft



## Lens & Accessory Options

**DL**  
Diffusing Lens



**HC**  
Honeycomb



## Optics

**FXX** (20°, 30°, 60°)  
Faceted Reflector



### Remote Driver Housing


Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.

| REMOTE DRIVER       | MODEL                           | OUTPUT          | CCT             | DRIVER          | DRIVER OPTIONS  |
|---------------------|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| HRM-Housing, Remote | LET44M-S-Leto 44 Mini Suspended | Same as Fixture | Same as Fixture | Same as Fixture | Same as Fixture |

| Maximum mounting distance to luminaire using 18 AWG wire |      |      |      |      |      |       |      |      |
|--|------|------|------|------|------|-------|------|------|
| PHSD   | 010S | 0103 | 010L | 010G | DALI | DALI8 | LUTE | DMX  |
| 16'  | 16'  | 16'  | 72'  | 72'  | 72'  | 72'   | 15'  | 149' |


### 4" Jbox

Minimum volume required to mount drivers in junction box: 70mm x 40mm x 30mm.




| Canopy | + | Driver |
|--------|---|--------|
| RDS    | + | PHSD   |
| RDS    | + | 010S   |
| SQS    | + | PHSD   |
| SQS    | + | 010S   |

### HRM Single with Externally Mounted Driver




| Driver |
|--------|
| 0103   |
| 010L   |
| 010G   |
| 010S   |
| DALI   |
| LUTE   |

### HRM Double



| Driver |
|--------|
| DALI8  |
| DMX    |


### HRM Cylinder Driver



| Canopy | + | Driver |
|--------|---|--------|
| SQR    | + | 010S   |
| SQR    | + | PHSD   |

### EMG Emergency Driver

120 minute EMG operation time.




| Driver |
|--------|
| EMG    |

## Standard Finishes

**BK**  
Black



**WH**  
White



**SL**  
Silver



## Premium Finishes

**MA**  
Mocha



**CC**  
Charcoal



**CR**  
Cerulean



**FB**  
Firebrick



**BZ**  
Bronze



**WN**  
Warm Nickel




**AB**  
Antique Bronze




## TM-30


### Warm Dim 1800K




### Warm Dim 3000K



### Tunable White 2700K





### Tunable White 6500K





## Photometry

### 20° Faceted Reflector



### 30° Faceted Reflector



### 60° Faceted Reflector

