



Features

- 24VDC Class 2 fixtures made to order up to 144". Fixtures can be linked up to 90' depending on output
- Suitable for undercabinet, millwork, direct view, vanity, architectural reveals, accent lighting and surface mount applications
- Approved for closet/storage space installation per NEC 410.16(A) (3) and 410.16(C)(5) on outputs 5.7 W/ft or less
- Dot free even illumination with frosted lens and high color quality outputs
- Class 2 listed for damp locations
- Proprietary strong bond solder method handles up to 50 lbs of pull force on wire leads and connectors
- Vibrant Color options offer premium color quality with R9 values up to 98
- High Efficacy options offer best in class output and efficacy with over 910 lm/ft and up to 129 lm/W
- Average Life (L70): 50,000hrs
- 7 Year warranty



Finish Options (see page 3 for additional information)

Base	Silver Anodized				
Powder Coat	Black	Bronze	White		
Premium	Matte Black	Warm Nickel	Aged Brass	Polished Gold	Chrome

Technical Information

TYPE	Vibrant Color VC72					
OUTPUT OPTIONS	**VC72VLO**	**VC72LO**	**VC72SO**	**VC72MO**	**VC72HO**	**VC72VHO**
Lumens Output (3000K) (with a Clear Lens)	103 lm/ft	262 lm/ft	349 lm/ft	461 lm/ft	557 lm/ft	742 lm/ft
Average Power Consumption (for a 4' section)	1.1 W/ft	2.8 W/ft	3.7 W/ft	4.9 W/ft	5.9 W/ft	7.9 W/ft
Efficacy	94 lm/W	94 lm/W	94 lm/W	94 lm/W	94 lm/W	94 lm/W
Max Run Length (in series)	56.9 ft	32 ft	28 ft	24 ft	21 ft	18 ft
Ambient Operating Temperature Range*	-4°F – 122°F (-20°C – 50°C)			-4°F – 113°F (-20°C – 45°C)	-4°F – 104°F (-20°C – 40°C)	-4°F – 86°F (-20°C – 30°C)

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

Vibrant Color (VC72)

CCT	Multiplier (ref. - 30K)	TM-30 CRI	TM-30 R_f	TM-30 R_g	TM-30 R_9
1800K	0.50	95	94	99	86
2200K	0.66	96	94	101	95
2400K	0.90	98	96	101	91
2700K	0.93	98	96	102	93
3000K	1.00	97	94	104	99
3500K	1.04	96	94	105	97
4100K	1.05	97	95	104	96

TYPE	High Efficacy HE64					
OUTPUT OPTIONS	**HE64VLO**	**HE64LO**	**HE64SO**	**HE64MO**	**HE64HO**	**HE64VHO**
Lumens Output (3000K) (with a Clear Lens)	114 lm/ft	246 lm/ft	353 lm/ft	469 lm/ft	666 lm/ft	914 lm/ft
Average Power Consumption (for a 4' section)	1 W/ ft	1.9 W/ ft	2.9 W/ ft	3.8 W/ ft	5.6 W/ ft	7.1 W/ ft
Efficacy	114 lm/W	129 lm/W	122 lm/W	123 lm/W	119 lm/W	129 lm/W
Max Run Length (in series)	90 ft	55 ft	34.9 ft	26 ft	17 ft	13 ft
Ambient Operating Temperature Range*	-4°F – 122°F (-20°C – 50°C)				-4°F – 104°F (-20°C – 40°C)	-4°F – 95°F (-20°C – 35°C)

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

High Efficacy (HE64)

CCT	Multiplier (ref. - 30K)	TM-30 CRI	TM-30 R_f	TM-30 R_g	TM-30 R_9
2200K	0.74	94	91	96	65
2400K	0.87	94	92	97	56
2700K	0.97	94	92	100	57
3000K	1.00	93	91	99	54
3500K	1.01	95	91	99	62
4000K	1.04	95	91	99	68

Ordering Code

MODEL - LENGTH[1] - OUTPUT[2] - CCT - LENS - MOUNTING - FINISH[3] - FEED POSITION LEFT[5] - FEED POSITION RIGHT[5]

MODEL
MK - Myka

LENGTH[1]
12"–144" 1" increments
12"–144" 2" increments

OUTPUT[2]
VC72VLO - Very Low
VC72LO - Low
VC72SO - Standard
VC72MO - Medium
VC72HO - High
VC72VHO - Very High
HE64VLO - Very Low
HE64LO - Low
HE64SO - Standard
HE64MO - Medium
HE64HO - High
HE64VHO - Very High

CCT
18K - 1800K
22K - 2200K
24K - 2400K
27K - 2700K
30K - 3000K
35K - 3500K
41K - 4100K
22K - 2200K
24K - 2400K
27K - 2700K
30K - 3000K
35K - 3500K
40K - 4000K

LENS
C - Clear
HF - Half Frosted
F - Frosted
MF - Matte Frosted
BLV - Black Blade Louver
WLV - White Blade Louver

MOUNTING
CB - Concealed Bracket
MAG - Magnetic
A - Adjustable Hinge Mounting

FINISH[3]
BASE
SA - Silver Anodized
POWDER COAT
BK - Black
BZ - Bronze
WH - White
PREMIUM
MBK - Matte Black
WN - Warm Nickel
AB - Aged Brass
PG - Polished Gold[4]
CH - Chrome[4]


FEED POSITION LEFT[5]
WIRE LEADS (72")
LWE - Wire End Feed
LWB - Wire Back Feed
LNPF - No Power Feed
QUICK CONNECTS (4")
LFE - Female Q/C, End Feed
LFB - Female Q/C, Back Feed
LNPF - No Power Feed

FEED POSITION RIGHT[5]
WIRE LEADS (72")
RWE - Wire End Feed
RWB - Wire Back Feed
RNPF - No Power Feed
QUICK CONNECTS (4")
RFE - Female Q/C, End Feed
RFB - Female Q/C, Back Feed
RNPF - No Power Feed

1 - Custom lengths and increments are available, please consult Inside Sales with specific request.
2 - Title 24 JA8 achievable depending on Output, CCT, and Lens selections. See multiplier charts to calculate specific efficacies.
3 - Non Base finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
4 - Polished Gold, and Chrome finishes have a maximum fixture length of 96".
5 - LNPF - RNPF is not a valid configuration option

Powerfeeds and Connectors


Power Feed Position Options and Orientation




Arrows indicate light directions.
Diagram not representative of mounting options available.

Luminii defines LEFT when the fixture lens is facing upwards. For asymmetric fixtures/lens', Luminii defined LEFT when the lens is facing up and towards the user.


Linking and Extension Cable Options




LMC-12
Male quick-connect, 2 pin, 12"




LMC-70
Male quick-connect long, 2 pin, 70"







EC-12
Female to Female Extension Cable, 2 pin, 12"




EC-48
Female to Female Extension Cable, 2 pin, 48"




EC-120
Female to Female Extension Cable, 2 pin, 120"







LYC
1 Female to 2 Male Splitter Cable, 2 pin, 12"




FMA
Female to male adapter




IS-DC
Male to Female Inline DC Switch, 2 pin, 12"







Sample Layout








End feed shown




Back feed shown

Product Dimensions


Fixture/Lens Profile With Frosted Lens




Fixture/Lens Profile With Blade Louver




Fixture Side




Fixture/Mounting Profile




Blade Louver Lens with Concealed Bracket



Frosted Lens using Magnetic Tape






Frosted Lens using the Adjustable Bracket

Finish Options


- Finish options are available in a wide variety, allowing for complete customization of style and aesthetic.
- Non Base finishes may have extended lead times and price adder.
- Polished Gold and Chrome finishes have a maximum fixture length of 96".
- Custom RALs are available, please consult Inside Sales with specific request.

Silver Anodized
Base



Silver Anodized is a soft silver with a clear finish.

Black
Powder Coat



Black is a true deep black with a glossy finish.

Bronze
Powder Coat




Bronze is a rich, dark brown with a satin finish.

White
Powder Coat


White is a polar bright white and field paintable.

Matte Black
Premium




Matte Black is a dark, pitch-black with a soft flat finish.

Warm Nickel
Premium




Warm Nickel is a soft, silvery smoke with warm tones and a satin finish.

Aged Brass
Premium




Aged Brass is a deep brown shade with slightly golden undertones.

Polished Gold
Premium



Polished Gold is bright and radiant for a brilliant finish.

Chrome
Premium




Chrome is a highly reflective silver polish.

Light Transmission and Dotting

	Lens/Accessory																							
Output Options	**Clear Lens**				**Half Frosted Lens**				**Frosted Lens**				**Black Blade Louver**				**White Blade Louver**				**Matte Frosted Lens**			
Dimming Level	100%	50%	10%	1%	100%	50%	10%	1%	100%	50%	10%	1%	100%	50%	10%	1%	100%	50%	10%	1%	100%	50%	10%	1%
VC72VLO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
VC72LO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
VC72SO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
VC72MO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
VC72HO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
VC72VHO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
HE64VLO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
HE64LO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
HE64SO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
HE64MO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
HE64HO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
HE64VHO	CD	CD	CD	CD	ND	SD	SD	CD	ND	ND	SD	SD	ND	ND	ND	ND	ND	ND	ND	ND	ND	SD	SD	CD
Transmission Percentage	100%				84%				60%				31%				53%				73%			

Use complete Dotting Chart Tool online for more dotting information

I'm also click-able




CD - Clear Dotting

SD - Slight Dotting


ND - No Dotting

Accessory Options

LVSP-4T-BK
Low Voltage, 4 Terminal Splice Box, Black, IP20




OS-DC-F4-BK
Occupancy Sensor



Male Quick Connect, FMA, LMC, LYC, or IS-DC are required for input and output.


DIM-DC-F4-BK
24VDC Low Voltage In-line Dimmer Module




Male Quick Connect, FMA, LMC, LYC, or IS-DC are required for input and output.

NL.EX.D1.B & **NL.EX.D3.B**
Near Infrared Remote Door Sensor

NL.EX.D1.B - 1 IR Sensor




NL.EX.D3.B - 3 IR Sensor




Male Quick Connect, FMA, LMC, LYC, or IS-DC are required for input and output. For more information visit Sensor Spec Sheet (Link)

LV-BL-MKC-12-BK
Blade Louver reduces glare at high angle in two directions
Also available with complete fixture, use ordering code **-BLV**



This Black louver/lens combo comes in 12" increments and sits in place of a Myka lens, not in addition to.


LV-BL-MKC-12-WH
Blade Louver reduces glare at high angle in two directions
Also available with complete fixture, use ordering code **-WLV**



This White louver/lens combo comes in 12" increments and sits in place of a Myka lens, not in addition to.

Photometry

MK-48-VC72VHO-30K-C
Myka, 4ft, VHO, 3000K, Clear Lens




Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	258	35%
	0-40	420	57%
	0-60	647	87%
	0-90	735	99%
Total	0-180	742	100%

Beam Angle
77°

MK-48-VC72VHO-30K-HF
Myka, 4ft, VHO, 3000K, Half-Frosted Lens




Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	186	30%
	0-40	299	48%
	0-60	502	81%
	0-90	615	99%
Total	0-180	622	100%

Beam Angle
91°

MK-48-VC72VHO-30K-F
Myka, 4ft, VHO, 3000K, Frosted Lens




Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	114	26%
	0-40	189	42%
	0-60	341	77%
	0-90	440	99%
Total	0-180	445	100%

Beam Angle
112°

MK-48-VC72VHO-30K-MF
Myka, 4ft, VHO, 3000K, Matte-Frosted Lens




Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	139	26%
	0-40	230	42%
	0-60	412	76%
	0-90	535	99%
Total	0-180	542	100%

Beam Angle
112°

MK-48-VC72VHO-30K-BLV
Myka, 4ft, VHO, 3000K, Black Blade Louver




Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	75	32%
	0-40	122	52%
	0-60	204	88%
	0-90	230	99%
Total	0-180	233	100%

Beam Angle
109°

MK-48-VC72VHO-30K-WLV
Myka, 4ft, VHO, 3000K, White Blade Louver



Zonal Lumen Summary 3000K

	Zone	Lumen	% Fixture
	0-30	117	30%
	0-40	191	49%
	0-60	329	84%
	0-90	386	99%
Total	0-180	390	100%

Beam Angle
109°

Power Consumption

Please visit the link/QR code below to access the Luminii Power Consumption Chart tool on our website.

There you will be able to select your fixture, ouput, and desired power feed to get a full power consumption table.

I'm also click-able

Desired Nominal Length: _____

Desired Output: _____

Desired CCT: _____

Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Maximum Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
10	544.1	342.2	215.1	135.3	85.1	53.5	33.7
15	362.7	228.1	143.4	90.2	56.7	35.7	22.4
20	272.0	171.1	107.6	67.7	42.6	26.8	16.8
25	217.6	136.9	86.1	54.1	34.0	21.4	13.5
30	181.4	114.1	71.7	45.1	28.4	17.8	11.2
35	155.5	97.8	61.5	38.7	24.3	15.3	9.6
40	136.0	85.5	53.8	33.8	21.3	13.4	8.4
45	120.9	76.0	47.8	30.1	18.9	11.9	7.5
50	108.8	68.4	43.0	27.1	17.0	10.7	6.7
55	98.9	62.2	39.1	24.6	15.5	9.7	6.1
60	90.7	57.0	35.9	22.6	14.2	8.9	5.6
65	83.7	52.6	33.1	20.8	13.1	8.2	5.2
70	77.7	48.9	30.7	19.3	12.2	7.6	4.8
75	72.5	45.6	28.7	18.0	11.3	7.1	4.5
80	68.0	42.8	26.9	16.9	10.6	6.7	4.2
85	64.0	40.3	25.3	15.9	10.0	6.3	4.0
90	60.5	38.0	23.9	15.0	9.5	5.9	3.7
96	56.7	35.6	22.4	14.1	8.9	5.6	3.5

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL		INPUT CONTROL		WATTAGE		OUTPUT
	–		–		–	
PS - Power Supply, 120-277VAC		UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)		30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.


0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart

MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50"	7.40"	8.66"	11.85"
Width	3.73"	3.73"	3.73"	4.32"
Depth	1.61"	1.61"	1.61"	1.81"

PS-UNI-30/60/96



PS-UNI-3X96




For use with Static White


Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic		D - Dry		96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"



PS-010V-LIN/LOG-D-3X96




Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Athena 0-10V LED Driver

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts	24 - 24 VDC	AWNR - Athena




MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

For use with Static White

Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI2-DT6 - DALI2 DT6 (0.1%)	D - Dry	96 - 96 Watts	24 - 24 VDC




Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"


For use with Static White

Ordering Code - DALI Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI - DALI (0.1%)	D - Dry	96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC



PS-DALI-D-3X96-24



Model	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.


For use with Static White


Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DMX-DMX (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

ZONAL CONTROL POWER SUPPLIES.
CONTROL MULTIPLE TAPES/ZONES USING DMX CHANNELS.






For use with Static White

Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"




For use with Static White

Ordering Code - In-Ground Power Supplies

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS120-Power Supply, 120VAC PS240-Power Supply, 240VAC PS277-Power Supply, 277VAC	ELV-ELV Dimming (1%)	IG-In Ground	2X96-2X96 Watts	24-24 VDC

MODELS	2X96W
Length	8.40"
Width	8.30"
Depth	8.10"



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

LUTRON®

Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 1%


MODEL

L3DA4U1UKL-CV240

Hi-lume™ 1% EcoSystem Voltage LED driver 40W max

MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"

L3DA4U1UKL-CV240



LUTRON®

Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

Hi-lume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™ 96W max

MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"

