PS-DALI2-DT8-D-96-24-AWNR | Athena DALI2 DT8 Power Supply

luminii

Features

- Wireless enabled DALI2DT8 control via Lutron Athena
- Class 2
- Features EldoLED's LINEARdrive
- Suitable for Dry locations
- Must be connected to Lutron Athena Control System
- Digital wireless controll communication for a dynamic lighting control system for smart buildings and human-centric experiences
- Factory Installed Lutron Athena Wireless Node - simplifying set up time, enabling straightforward programming via the Lutron Designer software Applicaiton
- 5 year Warranty

c UL us LISTED | TITLE 24 JA8 COMPLIANT | FC | PLENUM FOR SUCH USE IN ACCORDANCE WITH UL2043 | CLASS 2 TYPE HL | ATHENA | Declare.

Technical Information

	MODEL	PS-DALI2-DT8-D-96-24-AWNR
ELECTRICAL	Voltage/ Frequency	120-277V AC @ 50/60Hz
	Inrush Current	100A @ 277V
	Power Factor	> 0.94 @ 120~277V*
	Efficiency	0.90 @ 120V 0.92 @ 277V
	Driver Heat Dissipation	36.39 BTU/hr @ 120V* 28.48 BTU/hr @ 277V*
	Max Input Current	1.00A @ 120V 0.44A @ 277V
	Max Output Power	96W
	Max Output Current	4.0A
	Output Voltage	24V DC
	Total Harmonic Distortion	< 20%*
	Start Up Time	< 0.5S*
	Minimum Load	10%
	Dimming (Athena)	0.1% - 100%
RATING	Environment	Dry IP20
	Compliance	UL 8750
	Ambient Operating Temperature Range	0 to 50°C
DIMENSIONS	Length A	14.40"
	Width B	5.20"
	Height C	2.60"
Net. Weight		4.1 lbs

*At max load

General Wiring Diagram



Dimensions



Ordering Code

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT		FEATURE
	–		–		–		–		–	
PS - Power Supply, 120-277VAC		DALI2-DT8 - DALI2DT8 Tunable White		D - Dry		96 - 96 W		24 - 24 VDC		AWNR - Athena Wireless Node