

Features



- Class 2 DALI controlled LED Driver features eldoLED's LINEARdrive
- Configurable warm dimming DALI driver rated at 96 watts
- Factory Programmed to deliver 18K-27K warm dim effect when pairing with 18K-35K tunable white LED
- DALI2-DT6 Dim-to-Warm functionality with 3-wire tunable white LED
- DALI-2 Compatible
- Suitable For Damp Location
- 5 year Warranty




Technical Information


MODEL		PS-DALI2-WD-D-96-24
ELECTRICAL	Voltage/ Frequency	120-277V AC @ 50/60Hz
	Inrush Current	100A @ 277V
	Power Factor	> 0.94 @ 120~277V*
	Efficiency	0.90 @ 120V 0.92 @ 277V
	Max Input Current	1.00A @ 120V 0.44A @ 277V
	Max Output Power	96W
	Max Output Current	4.0A
	Output Voltage	24V DC
	Total Harmonic Distortion	< 20%*
	Start Up Time	< 0.5S*
	Minimum Load	10%
	Dimming (DALI)	0.1% - 100%
RATING	Environment	Damp IP44
	Compliance	UL 8750
	Ambient Operating Temperature Range	- 20 to 50°C
DIMENSIONS	Length A	14.40"
	Width B	5.20"
	Height C	2.60"
	Net. Weight	3.8 lbs

*At max load


General Wiring Diagram




Dimensions



Warm Dim Curve



Ordering Code



PS-Power Supply, 120-277VAC

DALI2-WD-DALI2 DT6 Warm Dim (0.1%)

D-Dry

96-96 Watts

24-24 VDC