iLight Plexineon Rings Catenary | Static White and Monochrome Colors

luminii

Horizontal Ring

Vertical Ring

- For interior and exterior accent lighting
- Neon look providing a clear line of light visible for miles
- Includes Turnbuckles, Collar, Mounting Frame, Mounting Clips, and other hardware necessary to assemble to Catenary Cable
- Catenary Cable, Poles, Cable Eyes, and other Cable support hardware by others
- Operating Temperature: -40° F to 140° F (-40° C to 60° C)
- 24VDC Class 2
- IK10 and 3G rated
- IP67 rated
- 3 year warranty outdoor



Without Mounting | With Horizontal Catenary Mounting | With Vertical Catenary Mounting

3G IP67 IK10 CE RoHS MADE IN U.S.A DIM BAA & BABA +/- 30 CCT Single Bin c UL us LISTED

DISCONTINUED
DISCONTINUED
DISCONTINUED

Technical Information

RING OUTER DIAMETER* (inch)		Plexineon Static White (30K)	Plexineon Monochrome Colors					
			Red	Blue	Green	Magenta	Teal	Yellow
WAVELENGTH		N/A	622 nm	468 nm	525 nm	567 nm	486 nm	563 nm
EFFICACY		39 lm/W	12.1 lm/W	8.1 lm/W	33.8 lm/W	9.2 lm/W	20.9 lm/W	23.2 lm/W
Ø36 (Ø3ft)	Lumen Output	1159 lm	132 lm	104 lm	471 lm	226 lm	565 lm	584 lm
	Power Consumption	30.2 W	11.3 W	13.2 W	14.1 W	24.5 W	27.3 W	25.4 W
Ø72 (Ø6ft)	Lumen Output	2318 lm	264 lm	207 lm	942 lm	452 lm	1131 lm	1169 lm
	Power Consumption	60.3 W	22.6 W	26.4 W	28.3 W	49.0 W	54.7 W	50.9 W
Ø144 (Ø12ft)	Lumen Output	4637 lm	528 lm	415 lm	1885 lm	905 lm	2262 lm	2337 lm
	Power Consumption	120.6 W	45.2 W	52.8 W	56.5 W	98.0 W	109.3 W	101.8 W
Ø288 (Ø24)	Lumen Output	9274 lm	1056 lm	829 lm	3770 lm	1810 lm	4524 lm	4675 lm
	Power Consumption	241.3 W	90.5 W	105.6 W	113.1 W	196.0 W	218.7 W	218.7 W

*Rings will be made of equal sections no longer than 96" arc length. Rings exceeding 96W will have allowances for additional power feeds.

CCT	Multiplier (reference - 3000K)	CRI	TM-30 R_f	TM-30 R_g
2700K	0.94	90	88	97
3000k	1.00	90	87	97
3500k	1.02	90	87	97
4000k	1.02	90	84	92

Ordering Code

MODEL	RING DIAMETER[2]	RING TYPE	CCT	OUTPUT	LENS	MOUNTING	FINISH	POWERFEED POSITION/TYPE
PX-Plexineon[1]	___-Ring outer diameter in inches, 6"-144" (12ft)	HR-Horizonal Ring VR-Vertical Ring[3]	27K-2700K 30K-3000K 35K-3500K 40K-4000K B-Blue G-Green T-Teal Y-Yellow R-Red M-Magenta	SO-Standard	F-Frosted	CD-Catenary Mount, Decorative Clips[4]	GG-Gloss Grey BK-Matte Black GY-Matte Grey WH-Matte White	B-4-Plug Quick Connect one end, Receptacle Quick Connect other end

1. Standard lead time 8 weeks.
2. Rings will be made of equal sections no longer than 96" arc length. Tolerance on size of diameter is +/- 1".
3. Vertical Ring max diameter is 72", min diameter is 16"
4. Catenary Mount fixtures include a fixture mounting frame and all mounting components necessary to attach to Catenary Cable (by others). 2 mounting clips included for every 12" of diameter, with a minimum of 3 clips. Mounting frames over dia48" are ship in multiple pieces and are assembled on site. Decorative Clips match the fixture finish.

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

luminii

Finish Options

BK
Matte Black Finish



WH
Matte White Finish

GY
Matte Grey Finish



GG
Gloss Grey Finish



Mounting Components

CD

Catenary Mount, Decorative Clip



Thinner clip with finish options to match fixtures

Mounting Frame



Mounting clips are riveted at the factory to the Mounting Frame. Finish matches Ordering Code Finish selected

Mounting Frame Joiner

Assembles Mounting Frame together for runs over 96" (8ft)

80-HSH01-000-XX
Horizontal Catenary Strut Hanger



Able to adjust up to 2.5" vertically

35-CVC-003-XX
Vertical Catenary Collar Assembly



Able to adjust up to 2.5" vertically

0X	Clip Finish
01	Matte Black
02	Matte Grey
03	Matte White

Additional Material

- Ordered separately.

70-TOL02-001-01
Mounting Clip
Installation Tool



Use for installation of Plexineon into Mounting Clips

60-12-22AWGSBWN
Weatherproof Wire Nut
Silicone Filled



Order 2 per Power Supply

55-STW02-050-00
50 ft of 14 gauge wire Black jacket, 2 conductors



Sunlight, moisture resistant, and flame retardant PVC jacket per UL 1277

DISCONTINUED
DISCONTINUED
DISCONTINUED

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

Ring Types

HR
Horizontal Ring



(Use this dimension for Ordering Code)

VR
Vertical Ring



(Use this dimension for Ordering Code)

DISCONTINUED
DISCONTINUED
DISCONTINUED

Powerfeed and Connectors

- Quick Connectors with 6" flying leads are included in the Plexineon runs per CCT option selected. Order extras as desired.

Connectors for use with Static White and Mono - Sold Separately



60-SJ-0001-08
iLight TABBED PLUG Quick Connect with 6" flying leads, 2-conductor

Also available with longer Flying Leads

60-SJ-C2-0001-01	120" flying leads

60-SJ-0002-08
iLight RECEPTABLE Quick Connect with 6" flying leads, 2-conductor

Also available with longer Flying Leads

60-SJ-C2-0002-01	120" flying leads

60-SJ-C2-JMP-12-01
iLight Plug-Receptacle Quick Connect 12" Jumper, 2-conductor, Black silicone jacket



Also available with longer wires

60-SJ-C2-JMP-48-01	48" jumper
60-SJ-C2-JMP-120-01	120" jumper

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

luminii

Sample Layout

PX-72-HR-30K-SO-F-CD-GG-B-4
Plexineon Horizontal Ring, Catenary Mount, Decorative Clips



DISCONTINUED
DISCONTINUED
DISCONTINUED

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

luminii

Sample Layout

- Horizontal Ring

Dimensions for Turnbuckle show Cable to illuminated surface of Plexineon. Turnbuckle provides 2.5" vertical adjustability from 10.5" for 13.0" for leveling.



DISCONTINUED
DISCONTINUED
DISCONTINUED

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

luminii

Sample Layout

PX-36-VR-30K-SO-F-CD-GG-B-4
Plexineon Vertical Ring, Catenary Mount, Decorative Clips



DISCONTINUED
DISCONTINUED
DISCONTINUED

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

luminii

Sample Layout

- Vertical Ring

Collar provides up to 45° angular adjustability.
1 Collar per each plexineon vertical ring.





DISCONTINUED
DISCONTINUED
DISCONTINUED

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

Power Consumption

Tested at Full Power with PS-UNI Series power supplies.
Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

DISCONTINUED
DISCONTINUED

Static White

Nominal Ring Dia (in)	Wattage Per Ring	Nominal Ring Dia (in)	Wattage Per Ring
12	9.9	**217**	179.2
24	19.5	**222**	183.2
36	30.4	**227**	187.2
48	39	**232**	191.2
60	48.6	**237**	194.4
72	58.5	**242**	198.4
84	68.7	**244**	201.6
96	78	**250**	206.1
156	127.2	**256**	210.6
159	130.2	**261**	215.1
163	134.4	**267**	218.7
167	137.4	**273**	223.2
171	140.4	**272**	224
174	143.4	**278**	229
178	145.8	**284**	234
182	148.8		
181	148.4		
186	151.9		
190	156.8		
195	160.3		
199	163.8		
203	167.3		
208	170.1		
212	173.6		

Power Consumption

Tested at Full Power with PS-UNI Series power supplies.
Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

Monochrome

Nominal Length (in)	Watts						Nominal Length (in)	Watts					
	Red	Yellow	Green	Teal	Blue	Magenta		Red	Yellow	Green	Teal	Blue	Magenta
12	3.6	8.4	4.8	9.1	4.6	8.2	**217**	67.2	154.4	86.4	169.6	83.2	150.4
24	7.5	17.4	9.9	18.8	9.2	16.6	**222**	69.6	158.4	88.8	173.6	84.8	152
36	11	25.6	14.4	28.4	13.6	25	**227**	71.2	160	92.8	175.2	86.4	156
48	15	34.8	19.8	37.6	18.4	33.2	**232**	73.6	168	94.4	183.2	88.8	160
60	18.4	42	23.6	46.2	22.2	40.6	**237**	73.6	168	94.4	184.8	88.8	162.4
72	22.5	52.2	29.7	56.4	27.6	49.8	**242**	73.6	168	94.4	185.6	92.8	165.6
84	26.1	59.4	33.3	65.1	31.8	57	**244**	75.6	173.7	97.2	190.8	93.6	169.2
96	30	69.6	39.6	75.2	36.8	66.4	**250**	78.3	178.2	99.9	195.3	95.4	171
156	49.2	109.8	63.6	121.2	59.4	108.6	**256**	80.1	180	104.4	197.1	97.2	175.5
159	50.4	114.6	64.8	126	60.6	109.8	**261**	82.8	189	106.2	206.1	99.9	180
163	50.4	115.8	64.8	127.2	62.4	112.8	**267**	82.8	189	106.2	207.9	99.9	182.7
167	52.2	118.8	66.6	130.2	63.6	114	**273**	82.8	189	106.2	208.8	104.4	186.3
171	53.4	120	69.6	131.4	64.8	117	**272**	84	193	108	212	104	188
174	55.2	126	70.8	137.4	66.6	120	**278**	87	198	111	217	106	190
178	55.2	126	70.8	138.6	66.6	121.8	**284**	89	200	116	219	108	195
182	55.2	126	70.8	139.2	69.6	124.2							
181	57.4	128.1	74.2	141.4	69.3	126.7							
186	58.8	133.7	75.6	147	70.7	128.1							
190	58.8	135.1	75.6	148.4	72.8	131.6							
195	60.9	138.6	77.7	151.9	74.2	133							
199	62.3	140	81.2	153.3	75.6	136.5							
203	64.4	147	82.6	160.3	77.7	140							
208	64.4	147	82.6	161.7	77.7	142.1							
212	64.4	147	82.6	162.4	81.2	144.9							

DISCONTINUED
DISCONTINUED

Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Maximum Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
10	544.1	342.2	215.1	135.3	85.1	53.5	33.7
15	362.7	228.1	143.4	90.2	56.7	35.7	22.4
20	272.0	171.1	107.6	67.7	42.6	26.8	16.8
25	217.6	136.9	86.1	54.1	34.0	21.4	13.5
30	181.4	114.1	71.7	45.1	28.4	17.8	11.2
35	155.5	97.8	61.5	38.7	24.3	15.3	9.6
40	136.0	85.5	53.8	33.8	21.3	13.4	8.4
45	120.9	76.0	47.8	30.1	18.9	11.9	7.5
50	108.8	68.4	43.0	27.1	17.0	10.7	6.7
55	98.9	62.2	39.1	24.6	15.5	9.7	6.1
60	90.7	57.0	35.9	22.6	14.2	8.9	5.6
65	83.7	52.6	33.1	20.8	13.1	8.2	5.2
70	77.7	48.9	30.7	19.3	12.2	7.6	4.8
75	72.5	45.6	28.7	18.0	11.3	7.1	4.5
80	68.0	42.8	26.9	16.9	10.6	6.7	4.2
85	64.0	40.3	25.3	15.9	10.0	6.3	4.0
90	60.5	38.0	23.9	15.0	9.5	5.9	3.7
96	56.7	35.6	22.4	14.1	8.9	5.6	3.5

DISCONTINUED
DISCONTINUED

iLight Plexineon Rings Catenary | Static White and Monochrome Colors

luminii

Common Applications

Custom Indoor Designs | Coves | Signs | Building Facades | Lobbies | Hallways | Statement Pieces | Restaurants
Corporate Offices | Schools | Residential Towers | Parking Garages | Hotels | Bridges | Benches | Airports

DISCONTINUED
DISCONTINUED

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		WATTAGE		OUTPUT
	–		–		–	
PS - Power Supply, 120-277VAC		UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)		30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.

0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart

MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50"	7.40"	8.66"	11.85"
Width	3.73"	3.73"	3.73"	4.32"
Depth	1.61"	1.61"	1.61"	1.81"





Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL		INPUT CONTROL		ENVIRONMENT		WATTAGE		OUTPUT
	-		-		-		-	
PS - Power Supply, 120-277VAC		010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic		D - Dry		96 - 96 Watts 3x96 - 3x96 Watts		24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"





DISCONTINUED
DISCONTINUED
DISCONTINUED

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

Ordering Code - Athena 0-10V LED Driver

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts	24 - 24 VDC	AWNR - Athena Wireless Node

PS-010V-LIN/LOG-D-96-ANWR



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI2-DT6 - DALI2 DT6 (0.1%)	D - Dry	96 - 96 Watts	24 - 24 VDC



Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Ordering Code - DALI Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI - DALI (0.1%)	D - Dry	96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC



Model	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

PS-DALI-D-3X96-24



DISCONTINUED
DISCONTINUED
DISCONTINUED

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
	-	-	-	-
PS-Power Supply, 120-277VAC	DMX-DMX (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC



MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

ZONAL CONTROL POWER SUPPLIES.
CONTROL MULTIPLE TAPES/ZONES USING DMX CHANNELS.



Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
	-	-	-	-
PS-Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Ordering Code - In-Ground Power Supplies

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
	-	-	-	-
PS120-Power Supply, 120VAC PS240-Power Supply, 240VAC PS277-Power Supply, 277VAC	ELV-ELV Dimming (1%)	IG-In Ground	2X96-2X96 Watts	24-24 VDC



MODELS	2X96W
Length	8.40"
Width	8.30"
Depth	8.10"

DISCONTINUED
DISCONTINUED
DISCONTINUED

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

Ordering Code - Athena VintageDim® 0-10V Two Channel LED Driver, 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS-Power Supply, 120-277VAC	010V-2CH-0-10V Dimming Two Channel Control, LED1 Brightness and LED2 Brightness	D-Dry	96-96 W	24-24 VDC	AWNR-Athena

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"



LUTRON®

Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 1%

MODEL

L3DA4U1UKL-CV240

Hi-lume™ 1% EcoSystem Voltage LED driver
40W max

MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"



LUTRON®

Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

Hi-lume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™
96W max

MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"



DISCONTINUED
DISCONTINUED
DISCONTINUED