



Plexineon Recessed Mount

Static White and Monochrome Colors

ilight
by luminii



- For interior accent lighting.
- Neon look providing a crisp, clear line of light visible for miles
- Mounting Clips are included in the appropriate quantities
- Operating Temperature: -40° F to 140° F (-40° C to 60° C)
- 24VDC Class 2
- IK10 and 3G rated
- 5 year warranty indoor



Technical Information

MODEL	Plexineon Static White (30K)	Plexineon Monochrome Colors					
		Red	Blue	Green	Magenta	Teal	Yellow
OUTPUT OPTIONS	SO	SO					
Lumens Output (3000K)	123 lm/ft	14 lm/ft	11 lm/ft	50 lm/ft	24 lm/ft	60 lm/ft	62 lm/ft
Average Power Consumption (for a 4' section)	3.2 W/ft	1.2 W/ft	1.4 W/ft	1.5 W/ft	2.6 W/ft	2.9 W/ft	2.7 W/ft
Wavelength	N/A	622 nm	468 nm	525 nm	567 nm	486 nm	563 nm
Efficacy	39 lm/W	12.1 lm/W	8.1 lm/W	33.8 lm/W	9.2 lm/W	20.9 lm/W	23.2 lm/W
Order Increment	1.97"	1.97"					
Max Run Length (in series)	30 ft	32ft	32ft	32ft	32ft	32ft	32ft

CCT	Multiplier (reference = 3000K)	TM-30		
		CRI	R _f	R _g
2700K	0.94	90	88	97
3000k	1.00	90	87	97
3500k	1.02	90	87	97
4000k	1.02	90	84	92

Ordering Code

MODEL	RUN LENGTH ¹	BEND	CCT	OUTPUT	LENS	MOUNTING ²	FINISH	POWERFEED POSITION/TYPE
PX-Plexineon	____ - Run length in inches, 3" min, no max run length	SR-Straight Run	27K- 2700K 30K- 3000K 35K- 3500K 40K- 4000K B-Blue G-Green T-Teal Y-Yellow R-Red M-Magenta	SO-Standard	F-Frosted	RM-Recessed Mount	BK-Matte Black	B-4- Plug Quick Connect one end, Receptacle Quick Connect other end

1. Available in 2"(1.97") increments, +/- 1/2" tolerance. Run Lengths over 96" (8ft) will be made of equal sections no longer than 96".
2. Recessed Mount includes all necessary hardware for either mud-in or hard ceiling (stone, marble) installation. Blocking above ceiling built by others.


Plexineon Recessed Mount

Static White and Monochrome Colors





Installation Configurations



- Position of Plexineon fixtures within Extrusion Housing is adjustable in the field at time of install.




Exposed



Semi-Recessed




Fully Recessed



Recessed Mounting Components & Tools


- Mounting Hardware is included with Plexineon runs in the appropriate quantity, including Extrusion Housing and Plaster Plate. Order extras as desired. Blocking above ceiling built by others.

75-EXT01-001-00
Extrusion Housing (Black)




Mount to deck or support backing above ceiling. Ships in 96" sections, field cut to size

75-CLP32-001-00
Recessed Mounting Clip




Placed approximately every 30" as well as 2" from the ends.
Use Glue to adhere with Plexineon fixture.

80-MTP01-001-00
End Plate




Two per continuous run

80-PIN03-001-00
Alignment Pin




Two for every Extrusion to Extrusion connection.

80-BSH02-001-00
Powerfeed Strain Relief



One per driver connection

35-EXT01-001-00
Plaster Plate, Mud-in




Used for drywall install and mud-in applications

60-12-22AWGSBWN
Weatherproof Wire Nut Silicone Filled




70-TOL03-001-00
Tool



Allows for changing of installation configurations

35-EXT03-001-00
Paint Mask



Protects interior of the Extrusion Housing during mud-in and paint

45-GLU01-001-00
Glue




Used to adhere Recessed Mounting Clips to Plexineon fixture

Plexineon Recessed Mount


Static White and Monochrome Colors




Recessed Mounting Installation



Install Recessed Mounting Clips onto plexineon straight run fixture. **Use glue to fill any gaps between clip and fixture.**
Note: use 1 clip per approximately every 30".




Build blocking above ceiling plane. Screw onto the support blocking or deck.




Install Plexineon with Recessed Mounting Clips into Extrusion Housing at desired position.

Powerfeed and Connectors

- Quick Connectors with 6" flying leads are included in the Plexineon runs per CCT option selected. Order extras as desired.




60-SJ-0001-08
iLight TABBED PLUG Quick Connect with 6" flying leads, 2-conductor




Also available with longer Flying Leads

60-SJ-C2-0001-01 120" flying leads




60-SJ-0002-08
iLight RECEPTABLE Quick Connect with 6" flying leads, 2-conductor




Also available with longer Flying Leads

60-SJ-C2-0002-01 120" flying leads



60-SJ-C2-JMP-12-01
iLight Plug-Receptacle Quick Connect 12" Jumper, 2-conductor, Black silicone jacket



Also available with longer wires

60-SJ-C2-JMP-48-01 48" jumper

60-SJ-C2-JMP-120-01 120" jumper

Additional Material

60-12-22AWGSBWN
Weatherproof Wire Nut Silicone Filled



Order 2 per Power Supply.


Plexineon Recessed Mount

Static White and Monochrome Colors

Sample Layout

PX-108-SR-30K-SO-F-RM-BK-B-4

Plexineon Recessed



Plexineon Recessed Mount

Static White and Monochrome Colors



Power Consumption

Tested at Full Power with PS-UNI Series power supplies.

Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

Static White

Nominal Length (in)	Actual Length	Watts	Nominal Length (in)	Actual Length	Watts
3	2 8/16	2.5	54	53 11/16	14.5
5	4 8/16	4.5	56	55 11/16	15.2
7	6 7/16	1.5	58	57 10/16	15.7
9	8 7/16	2.1	60	59 10/16	16.2
11	10 6/16	2.6	62	61 9/16	16.6
13	12 6/16	3.1	64	63 9/16	17.4
15	14 5/16	3.6	66	65 8/16	17.6
17	16 5/16	4.1	68	67 8/16	18.1
19	18 4/16	4.8	70	69 7/16	18.5
21	20 4/16	5.3	72	71 7/16	19.3
23	22 3/16	5.8	74	73 6/16	19
25	24 3/16	6.5	76	75 6/16	19.5
27	26 2/16	7	78	77 5/16	20
29	28 2/16	7.5	80	79 5/16	20.7
31	30 1/16	8.2	82	81 4/16	21.2
33	32 1/16	8.7	84	83 4/16	21.7
35	34	9.2	86	85 3/16	22.4
36	36	9.9	88	87 3/16	22.9
38	37 15/16	10.4	90	89 2/16	23.4
40	39 15/16	10.8	92	91 2/16	23.9
42	41 14/16	11.6	94	93 1/16	24.3
44	43 14/16	11.9	96	95 1/16	24.8
46	45 13/16	12.5			
48	47 13/16	12.8			
50	49 12/16	13.5			
52	51 12/16	14			

Plexineon Recessed Mount

Static White and Monochrome Colors



Power Consumption

Tested at Full Power with PS-UNI Series power supplies.

Standard Nominal Lengths offered provide minimal shadowing. For alternate lengths, please consult Inside Sales with specific request.

Monochrome

Nominal Length (in)	Actual Length	Watts						Nominal Length (in)	Actual Length	Watts					
		Red	Yellow	Green	Teal	Blue	Magenta			Red	Yellow	Green	Teal	Blue	Magenta
3	2 8/16	0.2	0.4	0.3	0.5	0.2	0.4	54	53 11/16	5.3	12.5	7.0	13.7	6.5	12.1
5	4 8/16	0.4	0.9	0.5	1.0	0.5	0.8	56	55 11/16	5.5	12.8	7.2	14.2	6.8	12.5
7	6 7/16	0.6	1.4	0.8	1.4	0.7	1.4	58	57 10/16	5.8	13.5	7.5	14.7	7.0	23.8
9	8 7/16	0.8	1.6	1.0	1.9	1.0	1.6	60	59 10/16	5.8	14.0	7.7	15.2	7.2	12.8
11	10 6/16	1.0	2.1	1.2	2.6	1.2	2.1	62	61 9/16	6.3	14.2	8.2	15.7	7.5	13.7
13	12 6/16	1.2	2.9	1.4	3.1	1.4	2.6	64	63 9/16	6.5	14.7	8.4	16.2	7.7	14.2
15	14 5/16	1.3	3.1	1.6	3.3	1.6	3.1	66	65 8/16	6.7	15.2	8.7	16.5	8.2	14.7
17	16 5/16	1.4	3.6	1.9	3.8	1.9	3.6	68	67 8/16	6.7	15.7	8.9	17.1	8.4	15.2
19	18 4/16	1.6	4.1	2.1	4.6	2.1	3.8	70	69 7/16	7.0	16.2	9.2	17.6	8.4	15.7
21	20 4/16	1.9	4.6	2.6	5.0	2.1	4.6	72	71 7/16	7.0	16.6	9.2	17.8	8.7	15.9
23	22 3/16	1.9	5.0	2.9	5.5	2.6	5.0	74	73 6/16	7.2	17.1	9.4	18.3	8.9	16.3
25	24 3/16	2.1	5.5	3.1	6.3	2.9	5.3	76	75 6/16	7.5	17.4	9.9	18.8	9.2	16.6
27	26 2/16	2.6	6.3	3.3	6.7	3.1	5.8	78	77 5/16	7.7	17.8	10.1	19.3	9.4	17.1
29	28 2/16	2.9	6.5	3.6	7.0	3.3	6.3	80	79 5/16	7.7	18.1	10.4	19.8	9.6	17.6
31	30 1/16	3.1	7.0	3.8	7.5	3.6	6.7	82	81 4/16	8.2	18.3	10.6	20.2	9.9	18.1
33	32 1/16	3.1	7.2	4.1	8.2	3.8	7.0	84	83 4/16	8.4	19.1	10.8	21.0	10.1	18.3
35	34	3.3	7.7	4.6	8.7	4.1	7.5	86	85 3/16	8.4	19.3	10.8	21.2	10.4	18.8
36	36	3.6	8.4	4.8	9.1	4.6	8.2	88	87 3/16	8.7	19.8	11.1	21.7	10.6	19.0
38	37 15/16	3.8	8.9	5.0	9.7	4.8	8.4	90	89 2/16	8.9	20.0	11.6	21.9	10.8	19.5
40	39 15/16	3.8	9.2	5.3	10.1	4.8	8.9	92	91 2/16	9.2	21.0	11.8	22.9	11.1	20.0
42	41 14/16	4.1	9.9	5.3	10.6	5.0	9.4	94	93 1/16	9.2	21.0	11.8	23.1	11.1	20.3
44	43 14/16	4.6	10.1	5.5	11.1	5.3	9.9	96	95 1/16	9.2	21.0	11.8	23.2	11.6	20.7
46	45 13/16	4.6	10.6	6.1	11.8	5.5	10.4								
48	47 13/16	4.8	11.1	6.3	12.3	5.8	10.6								
50	49 12/16	5.0	11.6	6.5	12.5	6.3	11.1								
52	51 12/16	5.3	12.1	6.7	13.0	6.5	11.6								

Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Maximum Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
10	544.1	342.2	215.1	135.3	85.1	53.5	33.7
15	362.7	228.1	143.4	90.2	56.7	35.7	22.4
20	272.0	171.1	107.6	67.7	42.6	26.8	16.8
25	217.6	136.9	86.1	54.1	34.0	21.4	13.5
30	181.4	114.1	71.7	45.1	28.4	17.8	11.2
35	155.5	97.8	61.5	38.7	24.3	15.3	9.6
40	136.0	85.5	53.8	33.8	21.3	13.4	8.4
45	120.9	76.0	47.8	30.1	18.9	11.9	7.5
50	108.8	68.4	43.0	27.1	17.0	10.7	6.7
55	98.9	62.2	39.1	24.6	15.5	9.7	6.1
60	90.7	57.0	35.9	22.6	14.2	8.9	5.6
65	83.7	52.6	33.1	20.8	13.1	8.2	5.2
70	77.7	48.9	30.7	19.3	12.2	7.6	4.8
75	72.5	45.6	28.7	18.0	11.3	7.1	4.5
80	68.0	42.8	26.9	16.9	10.6	6.7	4.2
85	64.0	40.3	25.3	15.9	10.0	6.3	4.0
90	60.5	38.0	23.9	15.0	9.5	5.9	3.7
96	56.7	35.6	22.4	14.1	8.9	5.6	3.5

Plexineon Recessed Mount

Static White and Monochrome Colors

ilight
by luminii



Common Applications

Custom Indoor Designs | Coves | Signs | Building Facades | Lobbies | Hallways | Statement Pieces | Restaurants
Corporate Offices | Schools | Residential Towers | Parking Garages | Hotels | Bridges | Benches | Airports



Plexineon Recessed Mount

Static White and Monochrome Colors



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.


Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)	30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.

0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart


MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50"	7.40"	8.66"	11.85"
Width	3.73"	3.73"	3.73"	4.32"
Depth	1.61"	1.61"	1.61"	1.81"




Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"



PS-010V-LIN/LOG-D-3X96



Plexineon Recessed Mount


Static White and Monochrome Colors

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

Ordering Code - Athena 0-10V LED Driver


MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D-Dry	96-96 Watts	24-24 VDC	AWN - Athena



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI2-DT6 - DALI2 DT6 (0.1%)	D-Dry	96-96 Watts	24-24 VDC




Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"

Ordering Code - DALI Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DALI - DALI (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC



Model	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"



Plexineon Recessed Mount

Static White and Monochrome Colors



Power Supplies



See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	DMX-DMX (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"


ZONAL CONTROL POWER SUPPLIES.
CONTROL MULTIPLE TAPES/ZONES USING DMX CHANNELS.



Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC


MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"



Ordering Code - In-Ground Power Supplies

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS120 - Power Supply, 120VAC PS240 - Power Supply, 240VAC PS277 - Power Supply, 277VAC	ELV-ELV Dimming (1%)	IG-In Ground	2X96-2X96 Watts	24-24 VDC

MODELS	2X96W
Length	8.40"
Width	8.30"
Depth	8.10"



Plexineon Recessed Mount

Static White and Monochrome Colors



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.



Luminii is a Lutron OEM Advantage Partner


Lutron Power Supplies 1%

MODEL

L3DA4U1UKL-CV240

HiLume™ 1% EcoSystem Voltage LED driver
40W max

MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"



Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

HiLume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™
96W max

MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"

