
SOLO 11

PRODUCT OVERVIEW

INTENSE LIGHT ENGINE



KEY FEATURES

Beam Options: 11 | 14 | 18 | 30 | 50
Light Engine Performance: 413lm | 4.20W
Movement: 360 Pan | 90 Tilt
Tool-less field changeable optics
Ultra narrow high intensity beams
Interchangeable accessories
UK Part L1 / L2 (Display) Compliant
Title 24 JA8 Certified

OVERVIEW

Solo 11 Intense 48V DC Track is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. Our 413lm | 4.20W light engine has a max peak intensity of 7259cd. An accessory holder is available separately that can accommodate 37mm (1.45") lenses and louvers. This product mounts to the 48V DC Stucchi Multisystem Evo Track and requires an external 12V Constant Voltage LED power supply to the track.

PERFORMANCE

	Intense				
	U. Narrow	Narrow	Medium	Flood	W. Flood
FWHM	11°	14°	18°	30°	50°
Luminous Flux	396 lm	413 lm	391 lm	322 lm	317 lm
Peak Intensity	7259 cd	5422 cd	3338 cd	1052 cd	383 cd
CCT	2700K | 3000K | 3500K | 4000K				
CRI Min.	92 | 92 | 92 | 90				
LED Current	0.350 A				
Voltage	48 V				
Input Wattage	4.67 W				
Efficacy	98.3 lm/W				
Driver Type	Constant Voltage | Remote AC to 48VDC				
Class	SELV | Class III				

ORDER CODE

Model	Type	Output	CCT	Beam Angle	Voltage	Control	Adaptor Finish	Finish
SOL11 *Solo 11*	**MU** *Multisystem Track*	**IO** *Intense Output*	**27K** *2700K*	**UN** *Ultra Narrow 11°*	**48** *48V DC*	**010G** *0-10V Log*	**WH** *White*	**WH** *White*
			30K *3000K*	**NR** *Narrow 14°*		**LOC** *On-board*	**BK** *Black*	**BK** *Black*
			35K *3500K*	**ME** *Medium 18°*		**CAS** *Casambi*		**AL** *Br. Aluminium*
			40K *4000K*	**FL** *Flood 30°*		**DALI** *DALI*		**RBZ** *Rubbed Bronze*
				WF *Wide Flood 50°*				**BR** *Br. Brass*
								PB *Polished Brass*

Example code: SOL11-MU-IO-27K-UN-48-010G-WH-WH

See Drivers, Power Supplies and Accessories sections for further order codes

RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

LIGHT ENGINE SELECTION

This product specification sheet references our Intense light engine, this product is also available with Plus and HE static white light engines, please refer to their separate sheets.

▸ intense ◂

Precisions signature intense light engines offer tight, surgical beams combined with the highest peak intensity values available.

- Ultra-tight beams
- High Peak Cd

plus+

Precisions plus light engines offer the best balance between delivered lumens, beam quality and outstanding colour rendition.

- Increased Lumen Output
- CRI 98 Typical

HE

Precisions high efficiency light engines deliver the highest possible lumen values as well as our outstanding energy efficiency

- Maximum Lumen Output
- Maximum Energy Efficiency


LIFETIME & ENVIRONMENTAL

At Precision, we design and engineer our products with longevity in mind. Many of the components that make up our light fixtures are both modular and re-usable, making it possible to service and repair them throughout their life in service. Once our products reach the end of their useful life, it is possible to re-work and renew them in to a new product. We prioritise the use of recyclable materials in both our products and packaging, and encourage our customers to engage responsibly in the correct disposal of any materials we supply.

CIBSE TM65	10.77 Kg/CO2e
CIBSE TM66	2.4
RoHS Compliance	Yes
REACH Compliance	Yes
WEEE Compliance	Yes - Registered Producer
Declare	Declared
Lifetime	L90B10 100,000hrs
Warranty	5 Years

UK PART L	
Part L1A / L1B (Dwellings) *≥75 lm/W source lumens*	*Compliant 105 lm/W* *Source lm (441 lm) / Source W (4.20 W)*
Part L2A (General) *≥95lm/W delivered lumens*	-
Part L2A (Display) *≥80 lm/W source lumens*	*Compliant 105 lm/W* *Source lm (441 lm) / Source W (4.20 W)*


DIMENSIONS



MECHANICAL

Location	IP20 | Indoor Dry Location Only	**Cutout**	N/A
Mounting	48V Track Recessed | Trimless Recessed | Surface | Suspended	**Ceiling Thickness**	N/A
Adjustability	360 Pan | 90 Tilt	**Product Class**	SELV | Class III
Lockable	Pan	**Material**	Machined AL 6063-T6 | Machined Brass
Accessories	Lenses | Louver	**Weight**	170g 235g* | 0.37lb 0.52lb*
			** Brass finishes weight*


FINISHES



White | Black | Brushed Aluminium | Polished Brass | Rubbed Bronze | Brushed Brass

100W | Direct to track | Remote | Constant Voltage


Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	Direct to track
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	Refer to guide



	All CCT's		L	W	H
Max. Lights	1 to 16	**mm**	190	52	37
Order Code	PSCV-100-48-N1-MW	**in**	7.48	2.05	1.46

200W | Direct to track | Remote | Constant Voltage

Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	Direct to track
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	Refer to guide



	All CCT's		L	W	H
Max. Lights	1 to 32	**mm**	195	68	40
Order Code	PSCV-200-48-N1-MW	**in**	7.68	2.68	1.57

48V TRACK CABLE DISTANCES

	A = Distance from power supply to track 2 x 16 AWG (1.5mm²) cable							
	m	ft	m	ft	m	ft	m	ft
	5	16.4	10	32.8	20	65.6	30	98.4
	B = Track Length with max 5.5% V drop							
	m	ft	m	ft	m	ft	m	ft
100W	50	164	50	164	40	131.2	25	82
200W	40	131.2	30	98.4	-	-	-	-

SOLO 11

DRIVERS & POWER SUPPLIES – NORTH AMERICA

INTENSE LIGHT ENGINE

96W | Direct to track | Remote | Constant Voltage

Input Voltage	120-277V | 50/60 Hz
Driver Type	Remote | Constant Voltage
Location	IP20 | Indoor Location Only
Dimming Control	Direct to track
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	Refer to guide



	All CCT's		L	W	H
Max. Lights	1 to 16	**mm**	220	95	40
Order Code	USCV-96-48-N1-SC-EN	**in**	8.66	3.74	1.57

48V TRACK CABLE DISTANCES

	A = Distance from power supply to track 2 x 16 AWG (1.5mm²) cable							
	m	ft	m	ft	m	ft	m	ft
	5	16.4	10	32.8	20	65.6	30	98.4
	B = Track Length with max 5.5% V drop							
	m	ft	m	ft	m	ft	m	ft
100W	50	164	50	164	40	131.2	25	82
200W	40	131.2	30	98.4	-	-	-	-

RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

SOLO 11

PHOTOMETRY

INTENSE LIGHT ENGINE

OUTPUT SCALING


CCT	Output Multiplier	CRI	R9 Typ.	TM-30: Rf	TM-30: Rg	Max Lm
2400K	-	-	-	-	-	-
2700K	0.90	92	50	90	99	372
3000K	1.00	92	50	90	99	413
3500K	1.00	92	50	90	99	413
4000K	1.00	90	50	90	98	413


Colour Consistency: 2 SDCM at 2700K / 3000K, 3DCM at 3500 / 4000K


PHOTOMETRY

ULTRA NARROW

FWHM	11°
Delivered Flux	396 lm
Peak Intensity	7259 cd










NARROW

FWHM	14°
Delivered Flux	413 lm
Peak Intensity	5422 cd









MEDIUM

FWHM	18°
Delivered Flux	391 lm
Peak Intensity	3338 cd










FLOOD

FWHM	30°
Delivered Flux	322 lm
Peak Intensity	1052 cd










WIDE FLOOD

FWHM	50°
Delivered Flux	317 lm
Peak Intensity	383 cd









RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

Ø37MM LINEAR SPREAD LENS



244-BK

+



992-37

- The Linear Spread Lens **992-37** is a prismatic glass lens that can be used to create asymmetric linear beam effects
- It must be used in conjunction with the Single Accessory Holder **244-BK**
- Using narrower base optics will produce a longer, thinner beam
- The beam is spread widest perpendicular to the disc's vertical stripes (see *fig. 1*)









fig. 1








▸ intense ◂

	Ultra Narrow (11°)	Narrow (14°)	Medium (18°)	Flood (30°)	Wide Flood (50°)
					
Distribution Angle	10° x 54°	12° x 43°	17° x 53°	28° x 68°	40° x 75°
Delivered Flux	255 lm	253 lm	245 lm	207 lm	160 lm
Peak Intensity	1,320 Cd	1,183 Cd	756 Cd	349 Cd	165 Cd
Efficiency	60.7 lm/W	60.2 lm/W	58.3 lm/W	49.3 lm/W	66.6 lm/W
Efficiency Multiplier	x 0.64	x 0.61	x 0.63	x 0.64	x 0.50






OPTICS

There are 5 tool-less interchangeable optics, cross reference the text on the optic disc for beam.

Optic Disc	Optic Disc	Optic Disc	Optic Disc	Optic Disc
				
Ultra Narrow Disc	**Narrow Disc**	**Medium Disc**	**Flood Disc**	**Wide Flood Disc**
FWHM 11 deg	FWHM 14 deg	FWHM 18 deg	FWHM 30 deg	FWHM 50 deg
Order Code	**Order Code**	**Order Code**	**Order Code**	**Order Code**
911-01	**911-02**	**911-03**	**911-04**	**911-05**

ACCESSORIES

This product can hold 2 x accessories using the double accessory holder. Accessories are pre-installed unless otherwise requested.

Accessory Holder	Glare Control	Beam Shaping	Beam Shaping	Colour Change
				
Double Accessory Holder	**Honeycomb Louver**	**Softening Lens**	**Linear Lens**	**1/4 CTO**
W43xH14mm | W1.69xH0.55"	W37xH3.2mm | W1.46xH0.13"	W37xH3.2mm | W1.46xH0.13"	W37xH3.2mm | W1.46xH0.13"	W37xH1.8mm | W1.46xH0.07"
Order Code	**Order Code**	**Order Code**	**Order Code**	**Order Code**
244-BK	**995-37-BK**	**991-37**	**992-37**	**997-1/4CTO-37**

Colour Change

Custom Colour Filter
W37xH1.8mm | W1.46xH0.07"
Order Code
Contact Sales Rep

The Double Accessory Holder (sold separately) greatly enhances Solo's optical accessory capacity providing space for up to two additional accessories. It snaps in and out of the fixture's snoot without the need for tools, making on-site adjustments quick and simple.

