SOLO 08

PRODUCT OVERVIEW

PLUS LIGHT ENGINE



KEY FEATURES

Beam Options: 17 | 24 | 35 | 50
Light Engine Performance: 461lm | 6.00W
Movement: 360 Pan | 90 Tilt
Tool-less field changeable optics
Interchangeable accessories
Ultra-high CRI
UK Part L1 / L2 (Display) Compliant
Title 24 JA8 Certified

OVERVIEW

Solo 8 Plus Surface is a Constant Current single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has four site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. Our 461lm | 6.00W light engine has a max peak intensity of 3738cd. This product requires an external 0.35mA 17.15V Constant Current LED driver.

PERFORMANCE

	Plus			
	Narrow	Medium	Wide	V. Wide
FWHM	17°	24°	35°	50°
Luminous Flux	405 lm	440 lm	461 lm	415 lm
Peak Intensity	3738 cd	2468 cd	1253 cd	591 cd
CCT	2400K | 2700K | 3000K | 3500K | 4000K			
CRI Min.	90 | 98 | 98 | 98 | 95			
LED Current	0.350 A			
Voltage	17.15 V			
Input Wattage	6 W			
Efficacy	76.8 lm/W			
Driver Type	Constant Current | Remote			
Class	SELV | Class III			

ORDER CODE

Model	Type	Output	CCT	Beam Angle	Finish
SOL08 *Solo 08*	**SP** *Surface Plate*	**PL** *Plus*	**24K** *2400K*	**NR** *Narrow 17°*	**WH** *White*
			27K *2700K*	**ME** *Medium 24°*	**BK** *Black*
			30K *3000K*	**WD** *Wide 35°*	**AL** *Br. Aluminium*
			35K *3500K*	**VW** *Very Wide 50°*	**RBZ** *Rubbed Bronze*
			40K *4000K*		**BR** *Br. Brass*
					PB *Polished Brass*

Example code: SOL08-SP-PL-24K-NR-WH

See Drivers, Power Supplies and Accessories sections for further order codes

RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

LIGHT ENGINE SELECTION

This product specification sheet references our Plus light engine, this product is also available with a HE static white light engine, please refer to is separate specification sheet.

plus+

Precisions plus light engines offer the best balance between delivered lumens, beam quality and outstanding colour rendition.

- Increased Lumen Output
- CRI 98 Typical

HE

Precisions high efficiency light engines deliver the highest possible lumen values as well as our outstanding energy efficiency

- Maximum Lumen Output
- Maximum Energy Efficiency


LIFETIME & ENVIRONMENTAL

At Precision, we design and engineer our products with longevity in mind. Many of the components that make up our light fixtures are both modular and re-usable, making it possible to service and repair them throughout their life in service. Once our products reach the end of their useful life, it is possible to re-work and renew them in to a new product. We prioritise the use of recyclable materials in both our products and packaging, and encourage our customers to engage responsibly in the correct disposal of any materials we supply.

CIBSE TM65	8.18 Kg/CO2e
CIBSE TM66	2.4
RoHS Compliance	Yes
REACH Compliance	Yes
WEEE Compliance	Yes - Registered Producer
Declare	Declared
Lifetime	L90B10 50,000hrs
Warranty	5 Years

UK PART L	
Part L1A / L1B (Dwellings) *≥75 lm/W source lumens*	*Compliant 121 lm/W* *Source lm (726 lm) / Source W (6.00 W)*
Part L2A (General) *≥95lm/W delivered lumens*	-
Part L2A (Display) *≥80 lm/W source lumens*	*Compliant 121 lm/W* *Source lm (726 lm) / Source W (6.00 W)*


DIMENSIONS



MECHANICAL

Location	IP20 | Indoor Dry Location Only	**Cutout**	N/A
Mounting	Surface mounting plate	**Ceiling Thickness**	N/A
Adjustability	360 Pan | 90 Tilt	**Product Class**	SELV | Class III
Lockable	Pan	**Material**	Machined AL 6063-T6 | Machined Brass
Accessories	Louver | Lenses	**Weight**	82g | 0.18lb

FINISHES



White | Black | Brushed Aluminium | Polished Brass | Rubbed Bronze | Brushed Brass

SOLO 08

DRIVERS & POWER SUPPLIES – UK, EU, MIDDLE EAST, ASIA, PACIFIC

PLUS LIGHT ENGINE

20W | 0-10V | Remote | Constant Current

Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Current
Location	IP20 | Indoor Location Only
Dimming Control	0-10V
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	16 AWG - 36m (118') | 18 AWG 22m (72')



	All CCT's		L	W	H
Max. Lights	1 to 2 in series	**mm**	160	41	30
Order Code	PSCC-20-350-A-EL	**in**	6.3	1.61	1.18

20W | DALI-2 | Remote | Constant Current

Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Current
Location	IP20 | Indoor Location Only
Dimming Control	DALI-2
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	16 AWG - 36m (118') | 18 AWG 22m (72')



	All CCT's		L	W	H
Max. Lights	1 to 2 in series	**mm**	160	41	30
Order Code	PSCC-20-350-D-EL	**in**	6.3	1.61	1.18

14W | Phase | Remote | Constant Current

Input Voltage	230VAC | 50/60 Hz
Driver Type	Remote | Constant Current
Location	IP20 | Indoor Location Only
Dimming Control	Phase
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	18AWG - 2m (6.56')



	All CCT's		L	W	H
Max. Lights	1 only	**mm**	125	32	41
Order Code	PSCC-14-350-PHC-EL	**in**	4.92	1.26	1.61

RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

30W | 0-10V | Remote | Constant Current

Input Voltage	120-277V | 50/60 Hz
Driver Type	Remote | Constant Current
Location	IP20 | Indoor Location Only
Dimming Control	0-10V
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	16 AWG - 36m (118') | 18 AWG 22m (72')



	All CCT's		L	W	H
Max. Lights	1 to 2 in series	**mm**	348	65	47
Order Code	USCC-30-350-A-EL-ENC	**in**	13.7	2.56	1.85

30W | DALI-2 | Remote | Constant Current

Input Voltage	120-277V | 50/60 Hz
Driver Type	Remote | Constant Current
Location	IP20 | Indoor Location Only
Dimming Control	DALI-2
Min. Dim Level	0.1%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	16 AWG - 36m (118') | 18 AWG 22m (72')



	All CCT's		L	W	H
Max. Lights	1 to 2 in series	**mm**	348	65	47
Order Code	USCC-30-350-D-EL-ENC	**in**	13.7	2.56	1.85

12W | Phase | Remote | Constant Current

Input Voltage	120V | 50/60Hz
Driver Type	Remote | Constant Current
Location	IP20 | Indoor Location Only
Dimming Control	Phase
Min. Dim Level	1.0%
Flicker	IEEE P1789 Compatible | No Observable Effect
Wiring Distance	16 AWG - 14m (46') | 18 AWG 9m (30')



	All CCT's		L	W	H
Max. Lights	1 only	**mm**	247	65	47
Order Code	USCC-12-350-P-HT-ENC	**in**	9.72	2.56	1.85

SOLO 08

PHOTOMETRY

PLUS LIGHT ENGINE

OUTPUT SCALING


CCT	Output Multiplier	CRI	R9 Typ.	TM-30: Rf	TM-30: Rg	Max Lm
2400K	0.97	90	90	90	99	447
2700K	0.93	98	95	95	101	429
3000K	1.00	98	95	95	100	461
3500K	1.05	98	92	95	99	484
4000K	1.05	95	90	90	99	484


Colour Consistency: 2 SDCM


PHOTOMETRY

NARROW

FWHM	17°
Delivered Flux	405 lm
Peak Intensity	3738 cd









MEDIUM

FWHM	24°
Delivered Flux	440 lm
Peak Intensity	2468 cd










WIDE

FWHM	35°
Delivered Flux	461 lm
Peak Intensity	1253 cd










VERY WIDE

FWHM	50°
Delivered Flux	415 lm
Peak Intensity	591 cd







RCLPLLSALES@LUMINII.COM
LUMINII.COM | PRECISIONLIGHTING.CO.UK

GLARE GUARD ACCESSORY HOLDER




The Glare Guard Accessory Holder is an angled, snap-in snoot extension capable of holding a range of optical accessories, including honeycombs, gels, and beam shaping optics such as Wallwash and Linear Spread Lenses. The holder comprises of two halves, a front compartment and a rear compartment. The rear compartment is capable of holding a single accessory, whilst the the front compartment is used to hold orientation dependent beam shaping optics such as the Wallwash and Linear Spread lens.

	a. Front Compartment	b. Rear Compartment
Accessory Diameter	Ø30 mm | 1.18"	Ø25 mm | 0.98"
Capacity	1.2mm | 0.05" Max. Thickness	3.2mm | 0.125" Max. Thickness
Orientation Indexing	Yes - Alignment Notches	No
Weight	Aluminium: 120g | Brass: 290g	


Ordering Codes

Black	1110-GLR-01-BK	**Polished Brass ***	1110-GLR-02-PB
Traffic White	1110-GLR-01-TW	**Brushed Brass***	1110-GLR-02-SB
Brushed Aluminium	1110-GLR-01-AL	**Rubbed Bronze ***	1110-GLR-02-RB




Optical accessories ordered separately

** N.B. - Custom RAL,,Brass and Brozne finishes subject to extended lead times*




Orientation Indexing

Orientation indexing is not available with this accessory holder, please align accessories by eye. Ensure that discs are installed with their textured side facing inwards towards LED.



Wallwash Fixture Angle

For optimum performance, the fixture should be angled at approx. 35° from the vertical plane.




Wallwash Positioning and Pitch

Wallwash fixtures should be positioned one-third of the ceiling height away from the wall and spaced apart by the same distance.

plus+

WALLWASH PHOTOMETRY




Solo 08 Plus

+



1110-GLR-01-AL

+





HKFD-30-WAS-1

- Recommended max. wall height is 1.00m / 3.28 ft
- Recommended set back and fixture spacing is 0.33m / 1.08 ft
- Recommended base optics are Medium 24° or Wide 36°
- The Wallwash Disc **HKFD-30-WAS-1** can only be used in combination with the Glare Guard Accessory Holder **1110-GLR-XX-XX**
- Follow the set back and fixture spacing rules outlined on page 10 - results may vary depending on your application

Base Optic	Narrow (17°)
Distribution Angle	22° x 49°
Delivered Flux	300 lm
Peak Intensity	751 Cd
Efficiency	50 lm/W
Efficiency Multiplier	x 0.74










3x Fixtures | 1.00m : 0.33m : 0.33m | 35° Tilt

Base Optic	Medium (24°)
Distribution Angle	27° x 51°
Delivered Flux	309 lm
Peak Intensity	628 Cd
Efficiency	51.5 lm/W
Efficiency Multiplier	x 0.70










3x Fixtures | 1.00m : 0.33m : 0.33m | 35° Tilt

Base Optic	Wide (35°)
Distribution Angle	37° x 55°
Delivered Flux	310 lm
Peak Intensity	472 Cd
Efficiency	51.6 lm/W
Efficiency Multiplier	x 0.67









3x Fixtures | 1.00m : 0.33m : 0.33m | 35° Tilt

Base Optic	Very Wide (50°)
Distribution Angle	46° x 58°
Delivered Flux	228 lm
Peak Intensity	276 Cd
Efficiency	38 lm/W
Efficiency Multiplier	x 0.55







3x Fixtures | 1.00m : 0.33m : 0.33m | 35° Tilt

Digital photometric files available as .LDT format.
Contact your sales rep or visit **www.luminii.com** for more information.

SNOOT ACCESSORY HOLDER




The Single Accessory Holder (sold separately) enhances the Solo 08's optical accessory capacity while adding decorative trim in a variety of complementary finishes. Its snap-in, snap-out mechanism is completely tool-free, making on-site adjustments simple and ensuring the holder fits flush with the snoot's front edge.

Accessory Diameter	Ø30 mm | 1.18"
Capacity	3.2 mm | 0.12" Max. Thickness
Orientation Index	No
Weight	Aluminum 60g | Brass 170g

Ordering Codes

Black	1110-HOL-01-BK	**Polished Brass ***	1110-HOL-02-PB
Traffic White	1110-HOL-01-TW	**Brushed Brass ***	1110-HOL-02-SB
Brushed Aluminium	1110-HOL-01-AL	**Rubbed Bronze ***	1110-HOL-02-RB



Optical accessories ordered separately


** N.B. - Custom RAL,,Brass and Brozne finishes subject to extended lead times*

Ø25MM LINEAR SPREAD LENS



1110-HOL-XX-XX

+



HKFD-25-LIN-1

- The Linear Spread Lens **HKFD-25-LIN-1** is a micoprismatic PMMA lens that can be used to create asymmetric linear beam effects
- For best performance, use in conjunction with the Snoot Accessory Holder **1110-HOL-XX-XX**
- Using narrower base optics will produce a longer, thinner beam
- The beam is spread widest perpendicular to the disc's vertical stripes (see *fig. 1*)








fig. 1



plus+

	Narrow (17°)	Medium (24°)	Wide (35°)	Very Wide (50°)
				
Distribution Angle	18° x 51°	23° x 53°	33° x 57°	46° x 63°
Delivered Flux	366 lm	380 lm	398 lm	334 lm
Peak Intensity	1,214 Cd	957 Cd	649 Cd	367 Cd
Efficiency	61.0 lm/W	63.3 lm/W	66.3 lm/W	61.1 lm/W
Efficiency Multiplier	x 0.90	x 0.86	x 0.86	x 0.80





OPTICS


There are 4 interchangeable optics, cross reference the molded ID on the optic for beam option.

Optic	Optic	Optic	Optic
			
Narrow TIR Optic	**Medium TIR Optic**	**Wide TIR Optic**	**Very Wide TIR Optic**
Molded ID 15 | FWHM 17	Molded ID 24 | FWHM 24	Molded ID 36 | FWHM 35	Molded ID 50 | FWHM 35
Order Code	**Order Code**	**Order Code**	**Order Code**
HKHG-25-15-PMMA	**HKHG-25-24-PMMA**	**HKHG-25-36-PMMA**	**HKHG-25-50-PMMA**

ACCESSORIES

This product can hold 2 x accessories within the integrated holder. To accommodate additional accessories please contact our sales team. Accessories are pre-installed unless otherwise requested.

Glare Control	Beam Shaping	Beam Shaping	Colour Change	Colour Change
				
Honeycomb Louver	**Softening Lens**	**Linear Lens**	**1/4 CTO**	**Custom Colour Filter**
W25xH3.2mm | W0.98xH0.13"	W25xH1.5mm | W0.98xH0.06"	W25xH1.5mm | W0.98xH0.06"	W25xH1.8mm | W0.98xH0.07"	W25xH1.8mm | W0.98xH0.07"
Order Code	**Order Code**	**Order Code**	**Order Code**	**Order Code**
995-25-BK	**HKFD-25-SMO-1**	**HKFD-25-LIN-1**	**997-1/4CTO-25**	**Contact Sales Rep**



Included with luminaire