




Finish Options



Black Painted




White Painted

Features

- Flawless beam quality from a unique micro-linear form factor
- Narrow 15° TIR native beam is aimable +/- 30°
- Louvers available for 15°, 30°, and 60° beams
- Snap-on optics available to easily adjust beam angle in the field
- For ceiling thicknesses from 0.5" up to 1.25"
- LED Module is field serviceable from below the ceiling.
- 24VDC Class 2 and IP40 rated for indoor damp locations
- Wall Wash optic provides even illumination starting from the top of the wall to the bottom
- Wall Wash recommended spacing is 2ft from the wall and 2ft on-center
- Fixture is IC rated and does not require a housing or pan.
- Airtight rated with optional junction box or new construction housing.



Product Dimensions



Technical Information

TYPE	Stenos			OPTIC	TRANSMISSION
LENGTH OPTIONS (15° OPTIC)	3	5	12	15	100%
Lumen Output (3000K)	274 lm	546 lm	1323 lm	LV15	60%
Beam Spread (FWHM)	14°	14°	14°	LV30	65%
Peak Intensity (CBCP)	1612 cd	3288 cd	8541 cd	LV60	50%
Power Consumption	2.8 W	5.4 W	13.5 W	WW	47%
Efficacy	98 lm/W	101 lm/W	98 lm/W	LU	35%
Aesthetic	Regressed Baffle	Regressed Baffle	Regressed Baffle	EL	81%

CCT	Multiplier (reference - 3000K)	TM-30			
		CRI	R _f	R _g	R ₉
2700K	0.96	93	93	98	56
3000K	1.00	94	91	97	60
3500K	1.07	94	92	99	63
4000K	1.11	92	91	99	59

Ordering Code | Directional Module

MODEL	LENGTH	CCT	OUTPUT	OPTIC	FINISH
SLD - Stenos Trimless Linear Downlight	3 - 2.9" 5 - 5.3" 12 - 12.36"	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	SO - Standard	15 - 15° Optic LV15 - 15° Louver ¹ LV30 - 30° Louver and Optic LV60 - 60° Louver and Optic WW - Wall Wash Optic ² LU - 15° Bullseye Louver ³ EL - 15°x 45° Elliptical Lens ⁴	BK - Black

1 - LV15° Louver reduces glare while maintaining 90% of CBCP when compared to standard 15° optic
2 - WW Wall Wash not available with the 3inch option.
3 - LU Bullseye Louver reduces glare while maintaining 75% of CBCP.
4 - Only available in BK Black.




Ordering Code | Accessories

MODEL	ACCESSORY	LENGTH	FINISH
SAC - Stenos Accessory	LV15 - 15° Louver LV30 - 30° Louver and Optic LV60 - 60° Louver and Optic WW - Wall Wash Optic ² LU - 15° Bullseye Louver ¹ EL - 15°x 45° Elliptical Lens ¹	3 - 2.9" 5 - 5.3" 12 - 12.36"	BK - Black WH - White


1 - WW Wall Wash, LU Bullseye Louver, and EL Elliptical Lens only available in BK Black.
2 - WW Wall Wash not available with the 3inch option.

Product Dimensions

SLD-3






Downlight without Louver




Downlight with Louver

SLD-5







Downlight without Louver




Downlight with Louver

SLD-12





Downlight without Louver





Downlight with Louver

Photometry SLD-3




SLD-3-30K-SO-LV30-BK/WH






SLD-3-30K-SO-LV60-BK/WH



SLD-3-30K-SO-EL-BK/WH




SLD-3-30K-SO-LU-BK/WH




Photometry SLD-5


SLD-5-30K-SO-15-BK/WH




SLD-5-30K-SO-LV15-BK/WH



SLD-5-30K-SO-LV30-BK/WH





SLD-5-30K-SO-LV60-BK/WH






Photometry SLD-5


SLD-5-30K-SO-WW-BK/WH



SLD-5-30K-SO-EL-BK/WH





SLD-5-30K-SO-LU-BK/WH





Photometry SLD-12



SLD-12-30K-SO-15-BK/WH





SLD-12-30K-SO-LV15-BK/WH



SLD-12-30K-SO-LV30-BK/WH





SLD-12-30K-SO-LV60-BK/WH






Photometry SLD-12



SLD-12-30K-SO-WW-BK/WH



SLD-12-30K-SO-EL-BK/WH




SLD-12-30K-SO-LU-BK/WH



TM-30-15-Data

27K CCT

Color Vector Graphic


Test —
Reference —

Graphic Shifts (%)

Hue Bin	Rf	Chroma	Hue
1	89.9	-5.0%	0.1%
2	92.9	-3.1%	1.7%
3	93.7	-1.9%	2.2%
4	96.3	-2.2%	-0.2%
5	96.2	-1.7%	1.5%
6	96.3	-0.5%	1.1%
7	95.4	-2.6%	-0.3%
8	96.7	0.4%	1.8%
9	96.1	-1.0%	1.8%
10	94.6	0.0%	2.7%
11	95.6	1.2%	3.1%
12	90.5	3.4%	-2.9%
13	89.1	1.2%	-7.6%
14	86.8	1.0%	-9.8%
15	91.1	-2.8%	-3.6%
16	85.7	-4.5%	-8.6%

30K CCT

Color Vector Graphic


Test —
Reference —

Graphic Shifts (%)

Hue Bin	Rf	Chroma	Hue
1	89.2	-4.7%	1.2%
2	93.0	-2.6%	1.4%
3	94.6	-1.7%	1.3%
4	93.3	-3.5%	-1.7%
5	92.1	-6.1%	0.1%
6	95.0	-2.3%	0.9%
7	89.6	-5.4%	2.6%
8	89.6	-0.9%	3.4%
9	89.6	-0.8%	6.0%
10	89.6	0.8%	6.4%
11	90.5	3.1%	5.0%
12	88.8	5.6%	-3.3%
13	89.1	0.5%	-7.5%
14	86.1	1.5%	-10.1%
15	86.3	-3.3%	-5.3%
16	84.5	-3.1%	-9.9%

35K CCT

Color Vector Graphic


Test —
Reference —

Graphic Shifts (%)

Hue Bin	Rf	Chroma	Hue
1	90.9	-4.5%	-0.4%
2	93.4	-2.7%	1.7%
3	92.4	-1.2%	3.2%
4	95.7	-0.9%	1.2%
5	94.8	-1.6%	1.4%
6	96.9	1.0%	0.4%
7	95.8	-1.5%	-0.3%
8	97.3	-0.6%	0.9%
9	94.9	-1.4%	2.5%
10	91.4	-1.3%	4.7%
11	89.2	2.3%	5.9%
12	90.0	4.0%	0.7%
13	92.5	2.2%	-4.2%
14	88.2	3.6%	-7.8%
15	89.0	-0.5%	-6.6%
16	87.4	-1.6%	-6.6%

40K CCT

Color Vector Graphic

Test —
Reference —


Graphic Shifts (%)

Hue Bin	Rf	Chroma	Hue
1	90.1	-4.9%	-1.3%
2	93.4	-3.0%	1.5%
3	90.0	-2.0%	4.3%
4	94.1	-0.6%	2.7%
5	93.6	-0.2%	2.2%
6	96.4	1.6%	0.2%
7	97.0	-0.7%	-1.1%
8	95.2	-2.0%	-0.5%
9	93.8	-2.7%	2.1%
10	89.7	-3.3%	4.7%
11	87.1	1.6%	7.4%
12	89.0	3.4%	3.8%
13	90.8	4.3%	-3.5%
14	93.2	3.4%	-3.1%
15	87.0	0.8%	-8.6%
16	86.0	-1.0%	-7.9%

Mounting Options (optional)

RMP-3-L-R


Recessed New Construction Mounting Pan,
3" Trimless Linear Downlight



Includes Hanger Bar set (PF-HB-ALL), extendable from 14" to 24".

JB-3L


Junction Box 3" Trimless Linear Downlight



Junction box for wire termination. Airtight Rated

JB-3L-CP


Chicago Plenum Junction Box,
3" Trimless Linear Downlight



Junction box for wire termination and to create a Chicago Plenum rated enclosure. Airtight Rated

RHI-3-L-R


Recessed New Construction Housing, IC Rated,
3" Trimless Linear Downlight



Includes Hanger Bar set (PF-HB-ALL), extendable from 14" to 24". Knock-outs are Ø0.875". Can be used for spray foam insulation. Airtight Rated



RHC-3-L-R

Recessed New Construction Housing, Chicago Plenum Rated
3" Trimless Linear Downlight



Includes Hanger Bar set (PF-HB-ALL), extendable from 14" to 24". Knock-outs are Ø0.875". Can be used for spray foam insulation. Airtight Rated


Components



Mounting Options (optional)

RMP-5-L-R


Recessed New Construction Mounting Pan,
5" Trimless Linear Downlight



Includes Hanger Bar set (PF-HB-ALL), extendable from 14" to 24".

JB-5L


Junction Box 5" Trimless Linear Downlight



Junction box for wire termination. Airtight Rated

JB-5L-CP


Chicago Plenum Junction Box,
5" Trimless Linear Downlight



Junction box for wire termination and to create a Chicago Plenum rated enclosure. Airtight Rated

RHI-5-L-R


Recessed New Construction Housing, IC Rated,
5" Trimless Linear Downlight



Includes Hanger Bar set (PF-HB-ALL), extendable from 14" to 24". Knock-outs are Ø0.875". Can be used for spray foam insulation. Airtight Rated



RHC-5-L-R

Recessed New Construction Housing, Chicago Plenum Rated
5" Trimless Linear Downlight




Includes Hanger Bar set (PF-HB-ALL), extendable from 14" to 24". Knock-outs are Ø0.875". Can be used for spray foam insulation. Airtight Rated

Components




Mounting Options (optional)

RMP-12-L-R
Recessed New Construction Mounting Pan,
12" Trimless Linear Downlight




Includes Hanger Bar set (PF-HB-ALL), extendable from 14" to 24".

JB-12L
Junction Box 12" Trimless Linear Downlight





Junction box for wire termination. Airtight Rated

JB-12L-CP
Chicago Plenum Junction Box,
12" Trimless Linear Downlight






Junction box for wire termination and to create a Chicago Plenum rated enclosure. Airtight Rated

Components



Field Serviceability



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White


Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)	30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.

0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart

MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50"	7.40"	8.66"	11.85"
Width	3.73"	3.73"	3.73"	4.32"
Depth	1.61"	1.61"	1.61"	1.81"




For use with Static White


Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"



PS-010V-LIN/LOG-D-3X96




For use with Static White

Ordering Code - Athena 0-10V LED Driver

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS - Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D - Dry	96 - 96 Watts	24 - 24 VDC	AWNDR - Athena

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"



Power Supplies


See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DALI2-DT6-DALI2 DT6 (0.1%)	D-Dry	96-96 Watts	24-24 VDC

Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"




For use with Static White


Ordering Code - DALI Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DALI-DALI (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC

Model	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"



PS-DALI-D-3X96-24




For use with Static White

Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC


MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DMX-DMX (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

ZONAL CONTROL POWER SUPPLIES.
CONTROL MULTIPLE TAPES/ZONES USING DMX CHANNELS.



PS-DMX-D-3X96-24




Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"



Luminii is a Lutron OEM Advantage Partner


Lutron Power Supplies 1%

MODEL

L3DA4U1UKL-CV240

HiLume™ 1% EcoSystem Voltage LED driver
40W max

MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"



Luminii is a Lutron OEM Advantage Partner


Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

HiLume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™
96W max

MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"




Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC



MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"



Luminii is a Lutron OEM Advantage Partner


Lutron Power Supplies 1%

MODEL

L3DA4U1UKL-CV240

HiLume™ 1% EcoSystem Voltage LED driver
40W max

MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"



Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

HiLume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™
96W max

MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"

