


Features

- Fixtures made to order up to 144" and can be linked together for a continuous run
- Suitable for wall mount applications
- Available with long throw and tall throw reflectors
- Class 2 listed for damp locations
- Average Life (L70): 50,000hrs
- Vibrant Color options offer premium quality and vibrant colors with R9 values up to 98
- High Efficacy options offer best in class output and efficacy with over 1240 lm/ft and over 146 lm/W
- Proprietary strong bond solder method handles up to 50 lbs of pull force on wire leads and connectors
- 7 Year warranty



Finish Options

- Paint Ready
- Black powder coated
- White powder coated



Technical Information

TYPE	Vibrant Color VC72						
OUTPUT OPTIONS	VC72VLO	VC72LO	VC72SO	VC72MO	VC72HO	VC72VHO	VC72XHO
Lumens Output (3000K) (with a LT Reflector)	116 lm/ft	297 lm/ft	395 lm/ft	522 lm/ft	631 lm/ft	840 lm/ft	1002 lm/ft
Average Power Consumption (for a 4' section)	1.1 W/ft	2.8 W/ft	3.7 W/ft	4.9 W/ft	5.9 W/ft	7.9 W/ft	9.9 W/ft
Efficacy	105 lm/W	106 lm/W	107 lm/W	107 lm/W	107 lm/W	106 lm/W	101 lm/W
Max Run Length (in series)	56.9 ft	32 ft	28 ft	24 ft	21 ft	18 ft	12 ft
Ambient Operating Temperature Range*	-4°F - 122°F (-20°C - 50°C)						

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

TYPE	High Efficacy HE64						
OUTPUT OPTIONS	HE64VLO	HE64LO	HE64SO	HE64MO	HE64HO	HE64VHO	HE64XHO
Lumens Output (3000K) (with a LT Reflector)	129 lm/ft	278 lm/ft	399 lm/ft	531 lm/ft	754 lm/ft	1034 lm/ft	1245 lm/ft
Average Power Consumption (for a 4' section)	1 W/ft	1.9 W/ft	2.9 W/ft	3.8 W/ft	5.6 W/ft	7.1 W/ft	8.9 W/ft
Efficacy	129 lm/W	146 lm/W	138 lm/W	140 lm/W	135 lm/W	146 lm/W	140 lm/W
Max Run Length (in series)	90 ft	55 ft	34.9 ft	26 ft	17 ft	13 ft	10.3 ft
Ambient Operating Temperature Range*	-4°F - 122°F (-20°C - 50°C)						

*Ambient Operating Temperature Range to maintain L70 of 50k+ hours in normal mounting conditions for the fixture. Exceeding Ambient Operating Temperature Range may result in decreased life/output. Consult Technical Support for specific inquiries.

CCT	Multiplier (ref. - 30K)	TM-30			
		CRI	R _f	R _g	R ₉
1800K	0.50	95	94	99	86
2200K	0.66	96	94	101	95
2400K	0.90	98	96	101	91
2700K	0.93	98	96	102	93
3000K	1.00	97	94	104	99
3500K	1.04	96	94	105	97
4100K	1.05	97	95	104	96

CCT	Multiplier (ref. - 30K)	TM-30			
		CRI	R _f	R _g	R ₉
2200K	0.74	94	91	96	65
2400K	0.87	94	92	97	56
2700K	0.97	94	92	100	57
3000K	1.00	93	91	99	54
3500K	1.01	95	91	99	62
4000K	1.04	95	91	99	68


Ordering Code

MODEL	LENGTH ¹	OUTPUT ²	CCT	REFLECTOR	FINISH ²	LEFT END CAP	RIGHT END CAP	POWER FEED LEFT END ³	POWER FEED RIGHT END ³	POWER SUPPLY TYPE
MREC - mCove Rectangle	12"-144" 1" increments	VC72VLO - Very Low VC72LO - Low VC72SO - Standard VC72MO - Medium VC72HO - High VC72VHO - Very High VC72XHO - Extreme	18K - 1800K 22K - 2200K 24K - 2400K 27K - 2700K 30K - 3000K 35K - 3500K 41K - 4100K	LT - Long Throw TT - Tall Throw	BASE PR - Paint Ready POWDER COAT BK - Black WH - White	LE - Endcap LN - No Endcap LE - Endcap LN - No Endcap	RE - Endcap RN - No Endcap RE - Endcap RN - No Endcap	LPB - Back DC Feed LPB - Back DC Feed LNPF - No Power Feed LNPF - No Power Feed	RPB - Back DC Feed RPNPF - No Power Feed RPB - Back DC Feed RPNPF - No Power Feed	R - Remote Power Supply
	12"-144" 2" increments	HE64VLO - Very Low HE64LO - Low HE64SO - Standard HE64MO - Medium HE64HO - High HE64VHO - Very High HE64XHO - Max	22K - 2200K 24K - 2400K 27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K			LE - Endcap LN - No Endcap LNJ - No Endcap, W/ Jumper LNJ - No Endcap, W/ Jumper	RNJ - No Endcap, W/ Jumper RNJ - No Endcap, W/ Jumper	LPB - Back DC Feed LNPF - No Power Feed LNPF - No Power Feed LNPF - No Power Feed	RPNPF - No Power Feed RPNPF - No Power Feed RPB - Back DC Feed RPNPF - No Power Feed	


1 - Custom lengths and increments are available, please consult Inside Sales with specific request.
 2 - Title 24 JA8 achievable depending on Output, CCT, and Lens selections. See multiplier charts to calculate specific efficacies.
 3 - Plenum Rated Wire leads are 72" long.
 4 - NOTE: Cannot pair LNPF-RNPF without jumper connections - either [LN] or [RN] must be selected to allow for LNPF-RNPF to be chosen.
 6 - NOTE: Cannot have a power feed (to other fixture or power supply) on the same end as a jumper wire connection.

mCove Rectangle Corner Options

MREC-OC
Outer Corner



MREC-IC
Inner Corner



Vibrant Color	Actual Length		Total Wattage							
	Corner Type	A	B	VC72VLO	VC72LO	VC72SO	VC72MO	VC72HO	VC72VHO	VC72XHO
Inner (MREC-IC)		14 9/16"	14 9/16"	2.2	5.7	7.4	9.9	12.7	16.0	21.4
Outer (MREC-OC)		9 13/16"	9 13/16"	2.2	5.7	7.4	9.9	12.7	16.0	21.4


High Efficacy	Actual Length		Total Wattage							
	Corner Type	A	B	HE64VLO	HE64LO	HE64SO	HE64MO	HE64HO	HE64VHO	HE64XHO
Inner (MREC-IC)		14 12/16"	14 12/16"	2.0	3.9	6.0	8.2	11.8	14.8	19.0
Outer (MREC-OC)		10 2/16"	10 2/16"	2.0	3.9	6.0	8.2	11.8	14.8	19.0

Ordering Code

MODEL	CORNER	ANGLE	OUTPUT ²	CCT	REFLECTOR	FINISH ³	LEFT END CAP	RIGHT END CAP	POWER FEED LEFT END ⁵	POWER FEED RIGHT END ⁵	POWER SUPPLY TYPE
MREC-mCove Rectangle	IC- Inner Corner OC- Outer Corner	90-90° Corner C- Custom Angle Corner	VC72VLO-Very Low VC72LO-Low VC72SO-Standard VC72MO-Medium VC72HO-High VC72VHO-Very High VC72XHO-Extreme	18K-1800K 22K-2200K 24K-2400K 27K-2700K 30K-3000K 35K-3500K 41K-4100K	LT-Long Throw TT-Tall Throw	BASE PR- Paint Ready POWDER COAT BK-Black WH-White	LE-Endcap LN-No Endcap	RE-Endcap RN-No Endcap	LPB-Back DC Feed LNPF-No Power Feed	RPB-Back DC Feed RNPF-No Power Feed	R-Remote Power Supply
			HE64VLO-Very Low HE64LO-Low HE64SO-Standard HE64MO-Medium HE64HO-High HE64VHO-Very High HE64XHO-Max	22K-2200K 24K-2400K 27K-2700K 30K-3000K 35K-3500K 40K-4000K			LE-Endcap LN-No Endcap	RNJ-No Endcap, W/Jumper	LPB-Back DC Feed LNPF-No Power Feed	RNPF-No Power Feed	
							LNJ-No Endcap, W/Jumper	RE-Endcap RN-No Endcap	LNPF-No Power Feed	RPB-Back DC Feed RNPF-No Power Feed	
							LNJ-No Endcap, W/Jumper	RNJ-No Endcap W/Jumper	LNPF-No Power Feed	RNPF-No Power Feed	


1 - Custom lengths and increments are available, please consult Inside Sales with specific request.
 2 - Title 24 JA8 achievable depending on Output, CCT, and Lens selections. See multiplier charts to calculate specific efficacies.
 3 - Plenum Rated Wire leads are 72" long.
 4 - NOTE: Cannot pair LNPF-RNPF without jumper connections - either [LN] or [RN] must be selected to allow for LNPF-RNPF to be chosen.
 5 - NOTE: Cannot pair LPB-RPB together. Only one power feed per fixture/section on mCove
 6 - NOTE: Cannot have a power feed on the same end as a jumper wire connection.

Power feed options for straight sections




Power feed options for corner fixtures


MREC-OC-90-XX-LPB-RNPF
Outside Corner, back left powerfeed




MREC-OC-90-XX-LNPF-RPB
Outside Corner, back right powerfeed









MREC-IC-90-XX-LPB-RNPF
Inside Corner, back left powerfeed





MREC-IC-90-XX-LNPF-RPB
Inside Corner, back right powerfeed



Product Dimensions



Wall Mount also acts as mechanical joiner to connect two fixtures



Finish Options

- Finish options are available in a wide variety, allowing for complete customization of style and aesthetic.
- Non Base finishes may have extended lead times and price adder.
- Custom RALs are available, please consult Inside Sales with specific request.

Paint Ready Base



Black Powder Coat



White Powder Coat




Paint Ready is designed for easy field painting and custom color matching


Black is a true deep black with a glossy finish.

White is a polar bright white and field paintable.

Sample Layout of Power Feed



Layout example



Light Transmission and Dotting

Output Options	Lens/Accessory							
	Long Throw Reflector				Tall Throw Reflector			
Dimming Level	100%	50%	10%	1%	100%	50%	10%	1%
VC72VLO	CD	CD	CD	CD	CD	CD	CD	CD
VC72LO	CD	CD	CD	CD	CD	CD	CD	CD
VC72SO	CD	CD	CD	CD	CD	CD	CD	CD
VC72MO	CD	CD	CD	CD	CD	CD	CD	CD
VC72HO	CD	CD	CD	CD	CD	CD	CD	CD
VC72VHO	CD	CD	CD	CD	CD	CD	CD	CD
VC72XHO	CD	CD	CD	CD	CD	CD	CD	CD
HE64VLO	CD	CD	CD	CD	CD	CD	CD	CD
HE64LO	CD	CD	CD	CD	CD	CD	CD	CD
HE64SO	CD	CD	CD	CD	CD	CD	CD	CD
HE64MO	CD	CD	CD	CD	CD	CD	CD	CD
HE64HO	CD	CD	CD	CD	CD	CD	CD	CD
HE64VHO	CD	CD	CD	CD	CD	CD	CD	CD
HE64XHO	CD	CD	CD	CD	CD	CD	CD	CD
Transmission Percentage	100%				100%			



CD - Clear Dotting
SD - Slight Dotting
ND - No Dotting

Use complete Dotting Chart Tool online for more dotting information




Fixture uses indirect lighting, will have clear dotting if looking from above the fixture

Accessory Options

LVSP-4T-BK


Low Voltage, 4 Terminal Splice Box, Black, IP20



Photometry


MREC-48-VC72VHO-30K-IT

MCove Rectangle, 4ft, VHO, 3000K, Tall Throw Lens



Zonal Lumen Summary 3000K


Zone	Lumen	% Fixture
0-30	222	26%
0-40	369	44%
0-60	667	79%
0-90	832	99%
Total 0-180	840	100%



UNIT: CD
C0/180
C90/270

MREC-48-VC72VHO-30K-LT

MCove Rectangle, 4ft, VHO, 3000K, Long Throw Lens



Zonal Lumen Summary 3000K

Zone	Lumen	% Fixture
0-30	194	23%
0-40	324	39%
0-60	618	74%
0-90	832	99%
Total 0-180	840	100%



UNIT: CD
C0/180
C90/270

Power Consumption

Please visit the link/QR code below to access the Luminii Power Consumption Chart tool on our website.

There you will be able to select your fixture, output, and desired power feed to get a full power consumption table.



I'm also click-able

Desired Nominal Length: _____

Desired Output: _____

Desired CCT: _____

Voltage Drop Calculator

The below chart assumes nominal voltage of 24 Volts and a Voltage Drop Allowance of 3% through the wire

Wattage [W]	Maximum Wire Length From Power Supply to Start of Run [ft]						
	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG
5	1088.2	684.4	430.3	270.6	170.2	107.1	67.3
10	544.1	342.2	215.1	135.3	85.1	53.5	33.7
15	362.7	228.1	143.4	90.2	56.7	35.7	22.4
20	272.0	171.1	107.6	67.7	42.6	26.8	16.8
25	217.6	136.9	86.1	54.1	34.0	21.4	13.5
30	181.4	114.1	71.7	45.1	28.4	17.8	11.2
35	155.5	97.8	61.5	38.7	24.3	15.3	9.6
40	136.0	85.5	53.8	33.8	21.3	13.4	8.4
45	120.9	76.0	47.8	30.1	18.9	11.9	7.5
50	108.8	68.4	43.0	27.1	17.0	10.7	6.7
55	98.9	62.2	39.1	24.6	15.5	9.7	6.1
60	90.7	57.0	35.9	22.6	14.2	8.9	5.6
65	83.7	52.6	33.1	20.8	13.1	8.2	5.2
70	77.7	48.9	30.7	19.3	12.2	7.6	4.8
75	72.5	45.6	28.7	18.0	11.3	7.1	4.5
80	68.0	42.8	26.9	16.9	10.6	6.7	4.2
85	64.0	40.3	25.3	15.9	10.0	6.3	4.0
90	60.5	38.0	23.9	15.0	9.5	5.9	3.7
96	56.7	35.6	22.4	14.1	8.9	5.6	3.5

Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White



Ordering Code - Universal Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	UNI - 0-10V Dimming (0.1%), Phase Dimming (0.1%)	30 - 30 Watts 60 - 60 Watts 96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC

Compatibility: View a complete list of compatible dimmers on the PS-UNI product page.

0-10V - 0.1% dimming
MLV/ELV/TRIAC - 0.1% dimming, consult dimming compatibility chart

MODELS	PS-UNI-30W	PS-UNI-60W	PS-UNI-96W	PS-UNI-3X96W
Length	6.50"	7.40"	8.66"	11.85"
Width	3.73"	3.73"	3.73"	4.32"
Depth	1.61"	1.61"	1.61"	1.81"





For use with Static White

Ordering Code - 0-10V Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	010V-LIN-0-10V Dimming (0.1%), Linear 010V-LOG-0-10V Dimming (0.1%), Logarithmic	D-Dry	96 - 96 Watts 3x96 - 3x96 Watts	24 - 24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.45"




Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.

For use with Static White

Ordering Code - Athena 0-10V LED Driver

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT	FEATURE
PS-Power Supply, 120-277VAC	010V-LIN - 0-10V Dimming (0.1%), Linear 010V-LOG - 0-10V Dimming (0.1%), Logarithmic	D-Dry	96-96 Watts	24 - 24 VDC	AWN-R-Athena




MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"

For use with Static White

Ordering Code - DALI 2 Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DALI2-DT6 - DALI2 DT6 (0.1%)	D-Dry	96-96 Watts	24 - 24 VDC




Model	96W
Length	14.40"
Width	5.20"
Depth	2.60"


For use with Static White

Ordering Code - DALI Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DALI-DALI (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24 - 24 VDC



Model	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.



For use with Static White

Ordering Code - DMX Dimming Power Supplies 0.1% 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	DMX-DMX (0.1%)	D-Dry	96-96 Watts 3x96-3x96 Watts	24-24 VDC

MODELS	96W	3X96
Length	14.40"	15.00"
Width	5.20"	6.62"
Depth	2.60"	4.56"

ZONAL CONTROL POWER SUPPLIES.
CONTROL MULTIPLE TAPES/ZONES USING DMX CHANNELS.




For use with Static White

Ordering Code - Non-Dimming Power Supply, 120VAC - 277VAC

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS-Power Supply, 120-277VAC	ND-Non Dimming	D-Dry	96-96 Watts	24-24 VDC

MODELS	96W
Length	14.40"
Width	5.20"
Depth	2.60"




For use with Static White

Ordering Code - In-Ground Power Supplies

MODEL	INPUT CONTROL	ENVIRONMENT	WATTAGE	OUTPUT
PS120-Power Supply, 120VAC PS240-Power Supply, 240VAC PS277-Power Supply, 277VAC	ELV-ELV Dimming (1%)	IG-In Ground	2X96-2X96 Watts	24-24 VDC

MODELS	2X96W
Length	8.40"
Width	8.30"
Depth	8.10"



Power Supplies

See Power Supply instructions and spec sheet for wiring information. For a complete list of compatible dimmers, see Compatible Dimming Chart on the Resources page.



Luminii is a Lutron OEM Advantage Partner


Lutron Power Supplies 1%

MODEL

L3DA4U1UKL-CV240

HiLume™ 1% EcoSystem Voltage LED driver 40W max

MODELS	L3DA4U1UKL-CV240
Length	4.98"
Width	4.00"
Depth	2.62"



Luminii is a Lutron OEM Advantage Partner

Lutron Power Supplies 0.1%

MODEL

L3D0-96W24V-U

HiLume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade-to-Black™ 96W max

MODELS	L3D0
Length	10.50"
Width	5.50"
Depth	2.00"

